## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:-011-23412593

No. F6/DFS/MS/GH/2014/ MD 2) 1619

E-mail ID: cfohq.dlfire@nic.in
Dated 22/12/19

## **FIRE SAFETY CERTIFICATE**

Certified that the M/S Gush International located at 626,627,631 (Part) Bowil Chowk, Pahar Ganj, New Delhi comprises of Ground + three Upper floors having 21 guest room Ground floor has (reception + 03 guest room), 1st floor to 3rd floor has (06 guest rooms at each floor), was granted NOC by this department vide letter No.F6/DFS/MS/GH/2011/2721 dated 25-10-2011. The premises was re-inspected by the officer concerned of this department on 14-12-2014 in the presence of Mr. Jitender Kumar Chawla (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 22 121 ... at New Delhi by.

(**Dr. G.C.Misra**) Chief Fire Officer Delhi Fire Service Ph = 011-23414333

Copy to:-

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi – 110049 w.r.t. letter No 41455/Joint. C.P./Lic. (H) dated New Delhi 03-11-2014.

2. Mr. Jitender Kumar Chawala (Owner) M/S Gush International located at 626,627,631 (Part) Bowil Chowk, Pahar Gani, New Delhi

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

2. Any loss of life or property due to non-functional fire safety measures shall be at the

responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of

unauthorized construction, if any.

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

## **INSPECTION REPORT**

1. Name & address of the building

: M/S Gush International located at 626,627,631 (Part) Bowli

Chowk, PaharGanj, New Delhi.

2. Type of Occupancy

: Residential Building Gr. + 3 upper floors (total 21 guest room)

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/MS/DFS/GH/2011/2721 dated 25/10/2011

5. Fire Safety directives Letter No. : NA

6. Date of inspection

: 14/12/2014

7 Name of the Inspecting Officer

: Sh. M. K. Sharma (ADO/CC)

8 Name and designation of Officer

from the building side

: Sh. Jitender Kumar (Owner)

9 Year of Construction

: 2009

10. Applicant's letter No.

: 41455/Joint. C.P./Lic.(H) dated, New Delhi the 03/11/2014.

MR

Minimum standards on fire prevention S No Old Case Existing Provided at site Remarks and fire safety U/R 33 Requirements (PSS Area) MR/NMR (PSS Area) 1. Access of building Road width NA 02 Mtr. MR Gate width NA NA NA Width of internal road NA NA NA Number, width, Type & Arrangements of exits 2. a. Number of staircases • Upper floors 1 Nos. 1 Nos. MR • Basements NA NA NA b. Width of staircases • Upper floors 0.80 Mtr. 1.25 Mtr. Old case MR Basements NA NA NA c. Protection of exits • Fire check door NA NA NA Pressurization NA NA NA d. No of continuous staircase to terrace 1 No. 1 No.

	e. Width Of Corridor	NA	NA	NA		
	f. Door Size					
2		My OIMIT.	O   Mtr.	MR		
3.	Compartmentation					
	Fire check door	NA	NA	NA		
	Sealing of electrical shafts	NA	NA	NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	• Fire Dampers	NA	NA	NA		
4	Smoke managements System					
	• Basements	NA	NA	NA		
	• Upper floors	12 ACPH	NATURAL	MR		
5	Fire Extinguishers					
	Total numbers	08 Nos.	08 Nos.	MR		
	• Types	ABC,CO <sub>2</sub> , Wco <sub>2</sub> ,	ABC,CO <sub>2</sub> , Wco <sub>2</sub>	MR		
	IS marking	Required	Provided	MR		
6	First - Aid Hose Reels					
	Total numbers on each floor	01	01	MR		
	<ul> <li>Length of hose reel hose</li> </ul>	30 Mtr.	30 Mtr.	MR		
	Nozzle diameter	05 MM	05 MM	MR		
7	Automatic fire detection and alarming s	and the second s	03 141141	IVIK		
	Type of detectors	NA	NA	NT A		
	<ul> <li>Location of Main Panel</li> </ul>	NA	NA NA	NA		
	Location of Repeater Panel	NA		NA		
	Alternate source of power	NA	NA	NA		
	Hooters' Location		NA	NA		
8	MOEFA	NA	NA	NA		
9		Required	Provided	MR		
10	Public Address System	Required	Provided	MR		
10	Automatic Sprinkler					
	Basements	NA	NA	NA		
	• Upper Floor	NA	NA	NA		
1.4	Sprinkler above false ceiling	NA	NA	NA		
11	Internal Hydrants					
	Size of riser/down- comer	NA	NA	NA		
	<ul> <li>Number of hydrants per floor</li> </ul>	NA	NA	NA		

W

			DIA	NA	NA
	•	Hose Box	NA	NA	TNLY
2	Yard H	lydrants			NT A
	•	Total number of hydrants	NA	NA	NA
	•	Hose Box	NA	NA	NA
3	Pumpi	ng Arrangements			
	0	Ground Level			
	•	Discharge of main pump	NA	NA	NA
	•	Head of main pump	NA	NA	NA
	•	Number of main pumps	NA	NA	NA
	•	Jockey pump out put	NA	NA	NA
	•	Jockey pump head	NA	NA	NA
		Standby Pump out put	NA	NA	NA
	•	Standby Pump Head	NA	NA	NA
		auto Staring/Manual stopping	NA	NA	NA
	•	Pump House Access	NA	NA	NA
		Terrace level			
	•	Discharge of pump	225 LPM	225 LPM Old case	MR
		Head of the pump	30 Mtr.	30 Mtr.	MR
		Power supply	Required	Provided	MR
		Auto starting of pump	Required	Provided	MR
14	Capti	ive water Storage for fire fighting	(4)		
	•	Under ground tank capacity	NA	NA	NA
	•	Draw of connection	NA	NA ,	NA
	•	Fire service inlet	Required	Provided	MR
		Access to tank	NA	NA	NA
	•	Overhead Tank capacity	25,00 Ltr.	> 2,500 Ltr. Old case	MR
15	Exit	Signage	Required	Provided	MR
16		vision of Lifts			
		Pressurization of Lift Shaft	. NA	NA	NA
* 59 K S		Pressurization of lift lobby	NA	NA	NA
		Communication in lift Car	NA	NA	NA
20	Re (	Fireman's Grounding Switch	NA	NA	NA
		• Lift Signage		NA	NA

		NA	NA	NA
	Standby power supply	1117		- 1
	Refuge Area		**	NA
		NA	NA	INA
	Total area	NIA	NA	NA
	• Location	NA		
	Fire control room		2.7.4	NA
	<ul><li>Detector system panel</li><li>Flow Switch Panel</li></ul>	NA	NA	
		NA	NA	NA
			NA	. NA
	<ul><li>PA System Panel</li><li>Batter backup</li><li>Building Floor Plans</li></ul>	NA		NA
		NA	NA	
		NA	NA	NA
			120.0	MR
20	Special Fire Protection Systems for	Required	ABC, Co <sub>2</sub>	
20	Protection of special Risks, if any;			
			-	1.0 1
	The fire protection systems provided in t	he building were rar	ndomly tested, checke	ed and found
	The fire protection systems provided in s			
	functional at the time of inspection.		1 CC and to the section	ation and fire
	In view of the deemed compliance	of the minimum sta	andards of fire preven	.uon and me
	III view of the decired under the ril	les the NOC issued	vide letter no.	Tim Comice

In view of the deemed compliance of the minimum standards of fire prevention and fire

safety measures as required under the rules the NOC issued vide letter no. F6/MS/DFS/GH/2011/2721 dated 25/10/2011 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

> Previous FSC was issued on 2500 liter overhead water tank for fire.

Signature of the Inspecting Officer Designation :- A. D.O. (CC)