GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6 DFS | ms | school | 2014 | MOZ / 1683

Dated: 31/12/14

FIRE SAFETY CERTIFICATE

Certified that the S.R. Capital Public School, Q-Block, Mohan Park, Naveen Shahdara, Delhi-32, comprised of ground floor plus two upper floors was granted Fire Safety Certificate by this department vide Letter No- F6/DFS/MS/2011/2084 dated 25.08.2011. School building was reinspected by the officer concerned of this department on 15.12.2004 in the presence of Vice Principal of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with the circular No. F.16/Estate/CC/Fire safety/2011/3298 to 3398 dated 01.03.11 issued by the Director of Education and found that the building is fit for occupancy Group B "Educational Building" with effect from ...3.1.1.2.19..... renewed for a period of three years, subject to conditions printed overleaf.

Issued on ...3.1./12.../1.4......at New Delhi by

(Dr.G.C.Misra)

Chief Fire Officer

Ph- 011- 23414333

0/0860

To,

The Vice Principal

S.R. Capital Public School, Q-Block, Mohan Park, Naveen Shahdara, Delhi-32 Copy to:-.

The Joint Director of Education

(Land & Estate)

Directorate of Education, Lucknow Road, Delhi -54

CONDITIONS:

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

	INSPEC	TION REPORT		*			
1. Na	ame & address of the building : S.R. C	Capital Public Schoo	l, Q-Block, Mohan Pa	ark,			
		en Shahdara, Delhi		,			
	uilding is comprised of : G+2						
3. Ty	pe of Occupancy : Educa	: Educational					
	pe of Case : Rene	wal					
5. De	etails of Previous FSC : F6/DF	: F6/DFS/MS/2011/2084 Dated 25.08.2011					
6. Fire	e Safety direction letter No : F.16/E		ty/2011/3298 to 339	8			
7. Da	te of Inspection : 15.12.	2014					
8. Name of the Inspecting Officers: : S							
	me of the designation of Officer						
fro	om the building side : Vice P	rincipal					
10. Y	ear of Construction : 1980	Control () Selected					
11. Ap	oplicant's letter No : dated	: dated 26.11.2014					
S.No		fety Requirement	Provided at Site	Remarks			
	requirements as per circular no. 3298		. To vided at Site	MR/NM			
	3398 dated 01.03.11	- C00000		IVIII/IVIV			
1	Access to building						
	Road width	6 m	10 m	MR			
	Gate width	N.A.	N.A.	N.A.			
201	Width of internal road	N.A.	N.A.	N.A.			
2	Number, Width, Type and Arrangemen	CANTENDAM CONTRACTOR C	IV.A.	IV.A.			
	a. Number of Staircases						
	Upper Floor	2 no.	3 no.	MAD			
	Basement	N.A.	N.A.	MR			
	B. Width of Staircases	N.A.	IV.A.	N.A.			
	Upper Floor	1.5 m	1,000,000,000,000	140			
	Basement	N.A.	1m, 0.90m, 1.1m	MR			
	c. Protection of exits		N.A.	N.A.			
	Fire check door	N.A.	N.A.	N.A.			
	Pressurization	N.A.	N.A.	N.A.			
	e. No. of continuous staircases to terrae	N.A.	·N.A.	N.A.			
	g. Width of Corridor	2 no.	2 no.	MR			
	h. Door Size	1.5 m	1.5 m	MR			
3	Compartment	1 m	1 m	MR			
	Compartmentation.						
	Fire check door	N.A.	N.A.	N.A.			
1	Sealing of electrical shafts	N.A.	N.A.	N.A.			
	Fire rating of shaft door	N.A.	N.A.	N.A.			
	Water curtain	N.A.	N.A.	N.A.			
	Fire Dampers	N.A.	N.A.	N.A.			
	Smoke Management System.						
	Basement	30a/c per hour	N.A.	N.A.			
	Upper floor	12a/c per hour	N.A.	N.A.			

5.	Fire Extinguisher					
	Total numbers	6 no.	20 no.	MR		
	types	ABC +CO ₂	ABC +CO ₂	MR		
	IS marking	ISI marked	ISI marked	MR		
6	First-aid-Hose Reels.					
	Total numbers of each floor	01 no.	01 no.	MR		
	Length of hose reel hose	30 m	30 m	MR		
	Nozzle diameter	5 mm	5 mm	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N.A.	N.A.	N.A.		
	Location of main panel	N.A.	N.A.	N.A.		
10	Location of repeater panel	N.A.	N.A.	N.A.		
9	Alternate source of power	N.A.	N.A.	N.A.		
	Hooters	N.A.	N.A.	N.A.		
8	MOEFA	N.A.	N.A.	N.A.		
9	Public address System.	N.A.	Provided	MR		
10	Automatic Sprinkler System.	ACCOUNT #55		2		
	basement	N.A.	N.A.	N.A.		
	upper floor	N.A.	N.A.	N.A.		
	sprinkler above false ceiling	N.A.	N.A.	N.A.		
11	Internal Hydrants					
	size of riser/down-comer	N.A.	100 mm	MR		
	Number of hydrants each floor	N.A.	1 no.	MR		
	Hose box each floor	N.A.	1 no.	MR		
12	Yard Hydrants.					
	Total number of hydrants	N.A.	N.A.	N.A.		
	Hose Box	N.A.	N.A.	N.A.		
13	Pumping Arrangements.					
	Ground Level	N.A.	N.A.	N.A.		
	 Discharge of main Pump 	N.A.	N.A.	N.A.		
	Head of Main Pump	N.A.	N.A.	N.A.		
	Number of main pumps	N.A.	N.A.	N.A.		
	> Jockey pump out put	N.A.	N.A.	N.A.		
	Jockey pump head	N.A.	N.A.	N.A.		
	Standby pump out put	N.A.	N.A.	N.A.		
-	Standby pump Head	N.A.	N.A.	N.A.		
	Auto Starting /Manual stopping	N.A.	N.A.	N.A.		
,	Pump House Access	N.A.	N.A.	N.A.		
20	Terrace Level		1			
	Discharge of pump	450 LPM	450 LPM	MR		
	Head of the Pump	40 m	40 m	MR		
		70 111	10 /11			
	Power supply	Required	Provided	MR		

14	Captive Water Storage for Fire Fighting.					
	Underground tank capacity Draw-off connection	N.A.	N.A.	N.A.		
	Fire service inlet	N.A.	N.A.	N.A.		
	Access to tank	N.A.	N.A.	N.A.		
362	Overhead Tank capacity	N.A.	N.A.	N.A.		
15	Exit Signage.	10,000 Liters	10,000 Liters	MR		
16	Provision of Lifts.	Required	Provided	MR		
	Pressurization of Life Cl. (c.					
	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
	Communication in lift car Firemen's grounding switch Lift Signage	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
7	A	N.A.	N.A.	N.A.		
8	Standby power supply Refuge Area.	N.A.	N.A.	N.A.		
	Total area					
	Location	N.A.	N.A.	N.A.		
9	Fire Control Room	N.A.	N.A.	N.A.		
	The Control Room					
	Detector system panel Flow switch panel	N.A.	N.A.	N.A.		
	PA system panel	N.A.	N.A.	N.A.		
	Batter backup	N.A.	N.A.	N.A.		
	Building Floor Plans	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.		



The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules the FSC issued vide letter no. F6/DFS/MS/2011/2084 dated 25.08.2011 renewal under the circular No. 3298 to 3398 dated 01.03.11 is recommended.

Signature of the Inspecting Officer

Name

Suresh Singh

Designation

ADO (Shah)

DO (EAST) Submitted for approval please.

Wrugh