GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F6/DFS/MS/GH/2015/NDZ/) \

Dated: 02 | 01 | 15

FIRE SAFETY CERTIFICATE

To,

The Joint Commissioner of Police (Lic.) 1st Floor, Police Station, Defence Colony, New Delhi.

Copy to :-

(1) Sh Mange Ram Sharma A-10, Main Road Gazipur, Delhi-96

(2) The Dy Health Officer
East Delhi Municipal Corporation, Health Department,
Shahdara (South) Zone, Karkardooma, Shahdara, Delhi

(Dr.G.C. Misra) Chief Fire Officer Ph.011-23414333

Redus

.Name	& address of the building : Anuj Guest House	se at Ground,1 st & pur, Delhi -96.	& 2 nd floor, Plot no.A	-10,			
) Buildi	ng Comprised of : Basement, groun		per floors.				
3. Type of Occupancy : Residential (Guest House)							
	of Case : New						
	ils of Previous FSC :Nil						
		t IV					
		CIV					
		ngh & ADO Sures	ch Singh				
	e of the Inspecting Officer : DO Virendra Si	ligil & ADO Sules	on Jingn				
	ne of the designation of Officer	arl	The second secon				
1000	the building side : Sh.Anuj (own	er)					
	ar of Construction : 2009	+ CD /I in (II)	dated 17 00 14				
11.App	lication / letter No : 35286-90/Join	nt.C.P./Lic.(H)	ualeu 17.09.14				
	Asia Caraban Superior	NBC Part IV	Provided at Site	Remarks			
SI.No.	Minimum Standards on fire prevention		Provided at Site	Kemarks			
	and fire safety U/R33	Requirement	\				
1	Access to building		40.14	AAD			
	 Road width 	06 Mtrs.	12 Mtrs.	MR			
	Gate width	N/A	N/A	N/A			
	 Width of internal road 	N/A	N/A	N/A			
2	Number, Width, Type and Arrangement of						
	a. Number of Staircases	2					
	Upper Floor	01 No.	03 Nos.	MR			
		02 Nos.	02 Nos.	MR			
	Basement	02 1403.	02 1403.				
	B. Width of Staircases	4.5.4	4 5 84 4 25 84	MR			
	Upper Floor	1.5 M	1.5 M,1.25 M	IVIK			
			& 0.90 M	NAD @			
	Basement	1.25 M	1.25 M	MR			
	c. Protection of exits			3			
	Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	e. No. of continuous staircases to terrace	2 Nos.	2 Nos. 25 1.25M	MR			
	g. Width of Corridor	1.5 M		- MR			
	h. Door Size	1.0 M	1.0 M	MR			
3	Compartmentation.						
3	Fire check door	N/A	N/A	N/A			
		N/A	N/A	N/A			
	Sealing of electrical shafts		N/A	N/A			
	Fire rating of shaft door	N/A		N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	Upper floor	N/A	N/A	N/A			
5.	Fire Extinguisher	100	10 ===	MR			
	Total numbers	06 nos.	10 nos.				
	• Types	ABC & Co2	ABC & Co2	MR			
	IS marking	ISI marked	ISI marked	MR			
6	First-aid-Hose Reels.						
	Total numbers of each floor	1 no.	1 no.	MR			
			20	MR			
	Length of hose reel hose	30 m	30 m	IVIN			
	Length of hose reel hoseNozzle diameter	30 m	30 m	MR			

-				
7	Automatic fire detection and alarming sys			
	Type of detectors	N/A	N/A	N/A
	Location of main panel	N/A	N/A	N/A
	Location of repeater panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooters's location	N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public address System.	N/A	Provided	MR
10	Automatic Sprinkler System.	ga ay e s'ami de, mêt r'		
	Basement	Required	Provided	MR
3.	• upper floor	N/A	N/A	N/A
	 sprinkler above false ceiling 	N/A	N/A	N/A
11	Internal Hydrants			
	 size of riser/down-comer 	N/A	100 MM	MR
	 Number of hydrants per floor 	N/A	1 No.	MR
	Hose Box	N/A	1 No.	MR
12	Yard Hydrants.			
	 Total number of hydrants 	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.			
	Ground Level	N/A	N/A	N/A
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main Pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby pump out put	N/A	N/A	N/A
	Standby pump Head	N/A	N/A	N/A
	Auto Starting / Manual stopping	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
	Terrace Level			
	> Discharge of pump	900 LPM	900 LPM	MR
	> Head of the Pump	40 Mtrs	40 Mtrs.	MR
	> Power supply	Required	Provided	MR
	Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for Fire Fighting.			
	Underground tank capacity	N/A	N/A	N/A
	> Draw-off connection	N/A	N/A	N/A
	> Fire service inlet	N/A	N/A	N/A
	> Access to tank	N/A	N/A	N/A
	Overhead Tank capacity	10,000 Ltrs.	15,000 Ltrs.	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication in lift car	N/A	N/A	N/A
	Firemen's grounding switch	N/A	N/A	N/A
	Lift Signage	N/A	N/A	N/A

17	Standby power supply	Required	Provided	MR
18	Refuge Area.			
	Total area	N/A	N/A	N/A
	• Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector system panel	N/A	N/A	N/A
	Flow switch panel	N/A	N/A	N/A
	PA system panel	N/A	Provided	MR
	Battery backup	Required	Provided	MR
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name:-Suresh Singh

Designation: - ADO (Shad.)

DO (ED)

ulmittad la all allana