## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. 66/06s/as/school/wishoz/48

FIRE SAFETY CERTIFICATE

Dated: 09/0/ /2014

Certified that M C Primary Boys School, Indira Nagar, Delhi-110033 comprised of Ground + One Upper Floor owned/occupied by M C Primary Boys School have complied with the fire prevention and fire safety requirements in accordance with the Circular No F.16/Estate/CC/Fire Safety/2011/3298-3398 dated 01/03/2011 issued by Director of Education and verified by the officer concerned of Fire Service on 14/11/2014 in the presence of Mrs. Paramjeet Kaur (Principal) and that the building / premises is fit for occupancy of Educational building with effect from 69/0/2014 for a period of three years, subject to compliance of the conditions mentioned below:

## Conditions for the validity of Fire Safety Certificate:

- 1 All the fire safety arrangement provided there in shall be maintained in good working conditions at all times.
- 2 Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3 The trained fire fighting staff should be available round the clock.
- 4 Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5 This certificate cannot be treated in any case for regularizations of unauthorized construction.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>

Issued on \_\_\_\_\_\_ at New Delhi by

(SANTOKH SINGH) Chief Fire Officer Ph: 011-23414250

ge sy

Copy to:

1. The Principal, M C Primary Boys School, Indira Nagar, Delhi-110033.

2. The Dy. Director of Education, NDMC Civil Line Zone, 5<sup>th</sup> floor Rajpur Road, Delhi 54.

		INSP	ECTION REPOR	g T	ir tone flo	
5 6	1.	Name & address of the building:  Type of Occupancy :  Type of Case : New Details of previous NOC : Lett Fire Safety directives letter No : Date of inspection : Name of the Inspecting Officers : Name and designation of officers	Pi's of Sdy.  19.11.19  A 00 (Bw)	Roys School J Cis. 01.3.201	selhi-33  ated:	
from the building side  9. Year of Construction  10. Applicant's letter No.  Plot Area: 300 m2 Covered Area: 650 m2 No. of Students: 241 No. of Class Rooms: 13						
S. No.	_	Minimum Standards on fire prevention and fire safety U/R 33 cess to building	NBC/ Dir. Of Edu. Requirement	Provided at site	Remarks MR/NMR	
	-	• Road width	Accessable	Accessable	MR	
		• Gate width	_			
		<ul> <li>Width of internal road</li> </ul>				
2 N	Vui	mber, Width, Type & Arrangement	of Exits			
a.	. N	umber of staircases		7	~	
		• Upper Floors	01			
		Basements		01	MR	
b.	W	idth of staircases				
		Upper Floors	1.50 Mtz	1.65 M/Z	100	
		Basements	1 30717	1-03 1-12	MR	
C	Pr	otection of exits				
C.	1 1					
	•	Fire check door		_		
	•	Pressurization				
	1	o. of continuous staircases to terrace	_	99-201		
*		dth of Corridor or Size				
			1-00 Mtz	1.10 Mtz	MR	

3	Compartmentation.					
	Fire check door				6	
	Sealing of electrical shafts			LE-3		
	Fire Rating of shaft door					
12.3	Water Curtain					
	• Fire Dampers		MI			
4	Smoke Management System.					
	Basements	30 a/c per hour				
	Upper floors	12 a/c per hour				
5	Fire Extinguishers					
	Total numbers	SABC	7	M	e /	
	• Types	ISI marked	ABC	M	R	
	IS marking		7.25	MK		
6	First-Aid Hose Reels.				1	
	Total numbers on each floor					
	Length of hose reel hose	30 m				
	Nozzle diameter	5 mm	/			
7	Automatic fire detection and alarming system.					
	Type of detectors					
	Location of Main Panel					
	Location of Repeater Panel	X	7/4			
	Alternate source of power					
	Hooters' Location					
8	MOEFA					
9	Public Address System.					
10	Automatic Sprinkler System.					
	Basement			/		
	• Upper Floor					
	Sprinkler above false ceiling					
11	Internal Hydrants					
	Size of riser/down-comer	*				
	Number of hydrants per floor	MIR			3 7	
	• Hose Box					

			74-5		
12		Yard Hydrants.			
		Total number of hydrants			
		Hose Box			
13	Pum	ping Arrangements.			
	•	Ground Level			
		- senarge of main Pum	ip		
		riedd o'i Wain pump			
		of main pumps			
		sockey I ump out put			
		Jockey pump head		./	
		Standby Pump out put		NIX	
		Standby Pump Head			
		Auto Starting/ Manual			
		stopping Pump House Access			
	•	Terrace level			
		Discharge of pump			
		Head of the pump			
		Power Supply			
	7	Auto Starting of pump			W.
Ca	ptive	Water Storage for fire fight	ting		
	• U:	nderground tank capacity	ing.		
	> D <sub>1</sub>	raw-off connection			-
		re service inlet			
		ecess to tank			7 0.1
	· ·			/	1
T	4	erhead Tank capacity			
	Signa				
Prov	ision	of Lifts.			
•	Pres	ssurization of Lift Shaft			
•		surization of Lift lobby		(X	
•	Con	munication In lift Car	A STATE OF THE STA		
•		man's Grounding Switch			
	Lift	Signage Switch			
Stand		wer supply			
-	~յ իս	wer supply			
					-475
					8