GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:-011-23412593

No. F6/DFS/MS/GH/2014/ND2 / /616

E-mail ID: cfohq.dlfire@nic.in
Dated 22 | 12 | 14

FIRE SAFETY CERTIFICATE

Certified that the Euro International Guest House located at 904-A, Gali Chandiwali, Main Bazar, Pahar Ganj, New Delhi comprises of Ground + Four Upper floors, Ground floor (reception + 01 guest room), 1st floor to 3rd floor (05 guest rooms at each floor) and 4th floor (04 guest room) was granted NOC by this department vide letter No.F6/DFS/MS/GH/2011/2991 dated 16-01-2011. The premises was re-inspected by the officer concerned of this department on 09-12-2014 in the presence of Mr. Ankit Mahajan (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 for 20 guest rooms with effect from 22-12-14-2014 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 22/12/14 at New Delhi by.

(**Dr. G.C.Misra**) Chief Fire Officer Delhi Fire Service Ph – 011-23414333

Copy to:-

- 1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi 110049.
- 2. The Commissioner North Delhi Municipal Corporation with a request to measure the height and appraise this department.
- 3. Mr. Ankit Mahajan (Manager) Euro International Guest House located at 904-A, Gali Chandiwali, Main Bazar, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

INSPECTION REPORT : Euro International Guest House located at 904-A, Gali 1. Name & address of the building Chandiwali, Main Bazar, Pahar Ganj, New Delhi. : Residential Building Gr. + 4 upper floors (total 20guest room) 2. Type of Occupancy : Renewal 3. Type of Case : F6/MS/DFS/GH/2011/2991 dated 16/11/2011 4. Details of previous NOC 5. Fire Safety directives Letter No. : NA . 09/12/2014 6. Date of inspection 7 Name of the Inspecting Officer : Sh. M. K. Sharma (ADO/CC) 8 Name and designation of Officer : Sh. Ankit Mahajan (Manager) from the building side : 2007 9 Year of Construction : 49987-90/Joint. C.P./Lic.(H) dated, New Delhi the 21/08/2012. 10. Applicant's letter No. Old Case Remarks Provided at site Minimum standards on fire prevention Existing S No MR/NMR (PSS Area) Requirements and fire safety U/R 33 (PSS Area) Access of building 1. MR 0.90 Mtr. NA Road width NA NA NA Gate width NA NA NA Width of internal road Number, width, Type & Arrangements of exits 2. a. Number of staircases MR 1 Nos. 1 Nos. • Upper floors NA NA NA Basements b. Width of staircases MR 0.80 Mtr. Old case 1 Mtr. • Upper floors NA NA NA Basements c. Protection of exits NA NA NA • Fire check door NA NA NA Pressurization 1 No. MR 1 No. d. No of continuous staircase to terrace

- Y7' 1.1 C 2			
e. Width Of Corridor	NA	NA	NA
f. Door Size			IVA
Compartmentation	1 Mtr.	1 Mtr.	MR
Fire check door			
	NA	NA	NA
Sealing of electrical shafts	NA	NA	NA
Fire Rating of shaft door	NA	NA	NA
Water Curtain	NA	NA	NA
• Fire Dampers	NA	NA	NA
Smoke managements System			
• Basements	NA	NA	NA
 Upper floors 	12 ACPH	NATURAL	MR
Fire Extinguishers			IVIIV
 Total numbers 	08 Nos.	10 Nr.	
• Types	ABC,CO ₂ , Wco ₂ ,	10 Nos.	MR
 IS marking 	Required	ABC,CO ₂ , Wco ₂	MR
First - Aid Hose Reels		Provided	MR
Total numbers on each floor	0.1		
 Length of hose reel hose 	01	01	MR
 Nozzle diameter 	30 Mtr.	30 Mtr.	MR
	05 MM	05 MM	MR .
Automatic fire detection and alarming s		i de la companya de l	
• Type of detectors	NA	NA	NA
Location of Main Panel	NA	NA	NA
Location of Repeater Panel	NA	NA	NA
Alternate source of power	NA	NA	NA
Hooters' Location	NA	NA	NA
MOEFA	NA	NA	NA
Public Address System	Required	Provided	MR
Automatic Sprinkler			1411/
• Basements	NA	NA	NIA
• Upper Floor	NA	NA	NA
Sprinkler above false ceiling	NA	NA	NA
Internal Hydrants		11/1	NA
• Size of riser/down- comer	NA	NIA	
 Number of hydrants per floor 	NA	NA	NA
, Francoi	IVA	NA	NA

*	•	Hose Box	NA	NA	NA	
12	Yard	Hydrants		J		
	•	Total number of hydrants	NA	NA	NA	
	•	Hose Box	NA	NA	NA	
13	Pumping Arrangements					
	0	Ground Level		v.		
	•	Discharge of main pump	NA	NA	NA	
	•	Head of main pump	NA	NA	NA	
	•	Number of main pumps	NA	NA	NA	
	•	Jockey pump out put	NA	NA	NA	
	•	Jockey pump head	NA	NA	NA	
	•	Standby Pump out put	NA	NA	NA	
	•	Standby Pump Head	NA	NA	NA	
	•	auto Staring/Manual stopping	NA	NA	NA	
	•	Pump House Access	NA	NA	NA	
	0	Terrace level				
	•	Discharge of pump	220 LPM	220LPM	MR	
	•	Head of the pump	40 Mtr.	40 Mtr.	MR	
	•	Power supply	Required	Provided	MR	
	•	Auto starting of pump	Required	Provided	MR	
14	Captix	ve water Storage for fire fighting			*	
17						
	•	Under ground tank capacity	NA:	NA	NA	
	•	Draw off connection	NA	NA	NA	
	•	Fire service inlet	NA	NA	NA	
	•	Access to tank	NA	NA	NA	
	•	Overhead Tank capacity	2500 Ltr.	> 2500Ltr. Old case	MR	
15	Exit Si	gnage	Required	Provided	MR	
16	Provis	ion of Lifts	I.		,	
15.	•	Pressurization of Lift Shaft	* NA	NA	NA	
	R ·	ressurization of fift loody	NA	NA	NA	
	•	Communication in lift Car	NA	NA	NA	
	•	Fireman's Grounding Switch	NA	NA	NA	
	•	Lift Signage	NA	NA	NA	
			8,	1		

Y/13

17	Standby power supply	Required	Provided	MR
18	Refuge Area	1111		
	Total area	NA	NA	NA
	• Location	NA	NA	NA
19	Fire control room			
	Detector system panel	NA	NA	NA
×	Flow Switch Panel	NA	NA	NA
,	PA System Panel	NA	NA	NA
	Battery backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA
20	Special Fire Protection Systems for	Required	ABC, Co ₂	MR
	Protection of special Risks, if any;			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/MS/DFS/GH/2011/2991 dated 16/11/2011 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

> Previous FSC was issued on 2500 liter overhead water tank for fire.

Signature of the Inspecting Officer

Name: - M.K. Sharma
Designation: - A. D.O. (CC)

Doseph linking