## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:-011-23412593

No. F6/DFS/MS/GH/2014/ x1P2 /1620

E-mail ID: cfohq.dlfire@nic.in Dated

## FIRE SAFETY CERTIFICATE

Certified that the Geet Deluxe Guest House located at 8569-70 Arakashan Road, Pahar Ganj, New Delhi comprises of Basement + Ground + Four Upper floors having 39 guest room (Basement is laying vacant), Ground floor has (reception + office + lobby), First floor has 09 rooms and 2<sup>nd</sup> floor to 4<sup>th</sup> floor has (10 guest rooms at each floor), terrace floor having 05 rooms are sealed with brick wall was granted NOC by this department vide letter No.F6/DFS/MS/GH/2012/1175 dated 29-03-2012. The premises was re-inspected by the officer concerned of this department on 09-12-2014 in the presence of Mr. Suresh Kumar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service Ph – 011-23414333

## Copy to:-

of c me 1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi – 110049 w.r.t. letter No 44665/Joint. C.P./Lic. (H) dated New Delhi 02-12-2014.

2. Mr. Suresh Kumar (Manager) Geet Deluxe Guest House located at 8569-70 Arakashan Road, Pahar Ganj, New Delhi

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

7. This NOC is for 39 guest rooms at First floor, Second floor, Third floor and fourth floor only.

12/18 INSPECTION REPORT 1. Name & address of the building : Geet Dx. Guest House located at 8569-70, Arakashan Road PaharGanj, New Delhi. : Residential Building B+Gr.+4 upper floors (total 39guest room) : Renewal : F6/MS/DFS/GH/2012/1175 dated 29/03/2012 : NA : 09/12/2014 : Sh. M. K. Sharma (ADO/CC) : Sh. Suresh Kumar (Manager) : 2001

5. Fire Safety directives Letter No. 6. Date of inspection

7 Name of the Inspecting Officer

8 Name and designation of Officer

2. Type of Occupancy

4. Details of previous NOC

3. Type of Case

from the building side

9 Year of Construction

10. Applicant's letter No. : 44665/Joint. C.P./Lic.(H) dated, New Delhi the 02/12/2014.

S No	Minimum et al. 1 C			old Case
3 110	Minimum standards on fire prevention	Existing	Provided at site	Remarks
	and fire safety U/R 33	Requirements	(PSS Area)	MR/NMR
		Tay	_	(PSS Area)
•	Access of building			
	Road width	NA	6 Mtr.	MR
	Gate width	NA	NA	NA
	Width of internal road	NA	NA	NA
	Number, width, Type & Arrangements of	exits		
	a. Number of staircases			
	• Upper floors	1 Nos.	1 Nos.	MR
	Basements	1 Nos.	2 Nos.	MR
	b. Width of staircases			
	• Upper floors	0.80 Mtr.	1.25 Mtr.	MR
	Basements	1.00 Mtr.	1.25 Mtr.	MR
	c. Protection of exits			
	• Fire check door	NĀ	NA	NA
	• Pressurization	NA	NA	NA
	d. No of continuous staircase to terrace	1 No.	1 No.	MR

	e. Width Of Corridor f. Door Size	1 Mt.	1 Mt.	MR	
		1 Mt.	1 Mt.	MR	
3.	Compartmentation	1 Wit.	1 IVIL.	IVIIX	
J.	Fire check door	NA	NA	NA	
		NA	NA	NA	
	Samuel of Alexander Shares	NA NA	NA	NA NA	
	Fire Rating of shaft door  Water Contains	NA	NA NA	NA NA	
	Water Curtain	NA	NA NA	NA NA	
1	• Fire Dampers	INA	INA	INA	
4	Smoke managements System				
	Basements	30 ACPH	Provided	MR	
	Upper floors	12 ACPH	NATURAL	MR	
5	Fire Extinguishers				
	Total numbers	18 Nos.	20 Nos.	MR	
	• Types	ABC,CO <sub>2</sub> , Wco <sub>2</sub> ,	ABC,CO <sub>2</sub> , Wco <sub>2</sub>	MR	
	IS marking	Required	Provided	MR	
6	First - Aid Hose Reels				
	Total numbers on each floor	01	01	MR	
	Length of hose reel hose	30 Mtr.	30 Mtr.	MR	
	Nozzle diameter	05 MM	05 MM	MR	
7	Automatic fire detection and alarming system				
	Type of detectors	NA	NA	NA	
	Location of Main Panel	NA	NA	NA	
	Location of Repeater Panel	NA	NA	NA	
	Alternate source of power	NA	NA	NA	
	Hooters' Location	NA	NA	NA	
8	MOEFA	Required	Provided	MR	
9	Public Address System	Required	Provided	MR	
10	Automatic Sprinkler				
	• Basements	Required	Provided	MR	
	Upper Floor	NA	NA	NA	
	Sprinkler above false ceiling	NA	NA	NA	
11	Internal Hydrants				
	Size of riser/down- comer	100 MM	100 MM	MR	
	Number of hydrants per floor	01	01	MR	

		Hara Day	01	01	MR
1.0	• 1 T	Hose Box			
12	Y ard F	Hydrants	NA	NA	NA
	•	Total number of hydrants		NA	NA
	•	Hose Box	NA	IVA	1172
13	Pumpi	ng Arrangements			
	0	Ground Level	y =	774	NIA
	•	Discharge of main pump	NA	NA	NA
	•	Head of main pump	NA	NA	NA
	•	Number of main pumps	NA	NA	NA
	•	Jockey pump out put	NA	NA	NA
		Jockey pump head	NA	NA	NA
		Standby Pump out put	NA	NA	NA
	•	Standby Pump Head	NA	NA	NA
		auto Staring/Manual stopping	NA	NA	NA
		Pump House Access	NA	NA	NA
		Terrace level	·		
		Discharge of pump	450 LPM	450 LPM	MR
		Head of the pump	30 Mtr.	30Mtr.	MR
	•		Required	Provided	MR
	•	Power supply	Required	Provided	MR
	•	Auto starting of pump	1		
14	Captive water Storage for fire fighting				
	•	Under ground tank capacity	NA	NA	NA
		Draw of connection	NA	NA	NA
	7	Fire service inlet	NA	NA	NA
•	•	A	NA	NA _	NA
		O 1 T 1 T and a site		10,000 T	MR
1.5	e	•	10,000 Ltr. Required	10,000 Ltr. Provided	MR
15	Exit Signage		required	Provided	
16		rision of Lifts	NA	NA	NA
		C1: C 1-1-1	NA	NA	NA
	9	Communication in lift Car	100.00 100.00	Provided	MR
		D' Compline Caritab	Required	Provided	MR
			Required		MR
		Lift Signage	Required	Provided	
17	Star	ndby power supply	Required	Provided	MR

10	110108011111111111111111111111111111111					
	Total area	NA	NA	NA		
	<ul> <li>Location</li> </ul>	NA	NA	NA		
19	Fire control room					
	Detector system panel	NA	NA	NA		
	Flow Switch Panel	NA	NA	NA .		
	PA System Panel	NA	NA	NA		
	Batter backup	NA	NA	NA		
	Building Floor Plans	NA	NA	NA		
20	Special Fire Protection Systems for	Required	ABC, Co <sub>2</sub>	MR		
	Protection of special Risks, if any;					
	The fire protection systems provided in the functional at the time of inspection.  In view of the deemed compliance safety measures as required under the rul F6/MS/DFS/GH/2012/1175 dated 29/03 rules 2010, is recommended.	of the minimum sta	indards of fire prevent	ion and fire		
		C:	ignature of the Inspect			

Designation: - A. D.O. (CC)

Refuge Area

18