## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001.

No. F.6/DFS/MS/EH/2014/ 52 | 1631

Dated: 23/12/14

## FIRE SAFETY CERTIFICATE

Certified that the Haldi Ram Restaurant, 4B/16, Najafgarh Rd, Tilak Nagar, New Delhi-110018, is in the building comprised of basement, ground floor plus two upper floors but the restaurant is running at ground plus two upper floors only of above said building and the basement is not in use. The restaurant having two exits owned/occupied by M/s Haldiram Products Pvt. Ltd. The Restaurant was inspected by the officer concerned of this department on 09.12.2014 in the presence of Sh. Udit Awasthi (General Manager) and found that the M/s Haldiram Products Pvt. Ltd. have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the Restaurant (at Ground plus two upper floors only) is fit for occupancy class Group D assembly building w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 23/12/19 at New Delhi.

(DR. G. C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph.011-23414333

Copy to:-

 The Manager, Haldi Ram Restaurant, 4B/16, Najafgarh Rd, Tilak Nagar, New Delhi-110018.

## Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per the building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

Basement (Not in use), Ground Plus Two Upper Floors.

	(Haldi Ram Restaurant, 4B/16, Najafg  • Upper floors		Natural	M/R
5.	Fire Extinguishers		Ventilation	
			#	
	<ul> <li>Total numbers</li> </ul>	Three no's / floor	Provided	
	• Types	ABC/CO2	Provided	M/R
	• IS marking	IOV	000000 0000	M/R
6.	First-Aid Hose Reels	ISI marked	ISI marked	M/R
	Total numbers on each floor			
	Length of hose reel hose	Two	Provided	M/R
	Nozzle diameter	30 mtrs	Provided	M/R
		5 mm	Provided	M/R
•	Automatic fire detection and alarming syste	em		
	• Type of detectors	Smoke & Heat	Provided	14/2
	Location of Main Panel			M/R
	Location of Repeater Panel     Alternate source of recommendations		Basement	M/R
	<ul><li>Alternate source of power</li><li>Hooters' Location</li></ul>	D	Provided	
		Required	Near exits	M/R
	MOEFA	Required	Provided	M/R
	Public Address C	required	Provided	M/R
	Public Address System	Required	Provided	M/R
).	Automatic Sprinkler System	1.	9	141/10
	• Basement	-	Provided	
	Ground Floor     Sprintly	Required	Provided in	MR
	<ul> <li>Sprinkler above false ceiling</li> </ul>		entire building	IVIIC
•	Internal Hydrants	N/A	N/A	N/A
	Size of riser/down com			
	<ul><li>Size of riser/down-comer</li><li>Number of hydrants</li></ul>	100 mm	Provided	M/R
	Hose Box	02 No's	Provided	M/R
	Yard Hydrants	02 No.	Provided	M/R
			à.	
	<ul> <li>Total number of hydrants</li> </ul>			
	Hose Box		_	
	Pumping Arrangements			
	Ground Level			
	Discharge of main Pump	NA	2280 LPM	
	Head of Main pump	NA		
	Number of main pumps	NA	50 mtrs	
	<ul><li>Jockey Pump out put</li><li>Jockey pump head</li></ul>		01	
	sockey pump nead	NA	180 LPM	
	Standby D.	NA	50 mtrs	
	Juliupy Plimn Out hut			
	Standby Pump out put	NA NA	2280 LPM	

Basement (Not in use), Ground Plus Two Upper Floors. (Haldi Ram Restaurant, 4B/16, Najafgarh Road, Tilak Nagar, New Delhi 110018.) Standby Pump Head NA Provided Provided Auto Starting/Manual Stopping Pump House Access Terrace level Discharge of pump Required 900 LPM M/R Head of the pump Required 40 mtrs M/R Power Supply Required Provided M/R Auto Starting of pump Required Provided M/R 14. Captive Water Storage for fire fighting Underground tank capacity NA Provided 50,000 Ltrs Draw-off connection Fire service inlet Access to tank Overhead Tank capacity 10,000 Ltrs 10,000 Ltrs M/R Required Provided M/R 15. Exit Signage. 16. Provision of Lifts. (No Lift) Pressurization of Lift Shaft N/A N/A N/A Pressurization of Lift lobby N/A N/A N/A Communication In lift Car N/A N/A N/A Fireman's Grounding Switch N/A N/A N/A Lift Signage N/A N/A N/A Provided Required M/R (DG set 260 KVA) 17. Standby power supply 18. Refuge Area. > Total Area N/A N/A N/A Location N/A N/A N/A 19. Fire Control Room **Detector System Panel** N/A N/A N/A Flow Switch Panel N/A N/A N/A PA System Panel N/A N/A N/A N/A N/A N/A Battery backup N/A N/A N/A **Building Floor Plans** N/A N/A N/A 20. Special Fire Protection System for Protection of special Risks, if any:

TO

Basement (Not in use), Ground Plus Two Upper Floors. (Haldi Ram Restaurant, 4B/16, Najafgarh Road, Tilak Nagar, New Delhi 110018.)

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the above substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Note: - The restaurant is at ground plus two upper floors, the basement is not in use and the total capacity of water tank is 60,000 ltrs (U/G-50,000 ltrs + O/H -10000 ltrs) and separate DG supply (125 KVA) has also been extended to Fire Pump Panel, as per the letter submitted by the authorized signatory.

Signature of Inspecting Officer

Name: - S.K. Tomar

Designation:- Divisional Officer

Signature of Inspecting Officer

Name:-

Designation:-