GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. FOLDBIMSI OMOTIZEUS 1402/96

Dated: 20 101 15

FIRE SAFETY CERTIFICATE

Certified that the Gopal Vatika (Banquet Hall/Marriage Home) at Plot No.603 to 612, Mandoli road, Shadara, Delhi-32, Comprised of ground floor only owned/occupied by M/s Gopal Vatika Banquet Hall/ Marriage Home have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of this department on dated 14.11.2014 in the presence of Sh. Rakesh Sharma (Prop.) and found that the ground floor of building is fit for occupancy class D 'Assembly (Banquet Hall/ Marriage Home)' at Ground floor with effect from for a period of three years, in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, subject to conditions printed overleaf.

Issued on....at New Delhi by

(Dr.G.C.Misra) Chief Fire Officer Ph.011-23414333

To,

The Dy. Health Officer, East Delhi Municipal Corporation ,Health Department, Shahdara (North) Zone, Shahdara, Delhi

Copy to-

Sh.Rakesh Sharma (Prop.) M/s Gopal Vatika Banquet Hall/Marriage Home Plot No.603 to 612, Mandoli road, Shadara,Delhi-32,

CONDITIONS:

- 1. All the means of escape shall be kept free of all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate,six months prior to its expiry"
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1. Na	ame & address of the building	: Gopal Vatika Banq	uet Hall at Plot N	o.603 to 612,			
7		Mandoli Road,Shahdara, Delhi.					
2. Bu	uilding is comprised of	: Ground floor onl					
3. Ty	pe of Occupancy	: Assembly (Banqu					
4. Ty	pe of Case	: New Case	,				
5. De	etails of Previous NOC	: Nil : NBC Part IV : 14.11.2014					
6. Fir	re Safety direction letter No						
	ate of Inspection						
	ame of the Inspecting Officers:		h & DO Virendra Si	ingh			
	ame of the designation of Officer			111811			
	om the building side	: Sh.Rakesh Sharm	na (Pron)				
	ear of Construction	: 2009	ia (110p)				
	pplicant's letter No	: dated 09.09.14					
S.No	Minimum Standards on fire	equirement/NBC	Drovided at Site	Remarks MR/NM			
The second	prevention and fire safety U/R33	equilibrii (1480	Provided at Site	Kellidiks ivinyiviy			
1	Access to building						
_	Road width	6 m	30 m	MR			
	Gate width	N.A.	N.A.				
	Width of internal road	N.A.		N.A.			
2		2 100-05 1000	N.A.	N.A.			
	Number, Width, Type and Arrangeme a. Number of Staircases	ent of Exits	T	T			
			_				
	Upper Floor	N/A	01No.for terrace	MR			
	Basement	N.A.	N.A.	N.A.			
	b. Width of Staircases		9 -				
	Upper Floor	N/A	1.25 M	MR			
	Basement	N.A.	N.A.	N.A.			
	c. Protection of exits	- J1	W .				
	Fire check door	N.A.	N.A.	N.A.			
	Pressurization	N.A.	N.A.	N.A.			
	d. No. of continuous staircases to	N.A.	N.A.	N.A.			
	terrace						
	e. Width of Corridor	N.A.	N.A.	N.A.			
	f.Number of door	02 Nos.	04 Nos.	MR			
	g. Door Size	2 m	2 m each	MR			
3	Compartmentation.						
		N.A.	N.A.	N.A.			
	Sealing of electrical shafts	N.A.	N.A.	N.A.			
			N.A.				
	VA/atau avutaiu			N.A.			
	Fire Damners	N.A.	N.A.	N.A.			
	rife Dairipers	N.A.	N.A.	N.A.			
4	Smoke Management System.						
	Basement	N.A	N.A.	N.A.			
	Ground floor	Required	Ventilated	M/R			

5.	Fire Extinguisher	0.4.81	OCNICO	MR				
	Total numbers	04 Nos.	06Nos.					
	types	CO ₂ & ABC	CO ₂ & ABC	MR				
	IS marking	ISI marked	ISI marked	IVIR				
j	First-aid-Hose Reels.							
	Total numbers of each floor	1 no.	1 no.	MR				
	Length of hose reel hose	30 m	30 m	MR				
	Nozzle diameter	5 mm	5 mm	MR				
7	Automatic fire detection and alarming system.							
	Type of detectors	N.A.	N.A.	N.A.				
	Location of main panel	N.A.	N.A.	N.A.				
	Location of repeater panel	N.A.	N.A.	N.A.				
	Alternate source of power	N.A.	N.A.	N.A.				
	Hooters's location	N.A.	N.A.	N.A.				
8	MOEFA	Required	Provided	MR				
9	Public address System.	N.A.	N.A.	N.A.				
10	Automatic Sprinkler System.							
	Basement	N.A.	N.A.	N.A.				
	upper floor	N.A.	N.A.	N.A.				
	sprinkler above false ceiling	N.A.	N.A.	N.A.				
11	Internal Hydrants							
	size of riser/down-comer	100 mm	100 mm	MR				
	Number of hydrants of each floor	1 no.	1 no.	MR				
	Hose Box	01 no.	01 no.	MR				
12	Yard Hydrants.							
12	Total number of hydrants	N.A.	N.A.	N.A.				
	Hose Box	N.A.	N.A.	N.A.				
13	Pumping Arrangements.							
	Ground Level	N.A.	N.A.	N.A.				
i.	Discharge of main Pump	N.A.	N.A.	N.A.				
	Head of Main Pump	N.A.	N.A.	N.A.				
	Number of main pumps	N.A.	N.A.	N.A.				
	Jockey pump out put	N.A.	N.A.	N.A.				
	Jockey pump head	N.A.	N.A.	N.A.				
	Standby pump out put	N.A.	N.A.	N.A.				
	Standby pump Head	N.A.	N.A.	N.A.				
	Auto Starting /Manual stopping	N.A.	N.A.	N.A.				
	Pump House Access	N.A.	N.A.	N.A.				
	Terrace Level							
	Discharge of pump	450 LPM **	450 LPM	MR				
	Head of the Pump	40 m	40 m	MR				
	Power supply	Required	Provided	MR				
	Auto Starting of pump	Required	Provided	MR				

NI3

14	Captive Water Storage for Fire Fightin	g.				
	Underground tank capacity	N.A.	N.A.	N.A.		
	Draw-off connection	N.A.	N.A.	N.A.		
	Fire service inlet	N.A.	N.A.	N.A.		
	Access to tank	N.A.	N.A.	N.A.		
	Overhead Tank capacity	10,000 Liters	10,000 Liters	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
	Communication in lift car	N.A.	N.A.	N.A.		
	Firemen's grounding switch	N.A.	N.A.	N.A.		
	Lift Signage	N.A.	N.A.	N.A.		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	Total area	N.A.	N.A.	N.A.		
	Location	N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel	N.A.	N.A.	N.A.		
	Flow switch panel	N.A.	N.A.	N.A.		
	PA system panel	N.A.	N.A.	N.A.		
	Battery backup	N.A.	N.A.	N.A.		
	Building Floor Plans	N.A.	N.A.	N.A.		
20	Special Fire Protection systems for	N.A	N.A	N.A		
	protection of special Risks, if any:	2	- a			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Name: Suresh Singh Designation: ADO (Shad.)