GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: <u>cfohq.dlfire@nic.in</u>, <u>Tel:-</u>011-23414333 No. F6 | OFS | ms | school | 2015 | 521 (23 Dated: 27)01 | (5

FIRE SAFETY CERTIFICATE

Certified that New Green Land Ideal Public School located at C-1, Holi Chowk, Sangam Vihar, New Delhi-110062 comprised of ground and one upper floor was granted NOC by this department vide letter No. F.6/DFS/MS/2006/1456 dated 03.07.2006 for ground and first floor only. The school building was re-inspected by the officer concerned of this department on 07.01.2014 in presence of the principal of the school and found that the School management have constructed a small basement (less than 200 m²) in the school building and also have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education circular No. 262-362 dated 17/01/05 and that the school building is fit for occupancy class "Educational" with effect from the date of issue of this certificate for a period of three years, subject to compliance of the under mentioned conditions.

Issued on -27/01/15 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

- 1. The Principal, New Green Land Ideal Public School, C-1, Holi Chowk, Sangam Vihar, New Delhi-110062.
- 2. The Directorate of Education, Old Secretariat, NewDelhi-110006.

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: New Green Land Ideal Public School, C-1, Holi Chowk,

Sangam Vihar, New Delhi-110062

1. Type of Occupancy

: Educational

2. Type of Case

: Renewal

3. Details of previous NOC

: F.6/DFS/MS/2006/1456 dated 03.07.2006

4. Fire Safety directives letter No

: Directorate of Education circular No. 262-362 dated

4

17/01/05

5. Date of inspection

: 07.01.2015

Name of the Inspecting Officers : M.K.Chattopadhyay, ADO(M.Rd)

7. Name and designation of officers

from the building side

: Principal

9. Year of Construction

: 2005-06

10. Applicant's letter No.

: NGIPS/01/2014-15 dated 17.11.2014.

New Green Land Ideal Public School is comprised of small basement, ground plus one upper floor.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building		-	
	Road width	06 mts	Provided	MR
	• Gate width	4.5 mts	Provided	MR
	 Width of internal road 	N/A	N/A	N/A
	Number, Width, Type & Arrangement	of Exits		,
	a. Number of staircases			
	• Upper Floors	01	01	MR
	Basements	01	01	N/A
	b. Width of staircases		*	
	• Upper Floors	1.5 mts or less & 0.75 mt	1.60 mts.	MR
	• Basements	1.5 mts or less & 0.75 mt	1.60 mts.	MR
	c. Protection of exits			
	 Fire check door 	N/A	N/A	N/A
	 Pressurization 	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	1.5 mts	Provided	MR
	h. Door Size	1.0 mts	Provided	MR

			1
ompartmentation.	NT/A	N/A	N/A
Fire check door			N/A
	N/A		N/A
 Fire Rating of shaft door 	N/A		N/A
• Water Curtain	N/A		N/A
• Fire Dampers	N/A	N/A	
Smoke Management System.			MR
 Basements 	30 a/c per hour		N/A
5 bol (2000) 3	12 a/c per hour	IN/A	
			MD
	06 nos.		MR
	ABC, CO ₂ type	Provided	MR
	ISI marked	Provided	MR
	01	Provided	MR
	30 m	N/A	N/A
	5 mm	N/A	N/A
	g system N	ot required	
	N/A	N/A	N/A
	N/A	N/A	N/A
		N/A	N/A
			N/A
	N/A	3	N/A
Hooters' Location	N/A	N/A	
MOFFA	N/A	N/A	N/A
	N/A	N/A	N/A
	•		
	N/A	N/A	N/A
	N/A	N/A	N/A
Sprinkler above false ceiling	N/A	N/A	N/A
1 Internal Hydrants			
Size of riser/down-comer	N/A	N/A	N/A
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarmin Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System Basement Upper Floor Sprinkler above false ceiling Internal Hydrants 	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers N/A Smoke Management System. Basements Upper floors Total numbers Total numbers IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system N/A Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location N/A N/A MOEFA Public Address System. Automatic Sprinkler System Basement Upper Floor Sprinkler above false ceiling N/A N/A Internal Hydrants 	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers N/A Provided N/A N

Z.				
	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
12	Yard Hydrants.			
	• Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements	*		
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	> Auto Starting/ Manual	N/A	N/A	N/A
	stopping	N/A	N/A	N/A
	Pump House AccessTerrace level			
	Terrace levelDischarge of pump	225 LPM	Provided	MR
	Head of the pump	30 mts	Provided	
	Power Supply			MR
	Auto Starting of pump	N/A	N/A	N/A
		required	Starting switch provided at GF	MR
14	Captive Water Storage for fire fightin	g	provided at Gr	*
	Underground tank capacity	N/A	N/A	N/A
	Draw-off connection	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A
	Overhead Tank capacity	2500 lts	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.	Not Applica	ible	
	Pressurization of Lift Shaft	N/A	N/A	N/A
	1		•	1

	Pressurization of Lift lobby	N/A	N/A	N/A
	 Pressurization of Lift lobby Communication In lift Car 	N/A	N/A	N/A
	• Fireman's Grounding Switch	N/A	N/A	N/A
	• Lift Signage	N/A	N/A	N/A
17	Standby power supply	N/A	N/A	N/A
18	Refuge Area.			
10	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room			
19	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
		N/A	N/A	N/A
20	Building Floor Plans Special Fire Protection Systems for Protection of special Risks, if any:	Required	01 ABC type fire extinguisher is provided near elect. Panel.	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/2006/1456 dated 03.07.2006, renewal under the Directorate of Education circular No. 262-362 dated 17/01/05 is recommended.

DFA is put up for approval & signature please

Signature of the Inspecting Officer
Name (M.K. CHATTOPADHYAY)

Designation: - Assistant Divisional Officer