GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE

NEW DELHI- 110 001

No. 66/065/ars/2015/52/110

Dated: 22/01/15

FIRE SAFETY CERTIFICATE

Issued 2.2./.o././.. 2015 at New Delhi by

(Dr.G.C.Misra)
Chief Fire Officer

T.No.011-23414333

Copy to:-

Sh. Sarabh Kumar (Executive Engineer), Electric, President Estate, Electric Division, CPWD, Rastrapati Bhawan, New Delhi-110004.

Conditions for the validity of fire safety certificate are overleaf:-

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- The employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All fire fighting equipments shall be maintained in perfect working condition all time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate in form J, six month prior to its expiry.

1.	Name & address of the building : RE	INSPECTION RE	POR	T				
	of childing Hall 100 attendance of the Arras					ditorium		
2. Building is comprised of : Ground plus one floor.(Culture centre at ground floor & only ALI								
							nlv AHU :	
3 Type of O								
	Type of C	sembly Building (C	ultur	re Centi	e/Ceremonial H	all).		
t .	Details of Provious NOS	ew Case				,		
6.	Fire Cof-1 1:							
6. Fire Safety direction letter No :No.F6/DFS/MS/BP/2011/2226, Dated 13.09.2011. 7. Date of Inspection :19.01.2015 8. Name of the Inspecting Officers: : Vedpal (ADO)								
	from the body of the same of t							
10.	Vear of Construction Construction (Executive Engineer).							
	2014.							
S.N	1. Applicant's letter No. : DB-17(Ceremonial Hall)/RSVM/2014-15/218, Dated 16.01. N Minimum Standards on fire						1 15	
		Requirem	nents	as	Provided at	Rema		
1	prevention and fire safety U/R3: Access to building	3 Per Direc	tives		Site	1 tome	uno	
	Road width							
	Gate width	9m	27 15 10 10 10 10	m		MR	31	
	Width of internal road	6m	D	irectly	approachable	MR	5	
	or internal road		O	n road				
2	Number Width Type and Arms	Der, Width, Type and Arrangement of Exits.			N.A.			
	a. Number of Staircases	ement of Exits.			1 garage 1			
	Upper Floor							
		02nos. for		02nos for AHU rooi		ms from	MR	
			AHU rooms at Auditorium building			g both	า	
	Basement	ement 1st floor. Buildings interconn		ected.				
	B. Width of Staircases	N.A.		N.A.	N.A.			
	Upper Floor	1.05m			4.10			
	Basement	1.25m N.A.	100	1.25	m	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	MR	
	c. Protection of exits	N.A.		N.A.		75 91	N.A.	
	Fire check door	Required	1.715/2	N.A.			N.A.	
	Pressurization	N.A.	Provided			MR		
	e. No. of continuous staircases	01no.	R TI SE	N.A.			N.A.	
	to terrace.	orno.		01no		A	NMR	
	g. Width of Corridor	N.A.		N.A.	5			
111	h. Door Size	1.5m	1	-			N.A.	
	Compartmentation	.ioiii	Spell he	1.65n			MR	
, 1	Fire check door	Required			Droy dela 1			
	Sealing of electrical shafts	Required			Provided		MR	
	Fire rating of shaft door		N.A. N		Provided		MR	
	Water curtain				N.A.		N.A.	
	Fire Dampers						N.A.	
		N.A.	* 1		N.A.		N.A.	
	Smoke Management System.	-				8	· \	
	January System.							
	Basement	30a/c per hour N.A					8	
×.			-	Drovided			N.A	
		12 a/c p	er	Provid	ed		MR	
×								

Ceremonial Hall Adjoing, Auditorium President Estete R.P. Brau

5.	Fire Extinguisher	g. Auditor unn	tresident 8	Stell	R.P. Bh		
	Total numbers	0 000			0		
	types	8 nos.	12 nos.	MI			
	IS marking	WCO ₂ & ABC	WCO ₂ & ABO	C M	7		
6	First-aid-Hose Reels.	ISI marked	ISI marked	MF	7		
	Total numbers of hall floor	0000		OLINIO AND DE			
	Length of hose reel hose	02nos.	04nos.	MF			
	Nozzle diameter		30 m 30m		MR		
7	· · · · · · · · · · · · · · · · · · ·	5mm	5mm	MF	3		
_	Automatic fire detection and alarming system. Type of detectors Heat & Smoke Heat						
	Location of main panel	Heat & Smoke Heat & Smo			M		
	Location of repeater panel	Ground floor Ground Flo		loor	M		
	Alternate source of power	N.A. N.A.			N.		
	Hooters	Required	Provided	Provided			
_		Required	Provided		MF		
8	MOEFA	Required	Provided		MF		
	Diff	5.00		an d	ivii		
9	Public address System.	N.A.	N.A.	- HE.	N.		
10	Automatic Sprinkler System.						
	Basement	N.A.	N.A.	N.A			
	upper floor	Required	Provided	MR			
	sprinkler above false ceiling	N.A.	N.A.	N.A			
11	Internal Hydrants		14.7 (.	IV.A	•		
	size of riser/down-comer	100	100mm	La Carte	MD		
	Number of hydrants in hall floor	02nos.	04nos.		MR MR		
		e 811	041103.		IVIL		
	Hose Box	Required	04 nos. Provid	led	MR		
0	V						
2	Yard Hydrants.	a e 2		A			
	Total number of hydrants	04nos.	04nos.	MR			
	Hose Box	04nos.	04nos.	MR			
13	Pumping Arrangements.			1			
	Ground Level						
	Ground LevelDischarge of main Pump	Required	Provided		MR		
	Head of Main Pump	2850LPM	2850LPM	markey o	MR		
	Number of main pumps	70m	70m		MR		
	Jockey pump out put	02Nos.	02Nos.		MR		
	Jockey pump head	180&280LPM	180 &280LPM		MR		
	Standby pump out put	70m(Each)	70m(Each)		MR		
	Standby pump Head	2850LPM.	2850LPM		MR		
	Auto Starting /Manual stopping	70m	70m		MR		
	Pump House Access	Required	Provided		MR		
	Terrace Level	Required	Provided		MR		
	Discharge of pump	Required	Provided		MR		
	Head of the Pump	450 LPM	450LPM		MR		
	Power supply	40 Mtrs.	40Mtrs.		MR		
	Auto Starting of pump	Required	Provided		MR		
1	O	Required	Provided				

Ceremonial Hell Asjoring Auditorium President Estate R. P. Bhawan N.D.

14	Captive Water Storage for Fire Fighting.					
	Underground tank capacity	50000Liters.	200000Liters.	MR		
	Draw-off connection	Required	Provided	MR		
	Fire service inlet Access to tank Overhead Tank servesits	Required	Provided	MR		
1		Required	Provided	MR		
1 -	Overhead Tank capacity	5000Ltrs.	5000Ltrs.	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
1	Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
1	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
> 1	Communication in lift car	Required	Provided	MR		
	Firemen's grounding switch Lift Signage	Required	Provided	MR		
		Required	Provided	MR		
17	Standby power supply	Required	Provided D.G. Set	MR		
18	Refuge Area.					
	Total area	N.A.	N.A.	N.A.		
	Location	N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel	N.A.	N.A.	N.A.		
18	Flow switch panel PA system panel	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
	Batter backup Building Floor Plans	N.A.	N.A.	N.A.		
	· ·	N.A.	N.A.	N.A.		
20	Special Fire Protection systems for of special Risks, if any:	N.A.	N.A.	N.A.		

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Name

D.O.(South)

Vedpal

Designation ADO

- Nulou