FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/OS/school/2015/W2/98

Dated: 20/01/15

FIRE SAFETY CERTIFICATE

Certified that the Vijay Public School located at Ground Floor only at 51-A,Inderlok, Delhi – 110035 of a premises comprised of Ground + 02 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/2012/121 Dated 13-01-2012. The premises was re inspected by the officers concerned of this department on 24-12-2014 in the presence of Sh. Savitri Rawat (Principal) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance DOE Circular 3298-3398 Dated 01-03-2011 and that the premises is fit for occupancy class "Educational" Group B with effect from 10 pt 15 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .. 20. / .o.l. / 1.5..... at New Delhi by.

(Santokh Singh) Chief Fire Officer, Ph: 011 – 23414250.

Copy to:

1. The Principal, Vijay Public School, Ground Floor 51-A, Inderlok, Delhi – 35

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. The 1st & 2nd Floors shall be not used strictly for school activities or other hazardous activities.

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Vijay Public School, 51-A, Inderlok, Delhi-35

2. Type of Occupancy : Educational (School running at Ground Floor in a building comprising Ground + 2 Upper Floor, 1st & 2nd Floors are being used for storage of old furniture, household etc)

3. Type of Case : Renewal

4. Details of previous NOC : F-6/DFS/MS/School/2012/121 dated

13/01/2012

5. Fire Safety directives Letter No.: 3298-3398 dated 01-03-2011

6. Date of inspection : 24-12-2014

Plot Area - 180 M² 7. Name of the Inspecting Officer: ADO (WP) Covered Area -180 M² No. or Class Rooms-4

8. Name and designation of Officer No. of Student- 120

from the building side : Smt Savitri Rawat(Principal)

9. Year of Construction : 1990

10. Applicant's letter No. : Form J Dated 28/11/2014

| | 10. Applicant stetter No. | | : Form J | Dated | 1 28/11/20 | 14 | |
|--------------------------------|---|-------------------|--------------------------------------|----------|------------------|--|--|
| S No | No prevention and fire safety U/R 33 | | Cr.No.3298- 3398 dated 1-3- 11 | | Provided at site | THE THE PARTY OF T | |
| 1. | Access of building | | | | 1 | | |
| Road width | | Accessible | | I | Provided | | MR |
| | Gate width | Accessible | | Provided | | | |
| | Width of internal road | NA | 4 2 | | VA | | MR |
| 2. | | | | | 17. | | NA |
| | Number, width, Type & Arrangements of exits | | | | | | |
| | a. Number of staircases | | | | | | |
| | Upper floors | NA | | NA | | A | |
| | Basements | NA | | NA | | - | THE RESERVE TO A PROPERTY OF THE PARTY OF TH |
| | b. Width of staircases | NIA INTERNATIONAL | | 1711 | 1 12 1 | | |
| | Upper floors | NA | | NA | | | |
| | Basements | NA | | | | | NA |
| | c. Protection of exits | 1477 | Local de Prima | NA | | | NA |
| | • Fire check door | | | | | Harry . | |
| | | NA | | NA | | | NA |
| | i ressurization | NA | | NA | | | NA |
| | o or continuous | NA | | NA | | 1 11 | NA |
| | staircase to terrace | NA | 16 16 1 mm | | | | |
| | e. Width Of Corridor | | 4.5 1 1 | NA | | 4 | NA |
| | f. Door Size | 1 mtr | | Provi | | | MR |
| | | 7 | | 2X1r | ntr(Room | S | |
| | | | | havir | g>45 stuc | lents | |
| | | | the book of | | HELPHIN I | | |

| . (| Compartmentation | | | | S14 |
|-----|--|------------------------|----------|--|--|
| | Fire check door | NA | NA | | NA |
| | Sealing of electrical shafts | NA | NA | | NA |
| | • Fire Rating of shaft door | NA | NA | _111 | NA |
| | Water Curtain | NA | NA | 3 | NA |
| | • Fire Dampers | NA | NA | | NA |
| | Smoke managements System | | | | |
| | *** | NA | NA | :8 | NA |
| | | NA | NA | N E | NA |
| | • Upper floors | 1112 | | | |
| | Fire Extinguishers | • Total numbers 02nos. | | | MR |
| | | | | Provided | |
| | • Types | ISI marked | Provided | | MR |
| | • IS marking | 101 11141114 | | | |
|). | First – Aid Hose Reels | NA | NA | | NA |
| | • Total numbers on each | IVA | | | |
| | floor | | NA | 1/10/10 | NA |
| | • Length of hose reel hose | 30m | NA | e del Paristone e procure a la composition de la composition della | NA |
| | Nozzle diameter | | | | A KANTAN AND A |
| 7. | Automatic fire detection and alar | NA | NA | NA | |
| | Type of detectors | NA | NA NA | NA | The second of |
| | Location of Main Panel | NA | NA | NA | |
| | Location of Repeater | INA | 1 17 1 | | |
| | Panel | NA | NA | NA | |
| | Alternate source of | INA | 1111 | | |
| | power | NA | NA | NA | |
| | Hooters' Location | | NA | NA | |
| 8. | MOEFA | NA | NA NA | NA | |
| 9. | Public Address System | NA | INA | INT | |
| 10. | Automatic Sprinkler System | N. I. A. | NA | NA | |
| | Basements | NA | NA NA | NA | |
| | • Upper Floor | NA | NA NA | NA NA | |
| | Sprinkler above false | NA | IVA | 1 1 1 1 | |
| | ceiling | | | | |
| 11. | | D.T.A | NA | NA | |
| | Size of riser/down- | NA | NA NA | NA NA | THE PARTY OF THE P |
| | comer | NA | | NA | 7 7 7 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 |
| | Number of hydrants per | NA | NA | INA | |
| | floor | | | | |
| | Hose Box | | | | E A A CANADA |
| 12. | Yard Hydrants | | | | |
| | Total number of | NA | NA | NA | |
| | hydrants | | | | |
| | v v | NA | * NA | NA | |
| | Hose BoxPumping Arrangements: | | | 1 | V. |

| A | | R/ 2 | | |
|-----|--|--------|---------|--------------|
| | | 1.) | | |
| | | | | |
| | Ground Level | 271 | | |
| | Discharge of main pump | NA | NA | NA |
| | Head of main pump | NA | NA | NA |
| | Number of main pumps | NA | NA | NA |
| | Jockey pump out put | NA | NA | NA |
| | Jockey pump head | NA | NA | NA |
| | Standby Pump out put | NA | NA | NA |
| | > Standby Pump Head | NA | NA | NA |
| | > Auto Staring/Manual | NA | NA | NA |
| | stopping | | | |
| | Pump House Access | NA | NA | NA |
| | • Terrace level | | | |
| | Discharge of pump | NA | NA | NA |
| | Head of the pump | NA | NA | NA |
| | Power supply | NA | NA | NA |
| | > Auto starting of pump | NA | NA | NA |
| 14. | Captive water Storage for fire fig | hting: | | 1 6 A |
| | Under ground tank | NA | NA | NA |
| | capacity | | | |
| | Draw off connection | NA | NA | NA |
| | Fire service inlet | NA | NA | NA |
| | Access to tank | NA | NA | NA |
| | Overhead Tank capacity | NA | NA | NA |
| 15 | Exit Signage | NA | NA | NA |
| 16. | Provision of Lifts | ÷ | | |
| | Pressurization of Lift Shaft | NA | NA | NA |
| | Pressurization of lift | NA | NA | NA |
| | lobby Communication in lift | N.1.A | 214 | |
| | Car | NA | NA | NA |
| | Fireman's Grounding | NA | NA | NA |
| | Switch | | | |
| | Lift Signage | NA | NA | NA |
| 17. | Standby power supply | NA | NA . | NA |
| 18. | Refuge Area | 6. | - 1-770 | • 11 12 12 1 |
| | > Total area | NA | NA | NA |
| | Location | NA | NA | NA |
| 19. | Fire control room | | | |
| | Detector system panel | NA | NA | NA |
| | > Flow Switch Panel | NA | NA | NA |
| | PA System Panel | NA | NA | NA |
| | Battery backup | NA | NA' | NA |
| | Building Floor Plans | NA | NA NA | NA |
| | | | - 14 4 | |

| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | NA | NA | NA | | |
|-----|---|---|--|---------------------------------|---|----------------|
| | Note:-General requirements for dated 01/03/2011. 1. Escape route | | arMCB and tunder the stairs | nd ELCB | Providec | 1. |
| | The fire protection system found functional at the time of ins Keeping in view the substitution and fire safety require Safety Certificate under rule shortcomings as | pection. tantial comp red under th 35 of the | oliance of the m e rules it is rec Delhi Fire So | inimum s commend ervice R | standards or ed to grant ules 2010/ | n fire Fire |
| | Signature of the Inspecting Office Officer | | | gnature o | f the Inspec | ting |
| | Name Udee Vir | pingl | | ame esignation | | |