GOVERNMENT OF NATIONAL CAPITALTERRITORYOF DELHI HEAD OUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:-011-23412593

E-mail ID: cfohq.dlfire@nic.in

No. F6/DFS/MS/GH/2015/ NDZ/111

Dated 22/01/15

FIRE SAFETY CERTIFICATE

Certified that the Yuvraj Deluxe Guest House located at 38, Arakashan Road, Pahar Ganj, New Delhi comprises of Basement + Ground + Five upper floor having 37 guest rooms (Basement is used for storage purposes), Ground floor has reception + Office + 05 guest rooms, 1st floor to 4th floor has 08 guest rooms at each floor and 5th floor is sealed by MCD was granted NOC by this department vide letter No.F6/DFS/MS/GH/2012/1174 dated 29-03-2012. The premises was re-inspected by the officer concerned of this department on 19-12-2014 in the presence of Mr. Anil (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 for 37 Guest rooms at Ground floor + First floor + Second floor + Third floor + Fourth floor with effect from --2-2-1-01-1--2014 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010

(**Dr.G.C.Misra**) Chief Fire Officer Delhi Fire Service Ph – 011-23414333

OC M

Copy to:-

1. The Addl. Commissioner of police (Lic), 1st floor, P S Defence colony, New Delhi for information letter No. 44651/Joint C.P./Lic.(H) dated New Delhi 02/12/2014.

2. Mr. Anil (Manager) Yuvraj Deluxe Guest House located at 38, Arakashan Road, Pahar Ganj, New Delhi.

3. The Commissioner North Delhi Municipal Corporation with a request to measure the height and appraise this department.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

INSPECTION REPORT

1. Name & address of the building : Yuvraj Deluxe Guest House at 38, Arakashan Road,

Pahar ganj, New Delhi.

2. Type of Occupancy : Residential (Guest house) B + G + 5floors (37 Guest rooms)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2012/1174 dated 29/03/2012

5. Fire Safety directives Letter No. : NA

6 Date of inspection : 19/12/2014

7 Name of the Inspecting Officer : M. K. Sharma (Assistant Divisional Officer)

8 Name and designation of Officer

from the building side : Sh. Anil (Manager)

9 Year of Construction : 2001

10. Applicant's letter No. : 44651/Joint. C.P./Lic.(H) dated, New Delhi the 02/12/2014.

S No	Minimum standards on fire prevention and fire safety U/R 33		Existing	Provided at site	Remarks
			Requirements	(PPS Area)	MR/NMR
					(PPS Area)
1.	Access of building				
	•	Road width	NA	6 Mtr.	MR
	•	Gate width	NA	NA	NA
	•	Width of internal road	NA	NA	NA
2.	Number, width, Type & Arrangements of exits				
	a. Nu	mber of staircases			
	• Up	per floors	1 No.	1 No.	MR
	• Ba	sements	1 No.	1 No.	MR
	b.Width of staircases				
	• Up	per floors	0.80 Mtr.	1.25 Mtr.	MR
	• Ba	sements	0.80 Mtr.	1.25 Mtr.	MR
	c. Protection of exits				
	Fir	e check door	NA	NA	NA

	• Pressurization	NA	NA	NA
	d. No of continuous staircase to terrace	1 No.	1 No.	MR
	e. Width Of Corridor	NA	NA	NA
	f. Door Size	1.0 Mtr.	1.0 Mtr.	MR
3.	Compartmentation			
	Fire check door	NA	NA	NA
	 Sealing of electrical shafts 	NA	NA	NA
	 Fire Rating of shaft door 	NA	NA	NA
	Water Curtain	NA	NA	NA
	• Fire Dampers	NA	NA	NA
4	Smoke managements System			
	Basements	30 ACPH	Mechanical	MR
	• Upper floors	12 ACPH	NATURAL	MR
5	Fire Extinguishers			
	Total numbers	18 Nos.	20 Nos.	MR
	• Types	ABC, CO ₂ , Wco ₂	ABC, CO ₂ , Wco ₂	MR
	IS marking	Required	Provided	MR
6	d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size Compartmentation Fire check door Fire check door Fire Rating of shaft door Water Curtain Fire Dampers Basements Upper floors Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose Noble Automatic fire detection and alarming system Type of detectors Location of Repeater Panel Automatic Sprinkler			
	Total numbers on each floor	01	01	MR
	 Length of hose reel hose 	30 Mtr.	30 Mtr.	MR
	Nozzle diameter	05 MM	05 MM	MR
7	Automatic fire detection and alarming sys	stem		
	Type of detectors	NA	NA	NA
	Location of Main Panel	NA	NA	NA
	Location of Repeater Panel	NA	NA	NA
	Alternate source of power	NA	NA	NA .
	 Hooters' Location 	NA	NA	NA
8	MOEFA	Required	Provided	MR
9	Public Address System			MR
10	Automatic Sprinkler	,		
	Basements	Required	Provided	MR

4			NA	NA	NA
-	U	Upper floor Sprinkler above false ceiling		NA	NA
			NA		
11		Hydrants	100 MM	100 MM	MR
	1 1	Size of riser/down-comer		01	MR
	•]	Number of hydrants per floor	01	01	MR
	•	Hose Box	01	O1	
12	Yard H	ydrants		NIA	NA
	•	Total number of hydrants	NA	NA	NA
		Hose Box	NA	NA	1471
13	Pumpir	ng Arrangements			
		Ground Level			NIA
	•	Discharge of main pump	NA	NA	NA
		Head of main pump	NA	NA	NA
		Number of main pumps	NA	NA	NA
	•	Jockey pump out put	NA	NA	NA
	•		NA	NA	NA
	•	Jockey pump head	NA	NA	NA
	•	Standby Pump out put	NA	NA	NA
	•	Standby Pump Head	NA	NA	NA
	•	auto Staring/Manual stopping	NA	NA	NA
	•	Pump House Access	NA	NA	NA
	0		450 LPM	450 LPM	MR
9	•	Discharge of pump	30 Mtr.	30 Mtr.	MR
	•	Head of the pump	Required	Provided	MR
	•	Power supply	Required	Provided	MR
	•	Auto starting of pump	Required		
			NA	NA •	NA
14	Cap	tive water Storage for fire fighting	NA	NA	NA
		 Under ground tank capacity 		NA	NA
		 Draw of connection 	NA	NA	NA
		• Fire service inlet	NA	NA NA	DA DA
	7-6	 Access to tank 	NA	N. P.	

W

	Overhead Tank capacity	5000 ltr.	5000 ltr.	MR
15	Exit Signage	Required	Provided	MR
16	Provision of Lifts	Provided		
	 Pressurization of Lift Shaft Pressurization of Lift John 	NA	NA	NA
	1 1000y	NA	NA	NA
	• Communication in lift Car	Required	Provided	MR
	Fireman's Grounding Switch Life Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	Provided	MR
18	Refuge Area			
	Total area	NA	. NA	NA
	• Location	NA	NA	NA,
19	Fire control room		Provided NA NA Provided Provided Provided Provided NA	
	Detector system panel	NA	NA	NA
	 Flow Switch Panel 	NA	NA	NA
	PA System Panel	NA	NA	NA
	Batter backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA
20	Special Fire Protection Systems for	Required	ABC,Co ₂	MR
	Protection of special Risks, if any;	8	. 2	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no.

F6/DFS/MS/GH/2012/1174 dated 29/03/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Designation:- A. D.O. (CC)