GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

Fax:-011-23412593 E-mail ID: cfohq.dlfire@nic.in

No. F.6/DFS/MS/GH/2015/ HD2 148

Dated:

02/02/15

FIRE SAFETY CERTIFICATE

Certified that the Hotel Blue Sapphire located at 3351-54, Christen Colony, Bank Street, Karol Bagh, New Delhi-110005 comprises of Basement, Ground floor + Four Upper floors, using basement as hall, Ground floor as reception, office, hall, shops and staff pantry, first floor having nine guest rooms and one store room, second floor having five guest rooms and one store room, third floor having nine guest rooms and one store room (Total 23 guest rooms) and one staff room on terrace was granted NOC by this department vide letter No.F.6/DFS/MS/GH/2012/135 dated 13-01-2012. The premises was re- inspected by the officer concerned of this department on 24-01-2015 in the presence of Mr. Manjeet Singh and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 Guest House for 23 guest rooms with effect from -0-2-1-2-2015 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph-011-23414333

Copy to:-

1. The Joint Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049 w.r.t. letter No. 547/Joint C.P./Lic.(H) dated New Delhi 07-01-2015

2. Mr. Suman Anand (Owner) Hotel Blue Sapphire, 3351-54, Christen Colony, Bank Street, Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

| 100 | 1 | Name & address of the training | CTION REPORT | Γ | | | | |
|---------|------|--------------------------------------|--|-----------------------|-------------------------|--|--|--|
| | 1. | Name & address of the building : | Hotel Blue Sapph | nire, 3351-54, Christ | en Colony, Bank Street, | | | |
| | 2. | Type of Occupancy | Naroi Bagn, New Delhi-110005. | | | | | |
| | 3. | st House) <mark>B+G+4 Flo</mark> | oor total guest rooms-23 | | | | | |
| | | Type of Case Details of Previous NOC | Renewal | | | | | |
| | | Fire Safety directives letter No | | | | | | |
| | 6. | Date of inspection : | | | | | | |
| | | Name of Inspecting Officer | . 24/01/2015 | | | | | |
| | 8. | Name and designation of officers | ne and designation of officers Dy. C.F.O Rajesh Panwar | | | | | |
| | | m the building side | | | | | | |
| | 9. | Year of Construction | tion : Before 2002 | | | | | |
| | 10. | Applicant's letter No. | 5/17/Joint C D/Lie (U) de N. D. U. and A. | | | | | |
| S. No. | N | Ainimum Standards on fire prevention | imum Standards on fire prevention NRC/RRI Provide the New Deini 07/01/2015 | | | | | |
| | a | ind fire safety U/R 33 | Requirement | Provided at site | | | | |
| 1. | A | Access to building | | special area | MR/NMR | | | |
| | | Road width | Accessible | 12 mtr | MD | | | |
| A Trans | | Gate width | NA | NA | MR NA | | | |
| | | Width of internal road | NA | NA | NA NA | | | |
| 2. | N | umber, Width, Type & Arrangement | of Exits | - 1. A | IVA | | | |
| | a. | Number of staircases | | | | | | |
| 4 | | Upper Floors | One | 0 | | | | |
| | | Basements | One | One | MR | | | |
| | b. | Width of staircases | One | One | MR | | | |
| | | | 105 | | | | | |
| | | Upper Floor | 125 cms | 107 cms to 119 | MR, Old Case | | | |
| | | • Basements | 125 cms | cms | | | | |
| | C | Protection of exits | 123 cms | 114 cms | MR, Old Case | | | |
| | 0. | Fire check door | | | | | | |
| | | Pressurization | NA | NA | NA | | | |
| | d. | No. of continuous staircases to | NA | NA | NA | | | |
| | | terrace | | | | | | |
| | | | One | One | MR | | | |
| | e. | Width of Corridor | 1.0 Mtr | 2.0 Mtr | MR | | | |
| | | | | | IVII | | | |
| | f. | Door Size | 1.0 Mtr. | 97om V 204 | | | | |
| 2 | | | 1.0 Mil. | 87cm X 204 cm | MR, Old Case | | | |
| 3. | Co | mpartmentation | | | | | | |
| | | Fire check door | NA | 3 | | | | |
| | | Sealing of electrical shafts | | NA | NA | | | |
| | | • Fire Rating of shaft door | NA | NA | NA | | | |
| | | Water Curtain | NA | NA | NA | | | |
| | | • Fire Dampers | NA | NA | | | | |
| 4. | | | NA | NA NA | NA NA | | | |
| 4. | Sm | oke Management System | | 1111 | INA | | | |
| | | • Basements | 30 ACPH | Exhaust Fans are | 100 | | | |
| | | | JO ACITI | provided | MR | | | |
| | | Upper floors | 12 ACPH | Natural | MR | | | |
| | | | | Ventilation | IVII | | | |
| | Fire | Extinguishers | | | | | | |
| 7 | | Total numbers | Two at each floor | Provided | 1/0 | | | |
| | | • Types | Co2, Water Co2 | | MR | | | |
| | | IS marking | | Provided | MR | | | |
| | Fire | t-Aid Hose Reels | ISI marked | ISI marked | MR | | | |
| | | | | | | | | |
| | | rotal Hallibers off Each 1100 | One | Provided | MR | | | |
| | | cengarior nose reel nose | 30 m | Provided | MR | | | |
| | | NO7710 diameter | | | | | | |
| | | Nozzle diameter | 5 mm | Provided | MR | | | |

| | Automatic fire detection and alarming sys | tem | | 27.1 | | | | |
|-----|--|----------------------|---------------|--------------|--|--|--|--|
| | Type of detectors | NA | NA | NA | | | | |
| | Location of Main Panel | NA | NA | NA | | | | |
| | Location of Repeater Panel | NA | NA | NA | | | | |
| | Alternate source of power | Required | D.G set of 45 | MR | | | | |
| | Hooters' Location | | KVA NA | NA | | | | |
| | 1100ters Education | NA Required | Provided | MR | | | | |
| • | MOEFA | Required | Provided | MR | | | | |
| • | Public Address System | Required | | | | | | |
| 0. | Automatic Sprinkler System | Required | Provided | MR | | | | |
| | Basement Ground Floor | NA | NA | NA | | | | |
| | Ground Floor Sprinkler above false ceiling | NA | NA | NA | | | | |
| 1 | Internal Hydrants | | | NT A | | | | |
| 1. | Size of riser/down-comer | NA | NA | NA NA | | | | |
| | Number of hydrants per floor | NA | NA | NA NA | | | | |
| | Hose Box | NA | NA | INA | | | | |
| 2. | Yard Hydrants | | | NA | | | | |
| 2. | Total number of hydrants | NA | NA | NA NA | | | | |
| | Hose Box | NA | NA | INA | | | | |
| 13. | Pumping Arrangements | | | | | | | |
| 10. | Ground Level | | 3.7.4 | NA | | | | |
| | Discharge of main Pump | NA | NA | | | | | |
| | Head of Main pump | NA | NA | NA | | | | |
| | Number of main pumps | NA | NA | NA | | | | |
| | Jockey Pump out put | NA | NA | NA | | | | |
| | > Jockey pump head | NA | NA | NA | | | | |
| | > Standby Pump out put | NA | NA | NA | | | | |
| | > Standby Pump Head | NA | NA | NA | | | | |
| | Auto Starting/ManualStopping | NA | NA | NA * | | | | |
| | > Pump House Access | INA | 2 2 2 | | | | | |
| | Terrace level | 450 I DM | 450 LPM | MR, Old Case | | | | |
| | > Discharge of pump | 450 LPM | 30 M | MR | | | | |
| | Head of the pump | 30 M | Provided | MR | | | | |
| | Power Supply | Required | | NA | | | | |
| | Auto Starting of pump | NA | NA | 14/4 | | | | |
| | | | | | | | | |
| 14. | Captive Water Storage for fire fighting | g NA | NA | NA | | | | |
| | Underground tank capacity | NA | NA | NA | | | | |
| - | > Draw-off connection | NA NA | Provided | MR | | | | |
| | Fire service inletAccess to tank | NA NA | NA | NA | | | | |
| | Overhead Tank capacity | | 5000 Ltr | MR, Old | | | | |
| | Overnead Tank capacity | 5000 Ltr Required | Provided | MR | | | | |
| 15. | Exit Signage. | Roquitou | | | | | | |
| | | | | | | | | |
| 16. | Provision of Lifts. | NA | NA | N | | | | |
| | Pressurization of Lift Shaft | | NA | 7 | | | | |
| | Pressurization of Lift lobby | NA Required | | | | | | |
| | Communication In lift Car | | | | | | | |
| | Fireman's Grounding Switch | Required | | | | | | |
| | Lift Signage | Required | l Provided | | | | | |

| 17. | Standby power supply | Required | Provided | MR | | | |
|-----|---|----------|----------|----|--|--|--|
| 18. | Refuge Area. | | | | | | |
| | > Total Area > Location | NA | NA | NA | | | |
| | | NA | NA | NA | | | |
| 19. | Fire Control Room | | | | | | |
| | Detector System Panel | NA | NA | NA | | | |
| | Flow Switch Panel PA System Panel Batter backup Building Floor Plans | NA | NA | NA | | | |
| | | NA | NA | NA | | | |
| | | Required | Provided | MR | | | |
| | | NA | NA | NA | | | |
| 20. | Special Fire Protection System for Protection of special Risks, if any: | NA | NA | NA | | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2012/135 dated 13.01.2012 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Name:- Rajesh Panwar

Name

Designation

Signature of Inspecting Officer

Name.- Rajesh Panwar

Designation:- Dy. C.F.O (NDZ)

Signature of Inspecting Offi