GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2015/ 52 140

Dated: 02 02 15

FIRE SAFETY CERTIFICATE

Certified that the **Hotel Florence Inn** located at 15A/6, WEA, Karol Bagh, New Delhi-110005 is comprised of Basement, Ground floor plus four upper floors, using basement as Hall, ground floor as reception, office, store & 02 guest rooms, first, second & third floor each having 08 guest rooms respectively (Total 26 guest rooms) and one store room on fourth floor was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2012/60 dated 06.01.2012 owned/ occupied by Sh. Arun Kumar Soni. The guest house building was re- inspected by the officer concerned of this department on 22.01.2015 in the presence of Sh. Abishek Chanda (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on OHOULS at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.356/Joint C.P./Lic.(H), Dated 06.01.2015)
- Sh. Arun Kumar Soni (Owner)
 Hotel Florence Inn, 15A/6,
 WEA, Karol Bagh, New Delhi 110005.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	INSPEC	TION REPORT					
	1. Name & address of the building:	Hotel Florence	e Inn. 15Ale	JEA Karalan			
	2. Type of Occupancy	ding: Hotel Florence Inn, 15AG, WEA, Karol Bagt Residential (Guest House)					
	3. Type of Case 4. Details of Provious Noc.	: New Case/Renewal					
	Secons of Lightnes MAC.	Letter No. F.6/D	FS/MS/GH/2012/6	o Date oc. ol.			
		22.01.2015 A.D.O P.S. Dahiya					
	- over or mapertion						
	7. Name of Inspecting Officer						
	8. Name and designation of officers From the building side :		U				
	9. Year of Construction	Sh. Abishek Chanda (Manager) Before 2006					
	10 1						
S.	Minimum Standards on fire	356 Toint C.	P/LIC. (H) do	ted 06.01.2015			
No.	prevention and fire safety U/R 33	NBC/BBL	Provided at	Remarks			
1.	Access to building	Requirement	site	MR/NMR			
	Road width	Acces 1885					
	• Gate width	Accessible	09mtr Approx	A 100 100 100 100 100 100 100 100 100 10			
		-	167cms	MR			
2.	Width of internal road Side Roa	d	5:50 mtr	MR			
Now F	Number, Width, Type & Arrangement of Exits a. Number of staircases						
	• Upper Floors	One	One	MR, Old Cas			
	Basementsb. Width of staircases	- do -	-do-	- do -			
	• Upper Floor						
	Basements	125cms	129 cms	MR			
	c. Protection of exits	125 cms	127 cms	MR			
	• Fire check door						
	1.	Special Control of the Control of th					
	d. No. of continuous staircases to						
	terrace to terrace						
	e. Width of Corridor		One	-			
	f. Door Size		176 cms	The second secon			
		•	86 cms x205cm				
3.	Compartmentation		OU CING X 205 Cm				
** ************************************	Fire check door						
			-				
	Sealing of electrical shafts Fire Bating of about		Sealed	all provides and the second se			
	Fire Rating of shaft doorWater Curtain	•					
-	 Fire Dampers 						
.	Smoke Management System						
	 Basements 	30 a/c per	Exhaust fans				
	 Upper floors 	hour	are Provided	MR			
			Natural Ventilah	on MR			

1116	12 a/c por	1				
			i.			
	Hour	-	-			
Fire Extinguishers						
Total numbers	Two at each floo	Paul	MR			
Types	Co, WCo					
 IS marking 	ISI marked		MR			
First-Aid Hose Reels		131 Markea	MR			
 Total numbers on each floor 	One	Parille	D 00			
	30 m	1	MR			
 Nozzle diameter 	5 mm		MR			
Automatic fire detection and alarming	system	- 000	MR			
4 1000 10 000		N9 A C C - 4 : A : D : C :				
		BRCKVA	MR			
The state of the s	0 1	Staircase				
The service was a copy of a public of the service o	Kequired		MR			
	- do -	- do-	MR			
The state of the s		1				
	Required	Provided	MR			
		-				
The state of the s			+			
			+			
THE PART OF THE PA	1	J.				
The state of the s						
The second secon						
1-1-1 (1 1500) NO.		(r	, *			
Head of Main pumpNumber of main pumpsJockey Pump out put		-				
		-				
		.0	The second secon			
	•					
, and act pac						
S Ctandby Dime 11 1	£					
> Standby Pump Head		i.				
Standby Pump HeadAuto Starting/Manualstopping			-			
	 Types IS marking First-Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System Automatic Sprinkler System Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps 	• Total numbers • Types • IS marking First-Aid Hose Reels • Total numbers on each floor • Length of hose reel hose • Nozzle diameter Automatic fire detection and alarming system • Type of detectors • Location of Main Panel • Location of Repeater Panel • Alternate source of power • Hooters' Location MOEFA Public Address System Automatic Sprinkler System • Basement • Upper Floor • Sprinkler above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants • Total number of hydrants • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put	Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location Basement Upper Floor Sprinkler System Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Head of Main pump Number of main pumps Jockey Pump out put			

Т	Pump House Access			3			
	Terrace level						
and the same of th	Discharge of pump	-	450 LPM	MR, Old Co			
	> Head of the pump			MR. OldCo			
	Power Supply	Required	33 M Provided	MR			
	Auto Starting of pump	-					
		9					
4.	Captive Water Storage for fire fighting			9			
	 Underground tank capacity 			*			
	Draw-off connection	•		-			
12.	Fire service inlet		Provided	MR			
1	Access to tank	1	-				
	 Overhead Tank capacity 	10000 Ltr	10000 Ctr	MR			
15.	Exit Signage.	Required	Provided	MR			
15							
16.	Provision of Lifts.			-			
	Pressurization of Lift Shaft	-					
	Pressurization of Lift lobby			D . O			
	Communication In lift Car		Provided	MR			
	 Fireman's Grounding Switch 	Required	- do -	MR			
	 Lift Signage 	- do -	- do -	MR			
	S. the recover supply	Required - do - Required	Provided	MR			
17.	Standby power supply						
18.	Refuge Area.						
	> Total Area						
	Location						
	f						
19.	Fire Control Room						
1.7.	Detector System Panel						
	Flow Switch Panel		_				
	PA System Panel						
	Batter backup		Provided	MR			
	Building Floor Plans		- I sovided				
20.	Special Fire Protection System for Protection of special Risks, if any:						
	Protection of special kisks, it ally.						

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6 DFS MS 6H 2012 60 dated 06.01.2012 renewal under rule 35 of the

Delhi Fire Service rules 2010 is recommended.

Note: - The fourth floor of the Guest house was sealed by MCD November 2011.

Signature of Inspecting Officer

Name P.S. Dahiya
Designation ASSH. Divisional Officer

Designation

Signature of Inspecting Officer

Name