GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

No. F6/DFS/ars/ school/2015/32/229 Dated: 17/02/15

FIRE SAFETY CERTIFICATE

Certified that S.S. Public School located at B-545, Sangam Vihar, New Delhi- 110062 was granted N.O.C. by this department vide letter No. F6/DFS/MS/2006/2163 dated 22/08/2006 for ground and first floor. The school building was re-inspected by the officer concerned of this department on 03.02.2015 in presence of Mr. Jaiparkash, manager of the school and found that the management has constructed one more upper floor and now the school building is comprised of ground plus two upper floors and also that the school management have complied with the fire prevention and fire safety requirements in accordance with the Delhi Fire Service Act-2007 & Rules- 2010 and that the school building is fit for occupancy class "Educational" with effect from the date of issue of this certificate for a period of three years, subject to compliance of the under mentioned conditions.

Issued on 17/02/15 at New Delhi by.

(Dr. G.C. MI\$RA) CHIEF FIRE OFFICER

Copy to: -

- 1. The Manager, S.S. Public School, B-545, Sangam Vihar, New Delhi- 110062.
- 2. The Directorate of Education, Old Secretariat, NewDelhi-110006.

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : S.S. Public School, B-545, Sangam Vihar, New Delhi-

110062

2 Type of Occupancy : Educational

3 Type of Case : Renewal & addition of second floor

4 Details of previous NOC : F6/DFS/MS/2006/2163 dated 22/08/2006

5 Fire Safety directives letter No : Delhi Fire Service Act-2007 & Rules-2010

6 Date of inspection : 03.02.2015

7 Name of the Inspecting Officers : M.K.Chattopadhyay, ADO(M.Rd)

8 Name and designation of officers

from the building side : Mr. Jaiparkash, Manager

9. Year of Construction : 2006

10. Applicant's letter No. : SSPS/01/2014-15 dated 19.01.2015.

S.S. Public School is comprised of ground and two upper floors.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	Road widthGate widthWidth of internal road	06 mts 03 mts N/A	Provided Provided N/A	MR MR N/A	
2	Number, Width, Type & Arrangement	of Exits	7		
	a. Number of staircases				
	Upper Floors	02	02	MR	
	Basements	N/A	N/A	N/A	
	b. Width of staircases				
	 Upper Floors Basements	1.5 mts N/A	1.50, 1.12 mts N/A	MR N/A	
	c. Protection of exits				
	 Fire check door 	N/A	N/A	N/A	
	 Pressurization 	N/A	N/A	N/A	
	e. No. of continuous staircases to terrace	02	02	MR	
	g. Width of Corridor	1. 5 mts	Provided	MR	
	h. Door Size	1.0 mts	Provided	MR	
3	Compartmentation.				



		*				
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	N/A	N/A		
	 Fire Rating of shaft door 	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	• Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basements	30 a/c per hour	N/A	N/A		
	 Upper floors 	12 a/c per hour	N/A	N/A		
5	Fire Extinguishers					
	Total numbers	05 nos.	Provided	MR		
	• Types	ABC type	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system Not required					
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System					
	 Basement 	N/A	N/A	N/A		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11-	Internal Hydrants					
erymonomy as topic erymonomy contact	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		



Ms

	•		
Hose Box	N/A	N/A	N/A
Yard Hydrants.			
 Total number of hydrants 	N/A	N/A	N/A
Hose Box	N/A	N/A	N/A
Pumping Arrangements			
Ground Level			
Discharge of main Pump	N/A	N/A	N/A
Head of Main pump	N/A	N/A	N/A
Number of main pumps	N/A	N/A	N/A
Jockey Pump out put	N/A	N/A	N/A
Jockey pump head	N/A	N/A	N/A
➤ Standby Pump out put	N/A		N/A
Standby Pump Head			N/A
Auto Starting/ Manual			N/A
stopping			
Pump House Access		IN/A	N/A
		Provided	MD
			MR
	40 mts	Provided	MR
	N/A	N/A	N/A
	N/A	N/A	N/A
Captive Water Storage for fire fightin	ıg		
Underground tank capacity	N/A	N/A	N/A
	N/A	N/A	N/A
Section of the sectio	N/A	N/A	N/A
		N/A	N/A
Overnead Tank capacity	10,000 lts	Provided	MR
Exit Signage.	Required	Provided	MR
Provision of Lifts.	Not Applica	ble	
Pressurization of Lift Shaft	N/A	N/A	N/A
) I / A	NI/A	NI/A
Pressurization of Lift lobby	N/A	N/A	N/A
	Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts.	Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements Ground Level Discharge of main Pump Head of Main pump N/A Number of main pumps N/A Jockey Pump out put Standby Pump out put Standby Pump Head Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump	Vard Hydrants. Total number of hydrants Hose Box N/A N/A N/A N/A Pumping Arrangements Ground Level Discharge of main Pump N/A

40

		ν (16	
		N/A	N/A	N/A
	 Fireman's Grounding Switch 	N/A	N/A	N/A
	Lift Signage	N/A	N/A	N/A
17	Standby power supply	11/22	Commence of the Commence of th	
18	Refuge Area.	N/A	N/A	N/A
	Total AreaLocation	N/A	N/A	N/A
19	Fire Control Room	NI/A	N/A	N/A
	 Detector System Panel 	N/A N/A	N/A	N/A
	Flow Switch PanelPA System Panel		N/A	N/A
		N/A N/A	N/A	N/A
	 Batter backup 	27/4	N/A	N/A
20	Building Floor Plans Special Fire Protection Systems for	N/A Required	01 ABC type fire extinguisher is provided near elect. Panel.	
20	Protection of special Risks, if any:		near crees :	
			1 1 6000	d functional at

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, it is recommended to grant fire safety certificate under the Delhi Fire Service Act-2007 & Rules-2010.

DFA is put up for approval & signature please

Signature of the Inspecting Officer Name (M.K. CHATTOPADHYAY) Designation: - Assistant Divisional Officer