## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. 66 | DFS/as/school/2015/NDZ/267

Dated: 26/02/15

## FIRE SAFETY CERTIFICATE

Certified that the Har Govind Public School running at ground & first floor of the building comprising of small basement, ground plus first floor only, at B-1/99, Jail Road, Harsh Vihar, Delhi -110093, owned/occupied by Har Govind Public School was issued NOC vide letter no-F6/MS/DFS/2005/164 dated-28/01/2005. The school building was re-inspected by the officer concerned of this department on 17/01/2015 in the presence of Mr. C.B. Singh, Chairman of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with Circular Letter No-F16/Estate/CC/FireSafety/2011/3298to3398 dt-01/03/11 issued by Director of Education and found that the school building is fit for occupancy class "B" 'Educational Building' for ground plus first floor with effect from 26 Johns. for a period of three years, subject to conditions, printed overleaf.

Issued on ... 2 6 f ... at New Delhi by

(Dr. G.C. Misra) Chief Fire Officer Ph.011-23414333

0/0

To.

The Principal, Har Govind Public School, B-1/99, Jail Road, Harsh Vihar, Delhi –110093

Copy:-

The Dy. Director of Education, B–Block, Yamuna Vihar, Delhi-110053

## CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry
- 8. Basement shall remain sealed.

Name & address of the building

: Har Govind Public School, B-1/99,

Jail Road, Harsh Vihar, Delhi-110093

2. Building is comprised of

Ground plus first floor.

3. Type of Occupancy

: Educational

4. Type of Case

Renewal

5. Details of Previous NOC letter

: F6/MS/DFS/2005/164 dated-28/01/2005

6. Fire Safety direction letter No

: F16/Estate/CC/FireSafety/2011/3298to3398 dt-01/03/11

7. Date of Inspection

: 17/01/2015

8. Name of the Inspecting officers

: ADO Vijay Bahadur

9. Name and designation of Officer

from the building side

: Mr. C.B. Singh (Chairmen)

10. Year of Construction

: 2004

11. Applicant's letter No

: Letter No.-HGPS/621/2014, Dated- 24/12/2014

Sr.	Minimum Standards on fire	Circular	Provided at Site	Remarks				
No.	prevention and fire safety U/R33	Requirement		MR/NMR				
01	Access to Building							
	Road width	06 mtr.	09 mtr.	MR				
	<ul> <li>Gate width</li> </ul>	N/A	N/A	N/A				
	<ul> <li>Width of internal road</li> </ul>	N/A	. N/A	N/A				
02	Number, Width, Type and Arrangement of Exits							
	a. Number of Staircases							
	<ul> <li>Upper Floor</li> </ul>	02 nos.	04 nos.	MR				
	<ul> <li>Basement</li> </ul>	N/A	N/A	N/A				
	B. Width of Staircases							
	Upper Floor	1.50 mtr.	1.19, 1.14, 1.11 & 0.85 mtr.	MR				
	<ul> <li>Basement</li> </ul>	N/A	N/A	N/A				
	c. Protection of exits		очения от выз вин типо обесом на очение от					
	<ul> <li>Fire check door</li> </ul>	N/A	N/A	N/A				
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A				
	d. No. of continuous staircases to terrace	01 No.	04 Nos.	MR				
	e. Width of Corridor	1.50 mtr.	2.35 mtr.	MR				
	f. Door Size	01 mtr.	1.03 mtr.	MR				
03	Compartmentation.							
·	<ul> <li>Fire check door</li> </ul>	N/A	N/A	N/A				
	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A	N/A				
	<ul> <li>Fire rating of shaft door</li> </ul>	N/A	N/A	N/A				
	<ul> <li>Water curtain</li> </ul>	N/A	N/A	N/A				
	<ul> <li>Fire Dampers</li> </ul>	N/A	N/A	N/A				
)4	Smoke Management System.							
	Basement	N/A	N/A	N/A				
	<ul> <li>Upper floor</li> </ul>	N/A	N/A	N/A				

05.	Fire Extinguishers						
	Total numbers	05 nos.	16 nos.	MR			
	• types	ABC /CO <sub>2</sub>	ABC /CO <sub>2</sub>	MR			
	IS marking	ISI marked	ISI marked	MR			
06	First-aid-Hose Reels.						
	Total numbers on each floor	N/A	N/A	N/A			
	<ul> <li>Length of hose reel hose</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Nozzle diameter</li> </ul>	N/A	N/A	N/A			
07	Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	N/A			
	<ul> <li>Location of main panel</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Location of repeater panel</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Alternate source of power</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Hooter's location</li> </ul>	N/A	N/A	N/A			
08	MOEFA	N/A	N/A	N/A			
09	Public address System.	N/A	N/A	N/A			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	upper floor	N/A	N/A	N/A			
	sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	<ul> <li>Hose Box</li> </ul>	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level	N/A	N/A	N/A			
	Discharge of main Pump	N/A	N/A	N/A			
	➢ Head of Main Pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey pump out put	N/A	N/A	N/A			
***************************************	Jockey pump head	N/A	N/A	N/A			
e toespermentere arthu	> Standby pump out put	N/A	N/A	N/A			
	> Standby pump Head	N/A	N/A	N/A			
	Auto Starting /Manual stopping	ng N/A	N/A	N/A			
	➤ Pump House Access	N/A	N/A	N/A			
**********	Terrace Level	N/A	N/A	N/A			
	Discharge of pump	N/A	N/A	N/A			
	> Head of the Pump	N/A	N/A	N/A			
	> Power supply	N/A	N/A	N/A			
	> Auto Starting of pump	N/A	N/A	N/A			

	On the Mater Storage for Fire Fighting	N/A	N/A	N/A			
4	Captive Water Storage for Fire Fighting.	N/A	N/A	N/A			
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	> Fire service inlet	N/A	N/A	N/A			
	> Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	N/A	N/A	N/A			
15	Exit Signage.	107		and the second design of the second s			
16	Provision of Lifts.						
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	a lift car	N/A	N/A	N/A			
		N/A	N/A	N/A			
	Firemen's grounding switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
17	Standby power supply						
18	Refuge Area.						
and the second second second second second	Total area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
19	Fire Control Room	and any solid Bernard Company of the Company of the State of the Company of the C					
13		21/4	N/A	N/A			
	<ul> <li>Detector system panel</li> </ul>	N/A	N/A	N/A			
	Flow switch panel	N/A		N/A			
	PA system panel	N/A	N/A				
	Ph. II. In add to	N/A	N/A	N/A			
	The Diagram	N/A	N/A	N/A			
20	Special Fire Protection systems for	N/A	N/A	N/A			
	protection of special Risks, if any:						

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter no.-F6/MS/DFS/2005/164 dated-28/01/2005, renewal under the circular-F16/Estate/CC/FireSafety/2011/3298to3398 dt-01/03/11 is recommended.

Signature of the inspecting Officer Name- Vijay Bahadur

Designation- A.D.O