GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: <u>cfohq.dlfire@nic.in</u>, <u>Tel:-</u> 011-23414333 NO.F6/DFS/MS/GH/2015/ 52 | 298 Dated: 04/03/10

FIRE SAFETY CERTIFICATE

Delhi-13 comprised of basement/ lower ground floor (storage), ground floor (reception + 05 guest room), first floor (05 guest rooms) and second floor (05 guest rooms) was granted Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/GH/2012/150 dated 17.01.2012 and was re-inspected by the officer concerned of this department on 18-02-2015 in presence of Md. Ishrat, manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class residential (Guest house) with effect from ____OY_OS_IS _____ for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 04/03/15 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. The Joint C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

2. The Manager, Barkat Home Guest House, 7, Basti Hazrat Nizamuddin, New Delhi-13.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s Barkat Home Guest House, 7, Basti Hazrat Nizamuddin, New Delhi-13.

2 Type of Occupancy

: Lodging House

3 Type of Case

: Renewal

4 Details of previous NOC

: F.6/DFS/MS/GH/2012/150 dated 17.01.2012

5 Fire Safety directives letter No

: N/A

6 Date of inspection

: 18.02.2015

7 Name of the Inspecting Officers

: M.K.Chattopadhyay, ADO(M. Road)

8 Name and designation of officers

from the building side

: Md. Ishrat, manager

9 Year of Construction

: 2006-07

10 Applicant's letter No.

: 1453/Joint C.P./Lic.(H) dated New Delhi the 20.01.2015

The said guest house is comprised of lower ground/basement (storage), ground floor (reception + 05 guest room), first floor (05 guest rooms) and second floor (05 guest rooms)

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR		
1	Access to building					
	 Road width 	06 mts	provided	MR		
	Gate width		Directly accessible from the road	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	-	-	-		
	• Upper Floors	02	Provided	MR		
	 Basements 	02	Provided	MR		
	b. Width of staircases	-	-	-		
	Upper Floors	1.25 mts	1.45 mts, 0.42 mts	MR		
	Basements	1.25 mts each	1.25, 2.15 mts	MR		
	c. Protection of exits	-	-	_		
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	e. No. of continuous staircases to terrace	01	01	MR		
	g. Width of Corridor	1.0 mts	Provided	MR		
	h. Door Size	1.0 mts	Provided	MR		



				NI/A	
Cor	npartmentation.	N/A	N/A	N/A	
	Fire check doorSealing of electrical shafts	N/A	N/A	N/A	
		N/A	N/A	N/A	
	• Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	• Fire Dampers	1.1.1	1417		
Sn	noke Management System.	30 a/c per hour	Provided	MR	
	 Basements 	12 a/c per hour	N/A	N/A	
	• Upper floors	12 a/c per 110	14/71		
F	ire Extinguishers	1.0	Provided	MR	
	Total numbers	10	Provided	MR	
	• Types	ABC, CO ₂ ISI marked	Provided	MR	
	IS marking	1SI marked	Tiovides	1	
F	First-Aid Hose Reels.	0.1	Provided	MR	
	 Total numbers on each floor 	01	Provided	MR	
	 Length of hose reel hose 	30 m 5 mm	Provided	MR	
	Nozzle diameter		Tioridea		
7	Automatic fire detection and alarmir	N/A			
	T f datactors	N/A	N/A	N/A	
	Type of detectorsLocation of Main Panel	N/A	N/A		
		N/A	N/A	N/A	
	 Location of Repeater Panel 	N/A	N/A	N/A	
	 Alternate source of power 	N/A	N/A	N/A	
	Hooters' Location		Provided	MR	
8	MOEFA	Required	D '1-1	MR	
9	Public Address System.	Required	1 Trovides		
10	Automatic Sprinkler System.	D	d Provided	MR	
	• Basement	Required		N/A	
	• Upper Floor	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants	N/A	N/A	N/A	
	Size of riser/down-comerNumber of hydrants per floor			N/A	



,	Hose Box	N/A	N/A	N/A	
12	Yard Hydrants.			8	
and the same of th	Total number of hydrants	N/A	01 provided		
	Hose Box	N/A	01provided		
13	Pumping Arrangements.				
	Ground Level				
	Discharge of main Pump	N/A	N/A	N/A	
	Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put	N/A	N/A	N/A	
	Jockey pump head	N/A	N/A	N/A	
	Standby Pump out put	N/A	N/A	N/A	
	Standby Pump Head	N/A	N/A	N/A	
	 Auto Starting/ Manual stopping 	N/A	N/A	N/A	
	Pump House Access	N/A	N/A	N/A	
	Terrace level				
	Discharge of pump	450 LPM	Provided (450 & 225 LPM)	MR	
	Head of the pump	40 mts	Provided	MR	
	Power Supply	Required	Provided (DG Set)	MR	
	Auto Starting of pump	Required	Provided	MR	
4	Captive Water Storage for fire fighting.		2		
	Underground tank capacity	N/A	N/A	N/A	
	Draw-off connection	N/A	N/A	N/A	
	➤ Fire service inlet	Required	Provided	MR	
	Access to tank	N/A	N/A	N/A	
	Overhead Tank capacity	5,000 lts	Provided	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	➤ Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car	N/A	N/A	N/A	



		N/A	N/A	N/A
	Fireman's Grounding Switch	N/A	N/A	N/A
	> Lift Signage		Provided(30 KVA)	MR
7	Standby power supply	Required		
8	Refuge Area.	N/A	N/A	N/A
> Total Area		· N/A	N/A	
	> Location	N/A	1002	
19	 Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup 	N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
20	Building Floor Plans Special Fire Protection Systems for Protection of special Risks, if any:	Required	02 ABC type fire extinguisher cap. 5 Kg found provided near elect. panel	IVIIX

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2012/150 dated 17.01.2012, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

201412

18/2/15

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation: - Asstt. Div. Officer (M.Rd)