GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE

NEW DELHI- 110 001

No. F6/DFS) MS/CNG/2015/52/405

Dated: 20/03/15

FIRE SAFETY CERTIFICATE

Issued on....2015 at New Delhi by

(Dr.G.C.Misra)

Chief Fire Officer

T.No.011-23414333

Copy to:-

Sh. Alok Sharma, General Manager (Fire & Safety)

IGL Bhawan, Plot No.4, Community Centre,

R.K.Puram, Sectror-9, New Delhi-110022.

Conditions for the validity of fire safety certificate are overleaf:-

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- The employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All fire fighting equipments shall be maintained in perfect working condition all time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate in form J, six month prior to its expiry.

1.	Name & address of the	SPECTION REPO	ORT				
1	: M/S	Indraprastha Gas I	imited Day 11 O				
2.	Building is comprised of at S	ouri New Doll:	t (CNG Pump)				
3. Type of Occupancy Storage Occupancy (C.N.C. P							
5. I	Details of Previous NOC : No F	ewal	and ones Disp	bensing units.			
0. 1	HIPO COL-1 1.	5/(3A)/DFS/CNG/20 5/DFS/3A/2000/RD	006/220, Dated 11	05 2006			
/. L	Pate Of Inspection		/103, dated 23.03.2	2000.			
8. N	Name of the Inspecting Officers	al (ADO)					
J. 1	value and designation of Officer	ar (ADO)					
1		ushpendra Sharma (T' 0.60				
11 4	Year of Construction : Sh. F		Fire Officer)				
S.No	Applicant's letter No : 2000 Minimum Standards on 1	F&S/2014-15/15/60.	dated 00 12 14				
0.140	Minimum Standards on f	ire Requiremen	t Provide t	A 1 8 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			
	prevention and fire safety as per old	/	- Indud	at Remarks			
	NOC.		Site	MR/NMR			
1	Access to building		Connection to the second				
	Road width	0.55					
	Gate width	9 m	12 m	MR			
	Width of internal road	N.A.	N.A.	N.A.			
	Number, Width Type and A	N.A.	N.A.	N.A.			
	Number, Width, Type and Arrangem a. Number of Staircases	ent of Exits.	William Parket	IV.A.			
	Upper Floor						
	Basement	01no.	01no.	MD			
		N.A.	N.A.	MR			
	B. Width of Staircases Upper Floor		IV.A.	N.A.			
	Basement	70cm	07-				
		N.A.	67cm	MR			
	c. Protection of exits	N.A.	N.A.	N.A.			
	Fire check door	N.A.	N.A.	N.A.			
	Pressurization	the second secon	N.A.	N.A.			
	e. No. of continuous staircases to		N.A.	N.A.			
	terrace	N.A.	N.A.	N.A.			
	g. Width of Corridor						
	h. Door Size	N.A.	N.A.	N.A.			
(Compartmentation	1 m	1m	MR			
F	Fire check door			IVIII			
	Sealing of closes:	N.A.	N.A.	NI A			
. F	Sealing of electrical shafts	N.A.	N.A.	N.A.			
	Fire rating of shaft door	N.A.	N.A.	N.A.			
	Vater curtain	N.A.		N.A.			
	ire Dampers		N.A.	N.A.			
S	Smoke Management System.	N.A.	N.A.	N.A.			
В	asement	,					
	pper floor	30a/c per hour	N.A.	N.A.			
10	PP-1 11001	12 a c per hour	N.A.				
		//		N.A.			

Indraprastha Gas Limited Retail Outlet (CNG Pump) at San Martin, Chankyapuri, New Delhi.

	Fire Extinguisher							
	Total numbers		20 nos.		75kg=03nos,10kg	g=15nos.	MR	
	Types		CO ₂ & ,DCP)	4.5kg=4nos.Tota		140	
	IS marking		ISI marked		ISI marked		MR	
6	First-aid-Hose Reels.		_ remained		10) marked		MR	
	Total numbers of each floor		N.A.	A STANDARD	N.A.			
	Length of hose reel hose		N.A.			N.A.		
7	Nozzle diameter		N.A. N.A. N.A. N.A. ng system in compressor and in filling			N.A.		
					N.A.			
	Type of detectors	Gac	Reference in State of the Reference of t	mpress				
					Gas & Flame in		MF	
			compressor & portable Compressor &				9	
	Location of main panel		as detector with staff gas detector with					
	Location of repeater panel				N.A.		N.A	
	Alternate source of power	N.A.			N.A.		N.A	
	Hooters	N.A.			N.A.		N.A	
		Techr	ician room		Technician room	1	MR	
	MOEFA	N.A.			N.A.		N.A	
	Public address System.	N.A.			N.A.		N.A	
0	Automatic Sprinkler System.				A Company of the Comp		IV.A	
	Basement upper floor sprinkler above false ceiling		N.A.	I	J.A.	. N.A.		
			N.A.		I.A.	N.A.		
			N.A.	A vertical series	I.A.	application of the same of the		
1	Internal Hydrants				<u>.</u>	N.A.		
	size of riser/down-comer		N.A.	N	LA.			
	Number of hydrants per floor				the state of the s	N.A.		
	Hose Box		N.A.		.A.	, N.A.		
2	Yard Hydrants.		14.74.	IN	.A.	N.A.		
	Total number of hydrants		N.A.	l NI	_			
	Hose Box		N.A.	the state of the state of	.A.	N.A.		
	Pumping Arrangements.		IV.A.	N.	Α.	N.A.		
	> Ground Level		NI A		Chairman vinas			
	Discharge of main Pur	nn	N.A.		Α.	N.A.	N.A.	
	Head of Main Pump	lib	N.A.		Α.	N.A.	•	
	Number of main pump	9	N.A.	N.		N.A.		
	> Jockey pump out put	-	N.A.	N.		N.A.		
	 Jockey pump head Standby pump out put 		N.A.	N,		N.A.		
			N.A.	N.		N.A.		
	Standby pump Head		N.A.	N.		N.A.	()	
	 Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump 		N.A.	N.		N.A.		
			N.A.	N.		N.A.		
			N.A.	N./		N.A.		
			N.A.	N.A		N.A.		
			N.A.	N.A.		N.A.		
	Head of the Pump		V.A.	N.A		N.A.		
1000	Power supply		V.A.	N.A		N.A.		
	> Auto Starting of pump		V.A.					

Indraprastha Gas Limited Retail Outlet (CNG Pump) at San Martin, Chankyapuri, New Delhi.

_						
14	Captive Water Storage for Fire Fighti	na	to a series and series	ely Si		
	Underground tank capacity	N. A				
	Draw-off connection Fire service inlet		N.A. N.A. N.A.		N.A.	
		N.A.			N.A.	
	Access to tank	N.A.			N.A.	
	Overhead Tank capacity	N.A.	N.A.		N.A.	
15	No Smoking Signage.(Hindi & Enlish)	N.A.	IV.A.		N.A.	
	and an analysis of the second) Required	Dunit Line		MR	
16	Provision of Lifts.	* 25 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	And English		10 K	
	Pressurization of Lift Shaft					
	Pressurization of Lift lobby Communication in lift car Firemen's grounding switch	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
	Lift Signage	N.A.	N.A.	N.A.		
A 1 - II - I	Standby power supply	N.A.	N.A. N.A.			
		N.A.	Provided DG			
18	Refuge Area.		Set 50KVA	14.74.		
	Total area					
1	Location	N.A.	N.A.	N.A.		
19	A Continued a Residue of the continue of the c	N.A.	N.A.	N.A.		
	The Solitor Hoom					
	Detector system panel Flow switch panel PA system panel	N.A.	N.A.		N.A.	
		N.A.	N.A.		N.A.	
	Batter backup	N.A.	N.A.		1000	
	Building Floor Plans	N.A.	N.A.		N.A.	
		N.A.	N.A.		N.A.	
0	Special Fire Protection systems for	N.A.			N.A.	
F	protection of special Risks, if any:	_	9	system	N.A.	
	enkling start v		connected through detectors provided in each compressor.			

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules, the NOC issued vide letter No: F5/(3A)/DFS/CNG/2006/220, dated 11.05.2006, renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

(South)

Signature of the Inspecting Officer 29/1/15

Name: Vedpal Designation: