GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE **NEW DELHI- 110 001**

No. F6/DFS/OS/CAG/2015/52/354.
FIRE SAFETY CERTIFICATE

Dated: /3/03/15

Certified that M/S Indraprastha Gas Limited Retail Outlet (CNG Pump) at Mehrouli-Mahipalpur Road, Mahipalpur, New Delhi-110037, comprised of ground floor only, was granted NOC by this department vide letter No. F5/(3A)/DFS/CNG/2004/315, dated 21-06-2004. The premises was re-inspected by the officer concerned of this department on 08-01-2015 in the presence of Sh. Pushpendra Sharma (Fire Officer) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules 2010 and that the premises is fit for occupancy class Storage (C.N.G. Pump),04 Cascades (1no. at ground floor & 3nos. at roof of the office building), 04 Compressor Units and 8 Dispensing units with effect from 1.3/2,2,5/.....2015 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on. 13./....... 2015 at New Delhi by

(Dr.G.C.Misra) **Chief Fire Officer** T.No.011-23414333

Copy to:-

Sh. Alok Sharma, General Manager (Fire & Safety)

IGL Bhawan, Plot No.4, Community Centre,

R.K.Puram, Sectror-9, New Delhi-110022.

Conditions for the validity of fire safety certificate are overleaf:-

M 6.

1. Name & address of the building	INS	PECTION F	REPOR	Г			
	· TAT/ D	(Iranracth - C	The second second second				
2. Building is comprised of	at Mel	rouli-Mahina	lpur Ra	ed Ketail Outl	et (C.	NG Pump) w Delhi-110037.	
3. Type of Occupancy							
4 Type CG	& 3nos	at roof of the	e office	building) 04	scade	s (1no at ground fluctures or Living)	
4. Type of Case			its.	- anding), 04 (Comp	s (1no at ground floressors Units and	
5. Details of Previous NOC	: Renewa	1					
o. The Salety direction late	· No Es	PA)/DFS/CNO	G/2004/3	315, Dated 21	06.2	20.4	
	: 08 01 15	OA)/DFS/CN	G/2000/	315, Dated 21 133, dated 29.	02.20	JU4.	
8. Name of the Inspecting Officers: 9. Name and designation	: Vedpal (A	400)		,	03.20	JUU.	
from the building sit	- spar (/	(الاست					
10. Year of Construction	: Sh. Push	pendra Cha	. (5:				
L11. Applicant's letton NI	: 2000.	pendra Sharn	na (Fire	Officer)			
S.No Minimum Standards	: IGL/F&S	S/2014-15/15/	166				
Orevention and f	n fire	Requirem	oo, date	d 09.12.14			
prevention and fire safety as p	er old	. roquirell	ent	Provided	a	Remarks	
The state of the s				Site		MR/NMR	
Access to building		- Cal		A STATE OF THE STA		MINIM	
Road width							
Gate width	-	9 m		12 m	17	145	
Width of internal road	-	N.A.	na gen de l	N.A.		MR	
Number, Width Type and A		N.A.		N.A.		N.A.	
Number, Width, Type and Arra a. Number of Staircases	ngement	of Exits.		14.A.		N.A.	
Upper Floor		and the second					
Basement	C	Ino.					
B Width of Ct-		I.A.		01no.		MR	
B. Width of Staircases				N.A.		N.A.	
Upper Floor Basement	7	Ocm					
			7	70cm		MD	
c. Protection of exits		.A.	N.A.			MR	
Fire check door	N.					V.A.	
Pressurization	N.			N.A.		V.A.	
e. No. of continuous staircase	N.	Α.		.A.		V.A.	
	s to N.	٩.		.A.		I.A.	
g. Width of Corridor			IV	.А.	N	.A.	
h. Door Size	N.A						
	1 m		N.		N	.A.	
Compartmentation			1n	1	M		
Fire check door	NIA		0.5 40				
Sealing of electrical shafts		N.A.		N.A.		N.A.	
Fire rating of shaft door	N.A		N.A	N.A.			
vvaler curtain		N.A.		NA		N.A.	
Fire Dampers	N.A.				N.A	4.	
	N.A.		N.A		N.A	١.	
Smoke Management System.	IV.A.		N.A		N.A		
basement	00				1		
Upper floor	30a/d	per hour per hour	N.A.		N.A		
					IVA		

NS.

5. Fire Extinguisher									
	Total numbers		20 nos.		75kg=12nos,10kg=2 4.5kg=5nos.Total=42		MR		
	Types		CO ₂ & ,DCP	(CO ₂ & DCP Type		MI	/IR	
Ola B	IS marking		ISI marked	ISI marked			MR		
6	First-aid-Hose Reels.								
Total numbers of each floor Length of hose reel hose Nozzle diameter			N.A.		N.A.		N.A.		
			N.A.	A. N.A.		N.A.			
			N.A.	1	N.A.		N.A.		
7	Automatic fire detection and	alarming	system in comp	ress	or and in filling area	.			
	Type of detectors	Gas & Compr	Gas & Flame in Compressor & portable gas detector with staff		gas detector with s		ble	MR	
Location of main panel Location of repeater panel Alternate source of power		N.A.			N.A.			N.A.	
		N.A.		Laci I	N.A.			N.A.	
		N.A.			N.A.			N.A.	
Hooters	Techni	cian room	eri)	Technician room			MR		
8	MOEFA	N.A.			N.A.			N.A.	
9	Public address System.	N.A.			N.A.			N.A.	
10	Automatic Sprinkler System		- \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\					24-3-6	
	Basement		N.A.		N.A.		N.A.		
upper floor sprinkler above false ceiling			N.A.	N.A.		N.A.			
			N.A.		N.A.		N.A.		
11	Internal Hydrants		147	1 41					
11	size of riser/down-comer		N.A.		V.A.	N.A.		111	
	Number of hydrants per floor		N.A.				N.A.		
Hose Box			N.A.	***	N.A.		N.A.		
12	Yard Hydrants.		140						
12	Total number of hydrants Hose Box		N.A.		N.A.		N.A.		
			N.A.	-	N.A.		N.A.		
13	Pumping Arrangements.		IND.					I age of the control	
13	> Ground Level		N.A.		V.A.	N.A.			
 Discharge of main Pum Head of Main Pump 		lumn	N.A.		V.A.	N.A.			
		V 0	N.A.		V.A.	N.A.			
	 Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump Head Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump 		N.A.		N.A.	N.A.			
			N.A.		N.A.		N.A.		
			N.A.		N.A.		N.A.		
			N.A.	1	N.A.	N.A.		25	
			N.A.		N.A.	N.A	N.A.		
			N.A.		N.A.	N.A.			
			N.A.		N.A.	N.A.			
			N.A.		N.A.	N.A.			
			N.A.		N.A.	N.A.			
			N.A.		N.A.	N.A.			
			N.A.		N.A.	N.A.			
			N.A.		N.A.	N.A.			

Indraprastha Gas Limited Retail Outlet (CNG Pump) at Mahipalpur, New Delhi-22.

14	Captive Water Storage for Fire Fighting	g.				
	Underground tank capacity	N.A.	N.A.		N.A.	
	Draw-off connection	N.A.	N.A. N.		Α.	
	Fire service inlet	N.A.	N.A. N.			
	Access to tank Overhead Tank capacity	N.A.	N.A. N.		Α.	
		N.A.	N.A. N.A		Α.	
15	No Smoking Signage.(Hindi & Enlish)	Required	Provided in Hind And English	di MF	3	
16	Provision of Lifts.		New TS. No. of			
Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car Firemen's grounding switch	Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.	-	
	Firemen's grounding switch	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
17	Standby power supply	N.A.	Provided DG Set 50KVA	N.A.		
18	Refuge Area.					
	Total area	N.A.	N.A.	N.A.		
	Location	N.A.	N.A.	N.A.		
19	Fire Control Room	The state of the s	mational e		× *	
	Detector system panel	N.A.	N.A.		N.A.	
Flow switch panel		N.A.	N.A.		N.A.	
PA system panel Batter backup Building Floor Plans	N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.		
	Building Floor Plans	N.A.	N.A.			
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	Co ₂ flooding system connected through detectors provided in each compressor.			

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules, the NOC issued vide letter No: F5/(3A)/DFS/CNG/2004/315, dated 21.06.2004, renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

Signature of the Inspecting Officer Name: Vedpal

Designation: ADO

D.O. Bouth)