

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/Indl/2015/ 92/373

Dated: 17/03/15

## FIRE SAFETY CERTIFICATE

Certified that the **M/s Lord's Homoeopathic Laboratory Pvt. Ltd.** located at C-106/5, Naraina Industrial Area, Phase-I, New Delhi-110028 is comprised of Basement, Ground Floor, mezzanine floor & first floor was issued NOC by this department vide letter No.F.5/(5)/DFS/2010/109 dated 27.04.2010 owned/ occupied by the management of Lord's Homoeopathic Laboratory Pvt. Ltd. The Industrial building was re- inspected by the officers concerned of this department on 05.03.2015 in the presence of Sh. Rajesh Sharma and found that the management have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class Group G industrial building w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Phy 011-23414333

Copy to:-

- Sh. S.M. Sharma (Mg. Director)
   M/s Lord's Homoeopathic Laboratory Pvt. Ltd,
   C-106/5, Naraina Industrial Area, Phase-I, N.D-28.
- 2. The District Excise Officer (M & TP)
  Office of the Commissioner of Excise,
  L & N Block, Vikas Bhawan, New Delhi.

## Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.



	CONTROL OF THE PROPERTY OF THE						
	INSPECT	ION REPORT					
	1. Name & address of the building: Mls Lord's Homosphattic Later of the building:						
		Occupancy : Group G [Industrial Bldg.) Naraina Tid. Area P					
	i the or case	New Case/Repe	wal	laraina Ind. Area New Delli-1100			
	4. Details of Previous NOC	Letter No. FS	LI) INFSIMING	Date 97.04.			
	an ectives letter NO :	Letter No. FS (5)   DFS   10   109   Date 27.04.2					
	6. Date of inspection						
	name of inspecting Officer : N.O. C. K. Toward & O. A. A. L.						
	()						
	From the building side :	Sh. Rajest	Sharma				
	9. Year of Construction :	1999-200	0	Processing of sylvation and transfer the Commission of the Commiss			
	10. Applicant's letter No.	4 4 4	06.02.2015	and many total to be a series of the series			
S.	Minimum Standards on fire	NBC/BBL	Provided at	Remarks			
No.	prevention and fire safety U/R 33	Requirement	site	MR/NMR			
1.	Access to building		Jice	INITY INITY			
	<ul> <li>Road width</li> </ul>	Accessible	12 mtr	MR			
	Gate width		270 cms				
	<ul> <li>Width of internal road</li> </ul>		2 TO CMS	MR			
	Number, Width, Type & Arrangement of	fr					
and a region of Management	a. Number of staircases	JI EXITS					
	• Upper Floors						
	Basements	Two	Two	MR			
	b. Width of staircases	-do-	-do-	MR			
	• Upper Floor			v .*			
			120 cms, 112 cms	MR, Old Cas			
	• Basements		155cms, 85cms	-do -			
	c. Protection of exits			1			
	Fire check door	7		The second secon			
	• pressurization		Commence of the Control of the Contr				
	d. No. of continuous staircases to	The second secon	A STATE OF THE OWNERS OF THE PROPERTY OF THE OWNERS OF THE				
	terrace		Ohe	And the same of th			
	e. Width of Corridor						
	f. Door Size		180 cms, 210 cms	The state of the s			
		-	140 cms x 204 cms	-			
3.	Compartmentation	p 1					
	Fire check door						
	<ul> <li>Sealing of electrical shafts</li> <li>Fire Rating of shaft door</li> <li>Water Curtain</li> </ul>		2				
		-	Sealed	N 11			
				_			
	• Fire Dampers			<b>Same</b> .			
	Constitution of the Consti		-	W. See S. A. See S. See			
4.	Smoke Management System						
	* Basements	30 a/c per	Exhaust Fans				
	<ul> <li>Upper floors</li> </ul>	hour	are Provided	MR			
	A CONTRACTOR OF THE PARTY OF TH		-do-	MR			



	N8.	The design of the second of th	er <sub>a</sub> :	•
	18 o.j. o.g. (	12 a/c per hour	1.7.1	
5.	Fire Extinguishers	7 0 0 0		4
and the second s	<ul><li>Total numbers</li></ul>	Six at each Floor	Provided	MR
	<ul><li>Types</li></ul>	Coz, ABC, Foam	- da -	MR
	<ul><li>IS marking</li></ul>	ISI marked	151 Marked	MR
6.	First-Aid Hose Reels	:	12/1/WIKEA	7.71
	<ul> <li>Total numbers on each floor</li> </ul>	One	Provided	MR
	<ul><li>Length of hose reel hose</li></ul>	30 m	-do-	MR
	Nozzle diameter	5 mm	-do 2	MR
7.	Automatic fire detection and alarming	system	1	
	<ul> <li>Type of detectors</li> </ul>			
1	<ul><li>Location of Main Panel</li></ul>			
	<ul> <li>Location of Repeater Panel</li> </ul>			
	<ul> <li>Alternate source of power</li> </ul>		D. G. Set of 62 SKV	a Mo
	<ul> <li>Hooters' Location</li> </ul>		7 500 5 KV	
8.	MOEFA	Required	Proxided	MR
9.	Public Address System	- do - 1	- do -	MR
10.	Automätic Sprinkler System			
	• Basement	Required.	Provided	MR
	<ul> <li>Upper Floor</li> </ul>	L		
	<ul> <li>Sprinkler above false ceiling</li> </ul>		1	
11.	Internal Hydrants	a		
	<ul> <li>Size of riser/down-comer</li> </ul>	100 M.M	100 M.M.	MR
	<ul> <li>Number of hydrants per floor</li> </ul>	One	One	MR
	Hose Box	~ do -	-do-	MR
12.	Yard Hydrants		J.	
	<ul> <li>Total number of hydrants</li> </ul>			
13	* Hose Box	74		1
13.	Pumping Arrangements		1	# 1.
	Ground Level			
	Discharge of main Pump		<b></b>	1
	<ul><li>Head of Main pump</li><li>Number of main pumps</li></ul>			
	<ul><li>Number of main pumps</li><li>Jockey Pump out put</li></ul>	-		
	> Jockey pump head	5		
	<ul><li>Standby Pump out put</li></ul>	-		
	Standby Pump Head			
	Auto Starting/Manual			
	stopping	Nethodox -		
-		•		

N/9. C-106/S, Noraina Industrial Area, Phase-I, New Delli - 110028.

<b>}</b>	Phase-I, New Bein	T		
	> Pump House Access			
	Terrace level     Discharge of number			
	Discharge of pump	- Canada	456 LPM, 180 LPM	MR, Old
	> Head of the pump		30M Each Provided	MR
	Power Supply	Required	Provided	MR .
	> Auto Starting of pump			
L4.	Captive Water Storage for fire fighting			I
0	Underground tank capacity			
	Draw-off connection			
	Fire service inlet		Provided	MR
	Access to tank		10010101	
	Overhead Tank capacity	10000 Ur	10000 Cer	MR
l5.	Exit Signage.	10000 Ur Required	Provided	MR
16.	Provision of Lifts.	,		
LO.	Pressurization of Lift Shaft			<del></del>
	<ul> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> </ul>			
		Special Control of the Control of th	Provided	MR
	• * Fireman's Grounding Switch	- :		Old Cift
	Lift Signage			
L7.	Standby power supply	Required	Provided	MR
L8.	Refuge Area.		a a	
	> Total Area			
	> Location			
19.	Fire Control Room	T	1	3
	Detector System Panel		-	
	Flow Switch Panel		-	<b>******</b>
	PA System Panel	-	-	•
	Batter backup		-	
	Building Floor Plans			. L
20.	Special Fire Protection System for Protection of special Risks, if any:			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F5 (LS) DFS 10 109 dated 27.04.20/0 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name S.K. Tomar

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation ASSH. Divisional Officer