GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/ans/school/2015/NO2/374

Dated: 17/03/15

FIRE SAFETY CERTIFICATE

Certified that the Modern K.D. Field Public School, running at ground plus one upper floor of the building which is comprising of ground plus two upper floors at 1619-C, Panchsheel Garden, Naveen Shahdara, Delhi-32 was granted NOC by this department vide Letter No-F.6/DFS/MS/07/3719 dated 14.12.2007 (for ground plus one upper floor). School building was re-inspected by the officer concerned of this department on 22.12.2014 in the presence of Principal of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with the circular No. 262-362 dated 17.01.2005 issued by the Director of Education and found that the building is fit for occupancy Group B "Educational Building" for ground plus one upper floor with effect from .1.7.(.0.3./1.5.... renewed for a period of three years, subject to conditions printed overleaf.

Issued on 17/03/1.5 at New Delhi by

(Dr. G.C. Misra)

Chief Fire Officer

Ph -011- 23414333

To,

The Principal

Modern K.D. Field Public School,

1619-C, Panchsheel Garden, Naveen Shahdara, Delhi-32

Copy to:-.

The Director of Education,

East Delhi Municipal Corporation,

419, Udyog Sadan, Patparganj Industrial Area, Delhi-92

CONDITIONS:

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1 N	ame & address of the building : Modern I		S-L 1 4640 0 D				
1. 14	_		School, 1619-C, Pa	anchsheel			
2 D.		Naveen Shahdar		N. 1000			
1	uilding is comprised of : G+2 (Scho		round plus one up	per floor)			
	/pe of Occupancy : Education	nal					
	rpe of Case : Renewal						
5. De			ted 14.12.2007 (fo	or ground plus			
6 Ei	one upper floor)						
U. FII	re Safety direction letter No : Old requ						
7 Da		lo. 262-362 date	d 17.01.2005)				
1	ate of Inspection : 22.12.20						
1	ame of the Inspecting Officers: : Suresh Sing	gn (ADO)					
	ame of the designation of Officer						
	om the building side : Principal ear of Construction : 2005						
	a section of the sect						
	pplicant's letter No : Dated 11			201			
S.No	Minimum Standards on fire safety	C of the second second concentrations	Provided at	Remarks			
	requirements as per circular no. 262-362		Site	MR/NMR			
1	dated 17.01.2005	"					
1	Access to building						
	Road width	6 m	6 m	MR			
	Gate width	N.A.	N.A.	N.A.			
	Width of internal road	N.A.	N.A.	N.A.			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	Upper Floor	2 no.	2 no.	MR			
	Basement	N.A	N.A.	N.A.			
	B. Width of Staircases						
	Upper Floor	1.5 m	1.15m, & 1 m	MR			
	Basement	N.A	N.A.	N.A.			
	c. Protection of exits	N.A	N.A.	N.A.			
	Fire check door	N.A.	N.A.	N.A.			
	Pressurization	N.A.	N.A.	N.A.			
	e. No. of continuous staircases to terrace	2 no.	2 no.	MR			
	g. Width of Corridor	1.5 m	1.5 m	MR			
	h. Door Size	1 m	1 m	MR			
3	Compartmentation			.,,,,			
	Fire check door	N.A.	N.A.	N.A.			
	Sealing of electrical shafts	N.A.	N.A.	N.A.			
	Fire rating of shaft door	N.A.	N.A.	N.A.			
	Water curtain	N.A.	N.A.				
	Fire Dampers			N.A.			
4	Smoke Management System.	N.A.	N.A.	N.A.			
-	Basement	DI A					
	Upper floor	N.A.	N.A.	N.A.			
	Opper 11001	N.A.	N.A.	N.A.			

5.	Fire Extinguisher						
	Total numbers	04 no.	4 no.	MR			
	types	CO ₂ & ABC	CO ₂ & ABC	MR			
	IS marking	ISI marked	ISI marked	MR			
6	First-aid-Hose Reels.						
	Total numbers of each floor	01 no.	01 no.	MR			
	Length of hose reel hose	30 m	30 m	MR			
	Nozzle diameter	5 mm	5 mm	MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	N.A.	N.A.	N.A.			
	Location of main panel	N.A.	N.A.	N.A.			
	Location of repeater panel	N.A.	N.A.	N.A.			
	Alternate source of power	N.A.	N.A.	N.A.			
	Hooters's location	N.A.	N.A.	N.A.			
8	MOEFA	N.A.	Provided	MR			
9	Public address System.	N.A.	Provided	MR			
10	Automatic Sprinkler System.						
	basement	N.A.	N.A.	N.A.			
	upper floor	N.A.	N.A.	N.A.			
	sprinkler above false ceiling	N.A.	N.A.	N.A.			
11	Internal Hydrants						
9	size of riser/down-comer	N.A.	N.A.	N.A.			
	Number of hydrants per floor	N.A.	N.A.	N.A.			
	Hose Box	N.A.	N.A.	N.A.			
12	Yard Hydrants.						
	Total number of hydrants	N.A.	N.A.	N.A.			
	Hose Box	N.A.	N.A.	N.A.			
13	Pumping Arrangements.						
	Ground Level	N.A.	N.A.	N.A.			
	Discharge of main Pump	N.A.	N.A.	N.A.			
	Head of Main Pump	N.A.	N.A.	N.A.			
	Number of main pumps	N.A.	N.A.	N.A.			
	Jockey pump out put	N.A.	N.A.	N.A.			
	Jockey pump head	N.A.	N.A.	N.A.			
	Standby pump out put	N.A.	N.A.	N.A.			
	Standby pump Head	N.A.	N.A.	N.A.			
	Auto Starting / Manual stopping	N.A.	N.A.	N.A.			
	Pump House Access	N.A.	N.A.	N.A.			
	Terrace Level			,			
	Discharge of pump	220 LPM	220 LPM	MR			
	Head of the Pump	40 m	40 m	MR			
	Power supplyAuto Starting of pump	Required	Provided	MR			
	Auto Starting of pump	1					

14	Captive Water Storage for Fire Fight	ing				
	Underground tank capacity	N.A.				
	Draw-off connection		N.A.	N.A		
	Fire service inlet	N.A.	N.A.	N.A		
	Access to tank	N.A.	N.A.	N.A.		
	Overhead Tank capacity	N.A.	N.A.	N.A.		
15	Exit Signage.	2500 Liters	2500 Liters	MR		
16	Provision of Lifts.	N.A.	N.A.	N.A.		
	Pressurization of Lift Shaft					
	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
	Communication in lift car	N.A.	N.A.	N.A.		
	Firemen's grounding switch	N.A.	N.A.	N.A.		
	Lift Signage	N.A.	N.A.	N.A.		
17	*	N.A.	N.A.	N.A.		
18	Standby power supply	N.A.	N.A.	N.A.		
10	Retuge Area.					
	Total area	N.A.	N.A.	N.A.		
	Location	N.A.	N.A.			
19	Fire Control Room		IV.A.	N.A.		
	Detector system panel	N.A.	N.A.	1		
	Flow switch panel	N.A.		N.A.		
	PA system panel		N.A.	N.A.		
	Batter backup	N.A.	N.A.	N.A.		
	Building Floor Plans	N.A.	N.A.	N.A.		
0	Special Fire Protection systems for	N.A.	N.A.	N.A.		
	protection of special Risks, if any:	N.A.	N.A.	N.A.		
	protection of special Risks, if any:			Ν.Λ.		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules the NOC issued vide letter no. F.6/DFS/MS/07/3719 dated 14.12.2007 (for ground plus one upper floor), renewal under the circular No. 262-362 dated 17.01.2005 is recommended to grant Fire Safety

Signature of the Inspecting Officer

Name

Suresh Singh

Designation

ADO (Shah)

Dy CFO (NDZ)

Submitted for approval please.

Ning
610