GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/MS/2015/ND2/403

Dated: 20/03/15

FIRE SAFETY CERTIFICATE

Issued on.....at New Delhi by

(Dr. G.C. Misra) Chief Fire Officer Ph -011- 23414333

Copy to-

- The Deputy Health Officer,
 East Delhi Municipal Corporation,
 Health Department, Shahdara (South) Zone
 Karkardooma, Shahdara, Delhi-32.
- The Gen. Secretary,
 Royal Community Hall,
 Minocha Yogic Shiksha & Sanskriti Nyas,
 Mandawali Fazalpur, opp. Bathla CGHS, Patparganj, IP Extension, Delhi

CONDITIONS:

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1 N			REPORT				
1. 1	Name & address of the building : Royal Community Hall (Minocha Yogic Shiksha &						
	Sanskriti Nyas) at Mandawali Fazalpur, opp. Bath						
2. B	CGHS, Patparganj, IP Extension, Delhi Building is comprised of : B+G+1						
		+G+1					
			ably (Banquet Hall)				
F. Dotoile of Day : 1000							
	0.6		45 /DD /00 /E7E				
	Entry Safety direction letter No : F6/DFS/MS/BP/98/575 dated 20.03.1998 : 08.03.2015						
			igh (ADO)				
	ame of the designation of Officer	C311 3111	igii (ADO)				
	ome Alex In 1991	cretary	/				
	ear of Construction : 199		,				
11. A	pplicant's letter No : Nil						
S.No	Minimum Standards on fire preve	ention	Requirement	Provided a	nt Remarks		
	and fire safety U/R33		/NBC	Site	nt Remarks MR/NMI		
1	Access to building		75	Site	IVIR/IVIVI		
	Road width	24 m	NAD				
	Gate width		6 m	5 m	MR		
	Width of internal road		N.A.	N.A.	MR		
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	Upper Floor		2 no.	02 no.	MR		
	Basement		2 no.	02 no.	MR		
	b. Width of Staircases			02 110.	IVIII		
	Upper Floor		1.5 m	1.5 m each	MR		
	Basement	ŀ	1.5 m	1.5 m each	MR		
	c. Protection of exits			1.5 III CUCII	IVIIV		
	Fire check door Pressurization e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size		Required	Provided	MR		
			N.A.	N.A.	N.A.		
				14.74.	IV.A.		
- 1			N.A.	N.A.	N.A.		
i			2 m	2m,1.5m,1.5m	MR		
	i. No. of door		2 no.	3 no.	MR		
	Compartmentation.						
	Fire check door		Required	Provided	MR		
	Sealing of electrical shafts		Required	Provided	MR		
	Fire rating of shaft door		Required	Provided	MR		
	Water curtain		N.A.	N.A.	N.A.		
	Fire Dampers		N.A.	N.A.	N.A.		
!	Smoke Management System.			11.7.	IV.A.		
	Basement						
	Dasement	1	Ventilated	Ventilated	MR		

5.	Fire Extinguisher						
	Total numbers	06 no.	06 no.	MR			
	types	CO ₂ & ABC	CO ₂ & ABC	MR			
	IS marking	ISI marked	ISI marked	MR			
6	First-aid-Hose Reels.						
	Total numbers of each floor	1 no.	1 no.	MR			
	Length of hose reel hose	30 m	30 m	MR			
	Nozzle diameter	5 mm	5 mm	MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	N.A.	N.A.	N.A.			
	Location of main panel	N.A.	N.A.	N.A.			
	Location of repeater panel	N.A.	N.A.	N.A.			
	Alternate source of power	N.A.	N.A.	N.A.			
	Hooters's location	N.A.	N.A.	N.A.			
8	MOEFA	N.A.	N.A.	N.A.			
9	Public address System.	N.A.	N.A.				
10	Automatic Sprinkler System. N.A. N.A. N.A. N.A.						
	basement	Required	Provided	MR			
	upper floor	N.A.	N.A.	N.A.			
	sprinkler above false ceiling	N.A.	N.A.	N.A.			
11	Internal Hydrants	1.17,11	14.7.	IV.A.			
	size of riser/down-comer	N.A.	N.A.	N.A.			
	Total no. of hydrants each floor	N.A.	N.A.	N.A.			
	Hose Box per floor	N.A.	N.A.	N.A.			
2	Yard Hydrants.						
	Total number of hydrants	N.A.	N.A.	N.A.			
	Hose Box	N.A.	N.A.	N.A.			
.3	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	N.A.	N.A.	N.A.			
•	Head of Main Pump	N.A.	N.A.	N.A.			
	Number of main pumps	N.A.	N.A.	N.A.			
	Jockey pump out put	N.A.	N.A.	N.A.			
	Jockey pump head	N.A.	N.A.	N.A.			
	Standby pump out put	N.A.	N.A.	N.A.			
	Standby pump Head	N.A.	N.A.	N.A.			
	Auto Starting / Manual stopping	N.A.	N.A.	N.A.			
	Pump House Access	N.A.	N.A.	N.A.			
	Terrace Level		_				
	Discharge of pump	900 LPM	900 LPM	MR			
	Head of the Pump	40 m	40 m	MR			
	Power supply	Required	Provided	MR			
	Auto Starting of pump	Required					

14	Captive Water Storage for Fire Fighting.				
	Underground tank capacity	10,000 Liters	Provided	MR	
	Draw-off connection	N.A.	N.A.	N.A.	
	Fire service inlet	N.A.	N.A.	N.A.	
	Access to tank	N.A.	N.A.	N.A.	
	Overhead Tank capacity	12,500 Liters	Provided	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.	
	Pressurization of Lift lobby	N.A.	N.A.	N.A.	
	Communication in lift car	N.A.	N.A.	N.A.	
	Firemen's grounding switch	N.A.	N.A.	N.A.	
	Lift Signage	N.A.	N.A.	N.A.	
17	Standby power supply	N.A.	N.A.	N.A.	
18	Refuge Area.				
	Total area	N.A.	N.A.	N.A.	
	Location	N.A.	N.A.	N.A.	
19	Fire Control Room				
	Detector system panel	N.A.	N.A.	N.A.	
	Flow switch panel	N.A.	N.A.	N.A.	
	PA system panel	N.A.	N.A.	N.A.	
	Batter backup	N.A.	N.A.	N.A.	
	Building Floor Plans	N.A.	N.A.	N.A.	
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

85m/h

Signature of the Inspecting Officer

Name

Suresh Singh

Designation ADO

As ber approval dated 20.3.98 bldg was proposed B+4+FF+SF. but r

Et is only 13 + GF+ FF. Idea to not build allo as to band blow.

DO (EAST)

Dy CFO (NOZ)

Dy CFO (NOZ)