GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2015/52 /4/6

Dated: 23/03/15

FIRE SAFETY CERTIFICATE

Certified that the **Hotel Harjas Palace** located at 5/43, WEA, Karol Bagh, New Delhi-110005 is comprised of Basement, Ground Floor plus two upper floors, using basement as hall/storage & Bank locker, ground floor as reception, office & Bank Branch, first & second floor each having 10 guest rooms respectively (Total 20 guest rooms) and one staff room with one store on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2012/1732 dated 14.05.2012 owned/ occupied by Sh. Jaspinder Singh. The guest house building was re- inspected by the officers concerned of this department on 18.03.2015 in the presence of Sh. Dinesh Kumar Negi (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 23 03 15 at New Delhi.

(DR. G.C. MISRA)
CHIEF FIRE OFFICER
DELHI FIRE SERVICE
Ph:- 011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.8878/Joint C.P./Lic.(H), Dated 25.02.2015)
- 2. Sh. Jaspinder Singh (Owner) Hotel Harjas Palace, 5/43, WEA, Karol Bagh, New Delhi –110005.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

M 25.								
	INSPECTIO	ON REPORT						
	1. Name & address of the building: Hotel Harras Palace, 543, WEA, Karol Bagh, No-os							
	2. Type of Occupancy : Kesidential Chuest House)							
	3. Type of Case : N	ew Case/Renew	/al	2 85				
	4. Details of Previous NOC : Le	Letter No. F. 6 DFS MS GH 2012 1732 Date 14.05.2012						
	5. Fire Safety directives letter No : _							
	6. Date of inspection : _		13.2015	1				
	7. Name of Inspecting Officer : D.O S.K. Tomar & A.D.O P.S. Dahiya							
	8. Name and designation of officers							
	From the building side : _	Sh. Dine	sh Kumar Negi	(Manager)				
	9. Year of Construction : _	DEJOYE	2001	The Burth Control of the American Control of the Co				
			.P/Lic.CH) do	ited 15:02:2015				
S.	Minimum Standards on fire	NBCBBL	Provided at	Remarks				
No.	prevention and fire safety U/R 33	Requirement	site '	MR/NMR				
1.	Access to building			il.				
	 Road width 	Accessible	06 mtr	MR				
	 Gate width 		180 cms	MR				
	Width of internal road Side Road	_	04mtr	MR				
2.	Number, Width, Type & Arrangement o	fExits						
	a. Number of staircases							
	• Upper Floors	One	One	MR				
	 Basements 	-do-	- do -	MR				
	b. Width of stairdases			- J. (K				
	Upper Floor		113 cms	MR, Old Case				
	Basements		120 cms	-do -				
	c. Protection of exits		Ido Cms	- 20 -				
	Fire check door			difference manifester (not 1 x X distributions, market 1 indistributed all newspace distributed in 1 days require				
	pressurization							
	d. No. of continuous staircases to							
	terrace		1	references become the description of colors and a first section introduction and accommodate to the colors of the				
	e. Width of Corridor		One					
	f. Door Size		142 cms, 270 cms					
		-	7.7 cms x 203 cms					
3.	Compartmentation							
	Fire check door							
	Sealing of electrical shafts							
Without Addition Addition	Fire Rating of shaft door		Sealed					
	Water Curtain		Management					
				-				
	• Fire Dampers							
4.	Smoke Management System							
	* Basements	30 a/c per	Exhaust fans	Me				
	 Upper floors 	hour	are Provided	MR				
			Natural Ventilation	n MR				



	N/24.	The state of the s		
		12 a/c per hour		
5. ,	Fire Extinguishers			
	 Total numbers 	Two at each Floor	0	
	* Types	Co, WCo,	Povided	MR
1	IS marking	ISI marked	-do,-	MR
6.	First-Aid Hose Reels		151 Marked	MR
	 Total numbers on each floor 	One	Provided	Na
	 Length of hose reel hose 	30 m	- do -	MR
	 Nozzle diameter 	5 mm	- do'-	
7.	Automatic fire detection and alarming	system	- 00.	MR
	 Type of detectors 			
	 Location of Main Panel 			
	 Location of Repeater Panel 			
	 Alternate source of power 			
	 Hooters' Location 			
8.	MOEFA	Required	Provided	MR
9.	Public Address System	- do -	-do-	MR
10.	Automätic Sprinkler System			
	 Basement 	Required	Provided	MR
	 Upper Floor 	7	Too videa	
1	 Sprinkler above false ceiling 		1	
11.	Internal Hydrants	3 2	- A pina in a single	
Mayor Maria	 Size of riser/down-comer 			
	 Number of hydrants per floor 			
	 Hose Box 			-
12.	Yard Hydrants		J.	
	 Total number of hydrants 			-
ļ	* Hose Box			
13.	Pumping Arrangements		9	
1	* Ground Level		X	a 4
	Discharge of main Pump			
	> Head of Main pump			<u>,</u>
	Number of main pumps			. •
	> Jockey Pump out put > Jockey pump head		-	
	Jockey pump headStandby Pump out put			
	Standby Pump Head		4	
	> Auto Starting/Manual		i.	
	stopping		i	
1		•	Parame.	

A POP

N/25 5/43, WEA, Kasol Bagh, New Delli - 110005.

	New Being = 110					
	Pump House Access	•		-		
	 Terrace level 					
	Discharge of pump		450 LPM	MR Old Co		
	Head of the pump	Aprilana		MR, Old Co		
	Power Supply	Required	30 M Provided	MR		
	Auto Starting of pump	/				
14.	Captive Water Storage for fire fighting			1		
	 Underground tank capacity 	- Company of the Comp		,		
	Draw-off connection		Specimen.			
	Fire service inlet		-	-		
	Access to tank		Nonemann.			
	Overhead Tank capacity		Soco Ltr	MR, old C		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.			1		
	Pressurization of Lift Shaft	-		No Lift		
	 Pressurization of Lift lobby 			-do-		
	 Communication In lift Car Fireman's Grounding Switch Lift Signage 					
			Common as.	-do-		
		•	•	-do-		
	Ent signage	_	-	-do-		
17.	Standby power supply	Required	D.G. Set of 15 KVA	MR		
				77 24		
18.	Refuge Area.		, ,			
	> Total Area			1		
	> Location					
				:		
19.	Fire Control Room					
	 Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 		-			
				1		
				1		
		American de la constante de la	Parallal	N. 0		
			Provided	MR		
	- A	*	-	****		
20.	Special Fire Protection System for Protection of special Risks, if any:			-		

10

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6 DFS MS GH 2012 1732 dated 14.05,2012 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

13/11/15 B 13/11

Signature of Inspecting Officer

Name S.K. Tomar

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation Asstt. Divisional Officer