GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2015/ 52 \ 469

Dated: 31/02/15

FIRE SAFETY CERTIFICATE

Certified that the Hotel Jyoti Deluxe located at 4/68, WEA, Saraswati Marg, Karol Bagh, New Delhi-110005 is comprised of Ground Floor plus four upper floors, using ground floor as reception, lobby, offices, two room for personal use & 02 guest rooms, first, second & third floor each having 10 guest rooms with one store room and one room for personal use respectively, fourth floor having four rooms for personal use & hall (Total 32 guest rooms) and a pantry for staff on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2012/1302 dated 12.04.2012 for 42 guest rooms owned/ occupied by Sh. Rohit Garg. The guest house building was re- inspected by the officers concerned of this department on 19.03.2015 in the presence of Sh. Rohit Garg (Owner) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential for 32 guest rooms w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on. 31/03/15 at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER Ph:- 011-23414333

Copy to:-

- The Joint Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.8876/Joint C.P./Lic.(H), Dated 25.02.2015)
- 2. Sh. Rohit Garg (Owner) Hotel Jyoti Deluxe, 4/68, WEA, Saraswati Marg, Karol Bagh, N.D - 05.

	13.131 4.0						
	1. Name & address of the building	TION REPORT	ali a lilea 1 ii				
	2. Type of Occupancy	Residential (Guest House) Karol Bagh No					
	3. Type of Case	: New Case/Rond	Surst House)	Karol Bagh, N			
	4. Details of Previous NOC	rew case/nemewal					
	5. Fire Safety directives letter No	: Letter No. F.6/DFS/MS/GH/2012/1302 Date 12.04.20					
	6. Date of inspection	19.03.2015 D.O S.K. Tomar & A.D.O P.S. Dahiya					
	8. Name and designation of officers	5 Dio Siki 10h	nar & H.D.O P	·S. Dahiya			
	From the building side		4 0 / 0	1			
	9. Year of Construction	Before 199	nit Garg Cowner	2			
	10. Applicant's letter No.	8876 Taint C	PLIC.CH) do	1.1.0.			
S.	Minimum Standards on fire	NBC/BBL	Provided at				
No.	prevention and fire safety U/R 33	Requirement		Remarks			
1.	Access to building	Requirement	site	MR/NMR			
	Road width	Accessible	12 mts	Da0			
	Gate width	7766633181		MR			
	Width of internal road	Same	177cms	MR			
2.			07 mtr	MR			
	Number, Width, Type & Arrangement a. Number of staircases	t of Exits					
	• Upper Floors			* * * * *			
	Basements	One	One	MR			
	b. Width of staircases			No Basement			
	• Upper Floor			4			
			118 cms	MR, Old Case			
	Basementsc. Protection of exits	- Constant	Name.	No Basemen			
	I I						
	Fire check door	_	***************************************	AMERICAN COMMISSION IN THE STATE OF STREET, ST			
	pressurization d. Not of continuous stairs against		Attendance				
	or continuous stair cases to			anti tida daka pina annya 1935 fisika dia anti-nila 1 dikuana bikanaman bikanahan antika maka maka dia 1			
	terrace e. Width of Corridor		One				
	f. Door Size	Section 1	210 cms				
	1. 0001 3126		95 cms x 202 cms				
3.	Compartmentation		75 cms x 196 cms	-			
		(2)		The second secon			
	Fire check door						
	 Sealing of electrical shafts 	~	00-1-1	AND			
	 Fire Rating of shaft door 		Sealed				
	Water Curtain			Species .			
	 Fire Dampers 						
4.	Smoke Management System	,					
	* Basements		<u> </u>				
		30 a/c per		No Basement			
		1 hour		140 Busement			
	Upper floors	hour	Vatural Ventilation				

	N/97	Francisco de la constanta de l		
		12 a/c per hour	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
5.	Fire Extinguishers		2 1	
	 Total numbers 	Two at each floor	01	A A
	Types	Co, WCo, ABC	Provided	MR
i	IS marking	ISI marked	- do-	MR
6.	First-Aid Hose Reels		1SI Marked	MR
and complete or co	 Total numbers on each floor 	One	Provided	D00
	 Length of hose reel hose 	30 m	-do-	MR
	 Nozzle diameter 	5 mm	-do-	MR
7.	Automatic fire detection and alarming	g system	- 40	I. MR
	 Type of detectors 			T
1	 Location of Main Panel 		<u> </u>	
	 Location of Repeater Panel 			
	 Alternate source of power 			+
	 Hooters' Location 		7 01 1	1
8.	MOEFA	Rooming	In Staircase	
9.	Public Address System	Required - do-	Previded	MR
10.	Automätic Sprinkler System	- do-	I MR	
	• Basement			NA COLUMN
1	 Upper Floor 			No Basement
	 Sprinkler above false ceiling 		1	
11.	Internal Hydrants			
	 Size of riser/down-comer 			
	 Number of hydrants per floor 			7
	• Hose Box			
12.	Yard Hydrants		J	<u> </u>
	 Total number of hydrants 		_	
	* Hose Box	i de la companya de l	-	
13.	Pumping Arrangements			
	 Ground Level 			
	Discharge of main Pump		_	
	Head of Main pump			
	Number of main pumps			
	Jockey Pump out put			: 5
	Jockey pump head		Contraction of the Contraction o	,
	> Standby Pump out put		Name of the control o	
1	> Standby Pump Head		(
	Auto Starting/Manual		1	
	stopping	The state of the s		
L	and the second s		_	



4/68, WEA, Saraswati Marg, Karol Bagh, New Delhi-110005.

	Kasol Bagh, New	DEIN - 110002	The same of the sa			
	Pump House Access					
	Terrace level			2 2		
	Discharge of pump	450 LPM	450 LPM	MR		
	Head of the pump	30 M				
:	Power Supply	Required	30 M Provided	MR MR		
	Auto Starting of pump	V				
14.	Captive Water Storage for fire fighting			1		
	 Underground tank capacity 	_	_	- E		
	Draw-off connection		-			
	Fire service inlet					
	Access to tank					
	 Overhead Tank capacity 		6000 Ltr	MR, Old Cas		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.	2		9		
	Pressurization of Lift Shaft	-	_	,—		
	Pressurization of Lift lobby					
	Communication In lift Car		Paristal	100		
	 * Fireman's Grounding Switch 		Provided	MR		
	Lift Signage			Old Cift		
		_	-	_		
17.	Standby power supply	Required	D.G. Set of 25 KVA	MR		
18.	Refuge Area.					
	> Total Area		_	n —		
	> Location					
	1			÷		
19.	Fire Control Room					
	Detector System Panel	-	-			
	 Flow Switch Panel 		-			
	PA System Panel	·				
	Batter backup		Provided	MR		
	Building Floor Plans		- roviaea	-		
20.	Special Fire Protection System for Protection of special Risks, if any:		_	_		

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. Fight 1901 1302 dated 19.04.2012 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

K10 m23 311/2

Signature of Inspecting Officer

Name S.K. Tomar

Designation Divisional Officer

Signature of Inspecting Office

Name P.S. Dahiya

Designation ASSH. Divisional Officer