GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.

F6 DF3 MS) GN 2015 ND2 429

Dated

24/3/15

FIRE SAFETY CERTIFICATE

Certified that the Surya Inn is running at second floor and third floor of a building comprising of ground plus three upper floors at 35-38, Banarsi Dass Bldg, Thandi Complex, Main, Bazar Gandhi Nagar, Delhi-31. Shops (others property) at ground floor, one hall, 05 rooms used as residence at first floor, 15 guest rooms at second floors, one hall and 12 guest rooms at third floors respectively owned/occupied by M/S Surya Inn Guest House, was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2012/1948 dated 29.05.2012. The Premises was re-inspected by the officer concerned of this department on 14.03.2015 in the presence of Mr. Ved Parkash and found that the Guest house have deemed complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rules, 2010 and found that the building SF+TF is fit for occupancy class "Residential Guest House" for 27 Rooms only, with effect from 27 Properties of the conditions under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rule 2010, subject to conditions printed overleaf.

Issued on at New Delhi by

(Dr. G.C. Misra)
Chief Fire Officer
Ph -011- 23414333

To

The Manager,

Surya Inn, 35-38, Banarsi Dass Bldg, Thandi Complex, Main, Bazar Gandhi Nagar, Delhi-31 Copy to-

The Joint Commissioner of police (Lic.),

1st Floor Police station, Defence Colony, New Delhi

Conditions

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 2. All the means of escape shall be kept free of all type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 6 This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

(ADO [S. Smh.)

1 N	-	ON REPORT					
1. 14	,		Dass Bldg, Thandi	Complex, Main			
2 Ru	The second secon	ndhi Nagar, Delh					
		olus three upper floors					
		ial (Guest 1	(Guest House.)				
4. Type of Case : Renewal							
	5. Details of Previous FSC : F.6/DFS/MS/GH/2012/1948 dated 29.05.2012						
1							
11							
	ame of the Inspecting Officers: : Suresh Signe of the designation of Officer	ngh (ADO)					
		D- I I					
		Parkash					
		+ 6 5 /1: /11)					
S.No	Minimum Standards on fire prevention		ated 24.02.2015				
3.110	and fire safety U/R33	Old	Provided at Site	Remarks			
	and the safety 0/R33	Requirement	4	MR/NMR			
1	Access to building	/BBL					
	Road width	16					
	Gate width	6 m	12 m	MR			
	Width of internal road	NA	NA	NA			
2	IVA IVA						
	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases	2					
	Upper Floor Basement	2 no. N.A.	2 no. N.A.	MR			
	B. Width of Staircases	IV.A.	IV.A.	N.A.			
	AND A STATE OF THE						
	Upper Floor Basement	0.9 m	0.90 m, 0.90 m	MR			
	Auto-Sandard Common Control Common Co	N.A.	N.A.	N.A.			
	c. Protection of exits Fire check door	NA	NA	NA			
	Pressurization	NA	NA	NA			
	e. No. of continuous staircases to terrace	NA	NA	NA			
	g. Width of Corridor	1 no.	1 no.	MR			
	h. Door Size	1.2 m	1.2 m	MR			
		1 m	1 m	MR			
3	Compartmentation.						
	Fire check door	NA	NA	NA			
	Sealing of electrical shafts	NA	NA	NA			
	 Fire rating of shaft door 	NA	NA	NA			
	Water curtain	NA	NA	NA			
	Fire Dampers	NA	NA	NA			
4	Smoke Management System.						
	Basement	NA	NA	NA			
	 Upper floor 	NA	NA	NA			

5.	Fire Extinguisher	08 no.	08 no.	MR		
	Total numbers	CO ₂ +ABC	CO ₂ +ABC	MR		
	• Types	ISI marked	ISI marked	MR		
	IS marking	151 Markeu	131 marked			
6	First-aid-Hose Reels.		1 no.	MR		
	Total numbers of each floor	1 no.	30 m	MR		
	Length of hose reel hose	30 m		MR		
	Nozzle diameter	5 mm	5 mm	IVII		
7	Automatic fire detection and alarming system.					
1000000	Type of detectors	NA	NA	NA		
	Location of main panel	NA	NA			
	Location of repeater panel	NA	NA	NA		
	Alternate source of power	NA	NA	NA		
	Hooters's location	NA	NA	NA		
0	NACEA	NA	NA	NA		
8	MOEFA Dublic address System	NA	NA	NA		
9	Public address System.					
10	Automatic Sprinkler System.	NA	NA	NA		
	basement	NA	NA	NA		
	upper floor	NA	NA	NA		
	sprinkler above false ceiling	14/1				
11	Internal Hydrants	NA	NA	NA		
	size of riser/down-comer	NA	NA	NA		
	Number of hydrants per floor	NA	NA	NA		
	Hose Box	IVA	1473			
12	Yard Hydrants.	NA	NA	NA		
	Total number of hydrants	1 201	NA NA	NA		
	Hose Box	NA	IVA			
13	Pumping Arrangements.	1.010	NA	NA		
	Ground Level	NA	NA	NA		
21.7	Discharge of main Pump	NA	NA NA	NA		
	Head of Main Pump	NA	NA NA	NA NA		
	Number of main pumps	NA	1 100000	NA NA		
	Jockey pump out put	NA	NA.	NA NA		
	Jockey pump head	NA	NA NA	NA NA		
	> Standby pump out put	NA	NA	NA NA		
	> Standby pump Head	NA	NA	NA NA		
	Auto Starting / Manual stopping	NA	NA			
*	Pump House Access	NA	NA	NA		
	Terrace Level					
	Discharge of pump	225 LPM	225 LPM	MR		
	Head of the Pump	40 m	40 m	MR		
	Power supply	Required	Provided	MR		
	Auto Starting of pump	Required	Provided	MR		

14	Captive Water Storage for Fire Fighting.					
	Underground tank capacit5y	NA	NA	NA		
	Draw-off connection	NA	NA	NA		
	Fire service inlet	NA	NA	NA		
	Access to tank	NA	NA ·	NA		
	Overhead Tank capacity	5,000 Liters	5,000 Liters	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	NA	NA	NA		
	Pressurization of Lift lobby	NA	NA	NA		
	Communication in lift car	NA	NA	NA		
	Firemen's grounding switch	NA	NA	NA		
	Lift Signage	NA	NA	NA		
17	Standby power supply	NA	NA	NA		
18	Refuge Area.					
13514	Total area	NA	NA	NA		
	Location	NA	NA	NA		
19	Fire Control Room					
	Detector system panel	NA	NA	NA		
	Flow switch panel	NA	NA	NA		
	PA system panel	NA	NA	NA		
	Batter backup	NA	NA	NA		
	Building Floor Plans	NA	NA	NA		
20	Special Fire Protection systems for	NA	NA	NA		
	protection of special Risks, if any:					
20		NA	NA	NA		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules the FSC issued vide letter no. F.6/DFS/MS/GH/2012/1948 dated 29.05.2012 renewal under Rule 35 of the Delhi Fire Service Rules 2010 is recommended to grant fire safety certificate.

Signature of the Inspecting Officer

Name

Suresh Singh

Designation

ADO (Shah)

Submitted for approval please.