GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ MD2/580

Dated: 21/09/15

FIRE SAFETY CERTIFICATE

Certified that the Azmi Hostel located at 198, Gali Garahiya, Matial Mahal, Jamam Masjid, Delhi-110006 comprised of Ground, Mezzanine + 3 Upper Floors (Ground floor--dormitory for 07 beds+ 01 store room+ reception, Mezzanine-01 store room, first floor---03 rooms, 2nd Floor—dormitory for 12 beds+ 01 guest room & 3rd floor—dormitory for 12 by this department granted **FSC** room) was beds+ 01 guest No.F6/DFS/MS/GH/2012/953 dated 15/03/2012. The premise was re-inspected by the officer concerned of this department on 09/04/15 in the presence of Mr. Irfan Ahmed and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 04 dormitory (hall) with 15 beds only (Ground floor-01 dormitory hall with 04 beds, first floor-01 dormitory hall with 03 beds, second floor-01 dormitory hall with 04 beds, third floor - 01 dormitory hall with 04 beds)) with effect from -21/04/1/2--- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below. conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -2-1/-5---at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Ph: - 011-23414333

Ph: - 011-23414333

Copy to: (1) The Additional Commissioner of Police (Lic.), (ref no. 3484/Jt CP/Lic dt 20.02.15) 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Manager, Azmi hostel, 198, Gali Garahiya, Matia Mahal, Jama Masjid, Delhi-110006.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

1/10

INSPECTION REPORT

1. Name & address of the building:- Azmi Hostel, 198Gali Garahiya, Matia Mahal, Jama Masjid, Delhi-110006.

2. Type of occupancy:- Residential Group A-1 Ground+ Mezz+3

Upper Floors (04 dormitory with 15 beds)

3. Type of case:- Renewal

4. Details of previous NOC:- No. F6/DFS/MS/GH/2012/953 dated

15/03/2012.

5. Fire safety directives No.- N/A

6. Date of inspection:- 09/04/15

7. Name of the inspecting officer:- A.D.O. Rajesh Kumar

8. Name & designation of officer
From the building side:- Mr. Irfan Ahmed

9. Year of construction:- Old.

10. Applicant's letter No:- 3484/Joint.C.P./Lic. (H) Dated 20/02/15

S.No.	Minimum Standards on fire	Requirement	Pr	ovided at site		d Case marks	
5.110.	Prevention and fire safety U/R 33	(PSS Area)	PS			R/NMR	
1.	Access to Building						
	1) Road width	N/A.	10	feets	MR		
	2) Gate width	N/A	N	N/A		N/A	
	3)Width of internal road	N/A	N	/A	N/A	4	
2.	Number, Width Type & Arran	gement of Exits					
	A. Number of staircases						
	1. Upper floors	01 No	01 No.		MR		
	2. Basements	N/A	N/A		N/A	4	
	B. Width of staircase						
	1. Upper floors	80 cms.	0.81m		MF	2	
	2. Basements	N/A	N/A		N/A	4	
	C. Protection of exits						
	1. Fire check door	N/A	N/A		N/A		
	2. Pressurization	N/A	N/A		N/A	200	
	D. No. of continuous	01 No	01 No		MI	3	
	staircase to terrace						
	E. Width of corridor	N/A	N/A		N/		
	F. Door size	1 mtr.	1 mtr.		MI	2	
3.	Compartmentation						
	1) Fire check door	N/A	N/A		N/		
	2) Sealing of electrical shafts	N/A	N/A		N/		
	3) Fire rating of shaft door	N/A	N/A		N/		
	4) Water curtain	N/A	N/A		N/		
	5) Fire Dampers	N/A	N/A		N/	A	
4.	Smoke Management System						
	1) Basements	30 ACPH		N/A		N/A	
	2) Upper floors	12 ACPH		Natural		MR	
5.	Fire Extinguishers						
	1) Total numbers	06 Nos.		06 Nos.		MR	
	2) Types	ABC & CO2		ABC, CO2 &		MR	

11/4

		W.CO2				
3) ISI marking	ISI	Yes	MR			
1)Total number of each floor	01 No.	Provided at Ground & 2 nd floor	MR			
2) Length of hose reel hose	30 m	30 m	MR			
3) Nozzle diameter	5 mm	5 mm	MR			
Automatic Fire Detection & Alarming System						
	N/A	N/A	N/A			
	N/A	N/A	N/A			
	N/A	N/A	N/A			
	N/A	N/A	N/A			
5) Hooter's Location	N/A	N/A	N/A			
MOEFA	N/A	N/A	N/A			
	Required	Provided	MR			
Automatic Sprinkler System						
1) Basement	N/A	N/A	N/A			
	N/A	N/A	N/A			
	N/A	N/A	N/A			
	N/A	N/A	MR			
	N/A	N/A	MR			
	N/A	N/A	MR			
Yard Hydrants						
		N/A	N/A			
	N/A	N/A	N/A			
Pumping Arrangement		1				
	N/A	N/A	N/A			
a) Discharge of main	N/A	N/A	N/A			
pump	- 2	an en				
	N/A	N/A	N/A			
pump	N/A	N/A	N/A			
	N/A	N/A	N/A			
e) Jockey pump head	N/A	N/A	N/A			
f) Stand by pump output	N/A	N/A	N/A			
g) Stand by pump head	N/A	N/A	N/A			
h) Auto starting/Manual stopping	N/A	N/A	N/A			
a) Discharge of pump	Required	225 LPM	MR			
b) Head of pump	35 m	35 m	MR			
	Required	Provided	MR			
d) Auto starting of pump	Required	Provided	MR			
	First-Aid Hose Reel 1)Total number of each floor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & A 1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	First-Aid Hose Reel 1) Total number of each floor 2) Length of hose reel hose 30 m 3) Nozzle diameter 5 mm Automatic Fire Detection & Alarming Syster 1) Type of detectors N/A 2) Location of main panel N/A 3) Location of repeater panel N/A 4) Alternate source of power N/A 5) Hooter's Location N/A MOEFA N/A Public Address System Required Automatic Sprinkler System 1) Basement N/A 2) Upper floors N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/A 2) Number of hydrants per floor 3) Hose box N/A Yard Hydrants 1) Total number of hydrants N/A 2) Hose box N/A Pumping Arrangement 1) Ground level N/A a) Discharge of main pump b) Head of main pump c) Number of main N/A pump d) Jockey pump out put N/A e) Jockey pump out put N/A f) Stand by pump head N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply Required	Silant S			



N/12

	Under ground tar capacity	nk N/A	N/A	N/A
	a) Draw-off connec	A STATE OF THE PARTY OF THE PAR	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 Ltrs.	2,500 Ltr.	MR
15.	Exit Signage.			MR
16.	Provision of Lifts.			IVIIC
	a) Pressurization of shaft	lift N/A	N/A	N/A
	b) Pressurization of lobby	lift N/A	N/A	N/A
	c) Communication i		N/A	N/A
	d) Fireman's switch		N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch pane	1 N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor pla		N/A	N/A
20.	Special Fire Protection Syany:	01 fire extinguisher provided near elect panel		

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/GH/2012/ 953 dated 15/03/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

M15/4/18 Rajesh Kumar Assistant Divisional Officer