GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/M02/529

Dated: 13/09/15

FIRE SAFETY CERTIFICATE

Certified that the M/s Hotel India located at 691,Queens Garden,Bagh Deewar,Fatehpuri Delhi.comprised of Ground + 3 Upper Floors (Ground floor- 05 guest rooms + reception + office, first floor- 07 guest rooms + 01 staff room, 2nd Floor—08 guest rooms & 3rd floor—02 guest rooms + 01 store + 01 staff room = 22 guest rooms) was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/1262 dated 10/04/2012. The premise was re-inspected by the officer concerned of this department on 21/03/15 in the presence of Mr. Dharam Singh and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 (22 guest rooms at ground to 3rd floor) with effect from -1-3-1-0-4-1-5------ for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -13 / 6 4 / --- at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

0/1

lmg/4

(2) The Manager, M/s Hotel India,691,Queens Garden,Bagh Deewar,Fatehpuri Delhi...

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSP	ECTION REPO	RT			
1	Name & address of the building		ndia,691,Queens (Farden Ragh		
1.	Name & address of the building		ehpuri Delhi.	Jaruen, Dagn		
2	Type of occupancy:-		Group A-1 Groun	d 1 Innar		
۷.	Type of occupancy		guest rooms)	d 5 Opper		
3.	Type of case:-	Renewal	guest rooms)			
3. 4.	Details of previous NOC:-		S/MS/GH/2012/12	062 dated		
4.	Details of previous NOC	10/04/2012		202 dated		
5	Fire safety directives No	N/A	•			
6.	Date of inspection:-	21/03/15				
	7. Name of the inspecting officer:- Name & designation of officer D.O. Gurmukh singh					
0.	From the building side:-	Mr. Dharan	Singh			
9	Year of construction:-	1954	i biligii.			
	Applicant's letter No:-		C.P./Lic. (H) Date	d 20/02/15		
10.	rippireum s letter 100.	5400/30III.	C.1 ./ Lic. (11) Date	Old Case		
S.No.	Minimum Standards on fire	Requirement	Provided at site			
J.1 10.	Prevention and fire safety	(PSS Area)	PSS	MR/NMR		
	U/R 33	(10011100)				
1.	Access to Building					
	1) Road width	Required	7 Mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arran		14/11	14/11		
-	A. Number of staircases	Sometic of Exits				
	1. Upper floors	01 No	01 No.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase	14/71	14/74	14/74		
	1. Upper floors	80 cm	97 cm	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits	IN/A	IVA	IVA		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace	DT/A	NT/A	DT/A		
	E. Width of corridor	N/A	N/A	N/A		
2	F. Door size	82 cms.	82 cms.	MR		
3.	Compartmentation	27/4	27/4	77/4		
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
Consum of the Co	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	07 Nos.	07 No.	MR		
	2) Types	ABC & CO2	ABC, CO2 &	k MR		

N-22

			W.CO2			
	2) [G]	ISI	Yes	T.		
	3) ISI marking First-Aid Hose Reel	151	168	- 10		
5.		01 No.	01 No. at	MR		
	1)Total number at each floor	OT NO.	ground & 2			
	11001		floor	,		
	2) Length of hose reel hose	30 m	30 m	MR		
	3) Nozzle diameter	5 mm	5 mm.	MR		
7	Automatic Fire Detection & A		J IIIII.	IVIIC		
7.	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
3.	MOEFA	N/A	N/A	N/A		
) <u>.</u>	Public Address System	Required	Provided	MR		
0.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants					
11.	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor			3-,		
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement		The state of the s			
10.	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump	N 1				
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	p N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output		N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual		N/A	N/A		
	stopping					
	2) Terrace level					
	a) Discharge of pump	Required	225 LPM	MR		
	b) Head of pump	Required	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump		Provided	MR		
14.	Captive Water Storage for Fi					
	1) Under ground tank	N/A	N/A	N/A		

N-23

	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 Ltrs.	2,500 Ltr.	MR
15.	Exit Signage.	Required	Required	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No.F6/DFS/MS/GH/2012/1262 dated 10/04/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

DY. CFO (NDZ)

1001