## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2015/1402/675

## FIRE SAFETY CERTIFICATE

Certified that the Ashwani Lodge Guest House located at 8696-99, D.B.G. Road, Pahar Gani, New Delhi comprised of Basement + Ground + 04 Upper floors having 15 guest rooms, Basement (Storage), Ground floor (02 guest rooms + reception), 1st floor to 3<sup>rd</sup> floor (04 guest rooms at each floor + 01 store room at each floor) and 4<sup>th</sup> floor (01 guest rooms + 01 Manager room + 01 staff rooms) was granted FSC by this department vide letter No.F6/DFS/MS/2012/GH/3099 dated 27/08/12. The premises was re-inspected by the officer concerned of this department on 25/04/15 in the presence of Sh. Umesh (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 15 guest rooms only with effect from ----- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -----at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Ph-011-23414333

Copy to:-

- opy to:
  1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. letter no. 6226/Joint/C.P./Lic.(H) dated 09/04/2015.
- 2. Mr. Umesh (Manager),

Ashwani Lodge Guest House located at 8696-99, D.B.G. Road, Pahar Gani, New Delhi Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

## **INSPECTION REPORT**

1. Name & address of the building:- Ashwani Lodge Guest House located at

8696-99, D.B.G. Road, Pahar Ganj, New Delhi

2. Type of occupancy:-Residential, Sub Division-A-1

B + Gr. + 04 Upper floors (total 15 Guest rooms)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/2012/GH/3099 dated

> 27/08/12. N/A

5. Fire safety directives No.-

6. Date of inspection:-25/04/15

7. Name of the inspecting officer:-

Sh. Manoj Sharma (ADO/CC)

8. Name & designation of officer From the building side:-

Mr. Umesh (Manager)

9. Year of construction:-1983

10. Applicant's letter No:-No. Nil dated 12/04/2015.

CNI	N. C. I.		· · · · · · · · · · · · · · · · · · ·	Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site PSS	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	18 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3) Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Ari			IVA	
	A. Number of staircases	gement of L			
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	01 Nos.	01 Nos.	MR	
	B. Width of staircase				
	1. Upper floors	C.83 mtr.	1.35 mtr.	MR	
	2. Basements	0.80 mtr.	0.80 mtr.	MR	
	C. Protection of exits				
2	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	01	01	MR	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation	, , , , , , , , , , , , , , , , , , , ,	Ģ.		
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	Exhaust fans	MR	
	2) Upper floors	12 a/c per	Natural	MR	

		hour	Ventilation		
5.	Fire Extinguishers	6			
	1) Total numbers	12 Nos.	12 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel	9			
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 m	30 m	MR	
	3) Nozzle diameter	5 mm	5 mm	MR	
7.	Automatic Fire Detection & Alarming System				
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System				
	1) Basement	Required	Provided	MR	
	2) Upper floors	N/A	N/A	N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling				
11.	Internal Hydrants				
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per	N/A	N/A	N/A	
	floor				
	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants				
	1) Total number of hydrants	N/A	N/A	N/A	
\	2) Hose box	N/A	N/A	N/A	
13.	Pumping Arrangement				
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A	
	pump				
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	
	stopping				
	2) Terrace level	007777			
	a) Discharge of pump	225 LPM	225 LPM	MR	
	b) Head of pump	30 mtr.	30 mtr.	MR	
	c) Power supply	Required	Provided	MR	
1.4	d) Auto starting of pump	Required	Provided	MR	
14.	Captive Water Storage for Fi	re Fighting			

	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank	5000 ltrs.	5000 Ltr.	MR
15.	capacity  Exit Signage	7 1		
	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syster Risk, if any:	m for Protection	on of special	NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/3099 dated 27/08/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Date 36-LI-IS-Diary No.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)