FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/ans/2015/W2/660

Dated: 01/05/15

FIRE SAFETY CERTIFICATE

Certified that the Jain Banquet located at Plot no-10 Wazirpur Press Area, Near Panjab Kesari, N Delhi -110035 in a building comprised of Basement + Ground Floor + 01 Upper Floor owned/occupied by Jain Banquet have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on 04/03/2015 in the presence of Sh Sanjeev Jain (Owner) and the building/premises is fit for occupancy class "Assembly" Group D with effect from 01/01/15 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .. 01/00/15. at New Delhi by.

(Santokh Singh) Chief Fire Officer Delhi Fire Service Phone -23414250

Copy to:

Sh. Sanjeev Jain, Jain Banquet, Plot no-10 Wazirpur Press Area, Near Panjab Kesari, N Delhi -35 Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws. 1983.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form II [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www designation.

INSPECTION REPORT

 Name & address of the building: Jain Banquet at Plot no-10 Wazirpur Press Area, Near Panjab Kesari, N Delhi -110035

2. Type of Occupancy

: Assembly (Basement+G+1 upper Floor)

3. Type of Case

:New

4. Details of previous NOC

: F-6/DFS/MS/BP/97/1521 Dated 15/10/97(For

Industry)

5. Fire Safety directives Letter No.: F-6/MS/BP/96/879 dated25/07/1996 (For

Industry)

Plot Area = 810m²

6. Date of inspection

: 04-03-2015

Covered Area = 995m2

7. Name of the Inspecting Officer: DO/W&ADO (WP)

Basement=405 m², Ground=405 m² 1st Floor=185 M2

8. Name and designation of Officer

from the building side

: Sh. Sh Sanjeev Jain (owner)

9. Year of Construction

: 1997 -98

10. Applicant's letter No.

: Nil Dated02/01/2015

| S No | Minimum standards on fire prevention and fire safety U/R 33 | BBL Requirements | Provided at site | Remarks MR/NMR | | |
|---------|---|---------------------|------------------|-------------------|--|--|
| 1. | Access of building 12mtrs MR | | | | | |
| | Road width | 09 m | 12mtrs | MR | | |
| | Gate width | 5 m | Provided | NA | | |
| at . | Width of internal | NA | NA | INA | | |
| | road | | | | | |
| 2. | Number, width, Type & Arrangements of exits | | | | | |
| | a. Number of staircases | 8 | | MD | | |
| | Upper floors | 2 | Provided | MR | | |
| | Basements | 2 | Provided | MR | | |
| | b. Width of staircases | | | 1 (D) | | |
| | Upper floors | 2 mtr& 1.25mtr | | MR | | |
| | Basements | 1.5m&1.25m | 1.5m&1.3m | | | |
| | c. Protection of exits | | | | | |
| | Fire check door | Required | Provided | MR | | |
| | Pressurization | NA | NA | NA | | |
| | d. No of continuous | 1 | Provided | MR | | |
| | staircase to terrace | * | 22 | | | |
| | e. Width Of Corridor | NA | NA | NA | | |
| | f. Door Size | 2x1.2m | 2mtrs &1.3m | MR | | |

| 3. | Compartmentation | | | |
|-----|---|------------|------------|--------|
| | Fire check door | Required | Provided / | MR |
| | • Sealing of electrical shafts | NA | NA | NA |
| | • Fire Rating of shaft door | NA | NA | NA |
| | Water Curtain | NA | NA | NA |
| | Fire Dampers | NA | NA | NA |
| 4. | Smoke managements System | | | |
| | Basements | Required | Provided | MR |
| 141 | Upper floors | Required | Provided | MR |
| 5. | Fire Extinguishers | | | |
| | Total numbers | 08 nos. | Provided | MR |
| | Types | ABC & CO2 | Provided / | MR |
| | IS marking | ISI marked | Provided | MR |
| 6. | First – Aid Hose Reels | | | |
| | Total numbers on | 01 | Provided | MR |
| | each floor | . 30 m | Provided | MR |
| | Length of hose reel hose | 5 mm | Provided | MR |
| | Nozzle diameter | | | |
| 7. | Automatic fire detection and | | | |
| | Type of detectors | NA | NA | NA |
| | Location of Main | NA | NA | NA |
| | Panel • Location of Repeater | NA | NA | NA |
| | Panel • Alternate source of | NA | NA | NA |
| | power Hooters' Location | NA | NA | NA |
| 8. | MOEFA | Required | Provided / | MR |
| 9. | Public Address System | NA | NA | NA |
| 10. | Automatic Sprinkler System | L | | |
| | BasementsUpper Floor | Required | Provided | MR |
| | | NA | NA | NA |
| | Sprinkler above false ceiling | NA | NA | NA |
| 11. | Internal Hydrants | 1477 | 1111 | 1 47 7 |
| 11. | Size of riser/down- | 100 mm | Provided / | MR |
| | • Size of riser/down-w | 1 | Provided / | MR |
| | | 1 | Provided / | |
| | Number of hydrants per floor | 1 | 1 Tovided | MR |
| | Hose Box | | | |

| 12. | Yard Hydrants | | | | |
|-----|--|-------------|--|-------------------|--|
| | Total number of | NA | NA | NA | |
| | hydrants | | | | |
| | Hose Box | NA | NA | NA | |
| 13. | Pumping Arrangements | | | | |
| | Ground Level | | | | |
| | Discharge of main | NA | NA | NA | |
| | pump | ^ | | N | |
| | Head of main pump | NA | NA | NA | |
| | Number of main | NA | NA | NA | |
| | pumps | 27.4 | | | |
| | > Jockey pump out put | NA | NA | NA | |
| | Jockey pump head | NA | NA | NA | |
| | Standby Pump out put | NA | NA | NA | |
| | > Standby Pump Head | NA | 27.4 | | |
| | > Auto Staring/Manual | INA | NA | NA | |
| | stopping | NA | NA | DT A | |
| | > Pump House Access | INA | INA | NA | |
| | Terrace level | NA | NA | NA | |
| | Discharge of pump | 1111 | 11/21 | INA | |
| | > | 900 lpm | Provided | MR | |
| | Head of the pump | 40 m | Provided | MR | |
| | > Power supply | Required | Provided | MR | |
| | > Auto starting of | Required | Provided | MR | |
| 14. | pump | C 1 | | | |
| 14. | Captive water Storage for fire | NA | 100001 | 72 11 11 | |
| | Under ground tank capacity | NA | 10000 ltrs | Provided in | |
| | Capacity | | The state of the s | 2 plastic | |
| | > Draw of connection | NA | NA | tanks at GF NA | |
| | Fire service inlet | NA | NA NA | NA NA | |
| | > Access to tank | NA | NA | NA NA | |
| | Overhead Tank | 20,000 ltrs | Provided | MR | |
| | capacity | | 110 /1404 | IVIIC | |
| 15 | Exit Signage | Required | Provided | MR | |
| 16. | Provision of Lifts | | | | |
| | > Pressurization of | NA | NA | NA | |
| | Lift Shaft | | | | |
| | Pressurization of lift | NA | NA | NA | |
| | lobby Communication in | 27.1 | | | |
| | lift Car | NA | NA | NA | |
| | Fireman's | NA | NA | NA | |
| | Grounding Switch | | и п | ~ `^ ` | |
| | Lift Signage | NA | NA | NA | |
| 17. | Standby power supply | Required | Provided | MR | |
| | | | | | |

| Refuge Area | NA | NA | , | |
|---------------------------|---|---|---|--|
| > Total area | NA | NA | NA | |
| > Location | NA | NA | NA | |
| Fire control room | | | | |
| Detector system | NA | NA | NA | |
| panel | NA | NA | NA | |
| > Flow Switch Panel | NA | NA | NA | |
| > PA System Panel | NA | NA | NA | |
| Battery backup | NA | NA | NA | |
| Building Floor Plans | | | | |
| Special Fire Protection | NA | NA | NA | |
| Systems for Protection of | | | | |
| special Risks, if any; | * // A / | | 4 | |
| | ➤ Total area ➤ Location Fire control room ➤ Detector system panel ➤ Flow Switch Panel ➤ PA System Panel ➤ Battery backup ➤ Building Floor Plans Special Fire Protection Systems for Protection of | Total area Location NA Fire control room Detector system panel NA Flow Switch Panel PA System Panel NA Battery backup Building Floor Plans Special Fire Protection Systems for Protection of | ➤ Total area NA NA ➤ Location NA NA Fire control room NA NA ➤ Detector system panel NA NA NA NA NA ➤ Flow Switch Panel ➤ PA System Panel ➤ Battery backup ➤ Building Floor Plans NA NA Special Fire Protection Systems for Protection of NA NA | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted noted at serial numbers

Signature of the Inspecting Officer

Name Votation bigh Designation ADO/WP

Signature of the Inspecting Officer