GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ MOZ/607

Dated : 24/04/15

FIRE SAFETY CERTIFICATE

Certified that the Jukaso Inn located at P. 49-50, Sunder Nagar, New Delhi. comprised of Ground +2 Upper Floors having 31 guest rooms (Ground floor has 05 guest rooms + 01 Conference room +01 Pantry, Mezzanine floor 03 guest rooms +01 office, 1st floor 10 guest rooms,2nd floor 13 guest rooms + Residence +01 store) was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/1074 dated 23/03/2012. The premise was re-inspected by the officer concerned of this department on 20/04/15 in the presence of Sh. Parmod Sharma (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 31 guest rooms only at ground to 2nd floor with effect from -2 1/2 - 2 1/2 -

Issued -24-1----at New Delhi by.

(Dr. G.C.Misra) Chief Fire Officer Delhi Fire Service

O Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Manager, Jukaso Inn P. 49-50, Sunder Nagar, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building:- Jukaso Inn P. 49-50, Sunder Nagar, New Delhi.

2. Type of occupancy:- Residential Group A-1 Ground+ 02 Upper

Floors (31 guest rooms)
3. Type of case:
Renewal

4. Details of previous FSC :- No. F6/DFS/MS/GH/2012/1074 dated 23/03/2012.

5. Fire safety directives No.-6. Date of inspection:-N/A20/04/15

7. Name of the inspecting officer:- D.O. Gurmukh Singh

8. Name & designation of officer
From the building side:- Sh. Parmod Sharma (Manager)

9. Year of construction:-

10. Applicant's letter No:- 4498/Joint C.P./Lic.(H) Dated 05/03/2015

Old Case S.No. Minimum Standards on fire Requirement Provided at site Remarks Prevention and fire safety (Existing) MR/NMR U/R 33 1. Access to Building 1) Road width 06 Mtr. 06 Mtr. MR 2) Gate width N/A N/A N/A 3) Width of internal road N/A N/A N/A Number, Width Type & Arrangement of Exits 2. A. Number of staircases 1. Upper floors 02 No 02 No. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 90 Cm each 90 Cm each MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous 01 No 01 No MR staircase to terrace E. Width of corridor 1.00 Mtr. 1.00 Mtr. MR F. Door size 1.0 Mtr. 1.0 Mtr. MR 3. Compartmentation 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A 4. Smoke Management System 1) Basements 30 ACPH N/A N/A 2) Upper floors 12 ACPH Natural MR 5. Fire Extinguishers 1) Total numbers 08 Nos. 10 Nos. MR

	2) Types	ABC & CO2	ABC, CO2 & W.CO2			
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel			WIIC		
	1)Total number of each floor	01 No.	01 No.	MR		
	2) Length of hose reel hose	30 mm	30 mm.	MR		
	3) Nozzle diameter	5 mm	5 mm.	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	Required	Provided			
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System	required	1 TOVIGEG	MR		
*	1) Basement	N/A	N/A	27/1		
	2) Upper floors	N/A		N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	IN/A	N/A	N/A		
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per floor	N/A	N/A	N/A		
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement		14/21	IN/A		
	1) Ground level	N/A	N/A	DT/A		
	a) Discharge of main	N/A		N/A		
	pump	IN/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual stopping	N/A	N/A	N/A		
	2) Terrace level					
	a) Discharge of pump	450LPM	4501 DM	1.00		
	b) Head of pump		450LPM	MR		
	c) Power supply	30 Mtr.	30 Mtr.	MR		
		Required	Provided	MR		
4.	d) Auto starting of pump Captive Water Storage for Fire	Required Fighting	Provided	MR		
		N/A	N/A	N/A		

	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5,000 Ltrs.	5,000 Ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	for Protection of	f special Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/2012/GH/1074 dated 23/03/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended