## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

Fax:-011-23412593

E-mail ID: cfohq.dlfire@nic.in

No. F.6/DFS/MS/GH/2015/ 1402/586

Dated: 22/04/15

## **FIRE SAFETY CERTIFICATE**

Certified that the Guest House SISLEY THE BOUTIQUE located at 53/3, D.B.G Road, Karol Bagh, New Delhi-110005 comprises of Basement, Ground floor + Three Upper floors, using basement as hall/storage, Ground floor as reception, office and bank, first, second & third floor each having six guest rooms respectively (Total 18 guest rooms) was granted NOC by this department vide letter No.F.6/DFS/MS/GH/2012/583 dated 21-02-2012. The premises was re-inspected by the officer concerned of this department on 09-04-2015 in the presence of Mr. Gurpreet Singh (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 Guest House for 18 guest rooms with effect from 22-10-4-1-2015 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(**Dr. G.C. Misra**) Chief Fire Officer Delhi Fire Service Ph-011-23414333

Copy to:-

1. The Joint Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049 w.r.t. letter No. 3791/Joint C.P./Lic.(H) dated New Delhi 24-02-2015

2. Mr. Gurpreet Singh (Owner), Guest House SISLEY THE BOUTIQUE, 53/3, D.B.G Road, Karol Bagh, New Delhi-110005.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

INSPECTION REPORT SISLEY THE BAUTIQUE, 53/3, D.B.G Road, Karol Bagh, N.D-05. 1. Name & address of the building Residential (G.H ) B+G+3 Floor total guest rooms-18 Type of Occupancy 3. Type of Case Renewal F.6/DFS/MS/GH/2012/583 dated 21/02/2012 4. Details of Previous NOC 5. Fire Safety directives letter No N/A 09/04/2015 6. Date of inspection Dy. C.F.O Rajesh Panwar 7. Name of Inspecting Officer 8. Name and designation of officers Sh. Gurpreet Singh (Owner) From the building side Before 2010 9. Year of Construction 3791/Joint C.P/Lic (H) dt New Delhi 24/02/2015 10. Applicant's letter No. Provided at site Remarks NBC/BBL Minimum Standards on fire prevention S. No. MR/NMR special area Requirement and fire safety U/R 33 Access to building 1. MR Accessible 18 mtr Road width NA NA NA Gate width NA NA NA Width of internal road Number, Width, Type & Arrangement of Exits 2. a. Number of staircases. MR One One **Upper Floors** MR One Basements One b. Width of staircases MR 126 to 140 cms 125 cms Upper Floor MR, Old Case 90 cms Basements c. Protection of exits MR Provided NA Fire check door NA NA NA Pressurization No. of continuous staircases to MR One One terrace MR 1.44 Mtr 1.0 Mtr Width of Corridor f. Door Size MR, Old Case 80cm X 204 cm 1.0 Mtr. Compartmentation 3. NA NA NA Fire check door MR Sealing of electrical shafts NA Sealed Fire Rating of shaft door NA NA NA Water Curtain NA NA NA Fire Dampers NA NA NA Smoke Management System 4. Exhaust Fans are MR 30 ACPH Basements provided Natural MR 12 ACPH Upper floors Ventilation Fire Extinguishers 5. Two at each floor Provided MR Total numbers . ABC, Water Co2 MR Provided Types MR ISI marked IS marking ISI marked First-Aid Hose Reels 6. MR Provided One Total numbers on each floor MR 30 m Provided Length of hose reel hose 5 mm Provided MR Nozzle diameter

7.	Automatic fire detection and alarming s		NIA	NA	
	Type of detectors	NA NA	NA	NA	
	Location of Main Panel	NA NA	NA	NA	
	Location of Repeater Panel		NA	NA	
	Alternate source of power	NA	NA	MR	
	Hooters' Location	NA	NA	NA	
3.	MOEFA	Required	Provided	MR	
).	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System				
	Basement	Not Required	Provided	MR, Area less than 200 Sq.m	
	Ground Floor	NA	NA	NA	
	Sprinkler above false ceiling	NA	NA	NA	
1.	Internal Hydrants				
	Size of riser/down-comer	NA	NA	NA	
	Number of hydrants per floor	NA	NA	NA	
	Hose Box	NA	NA	NA	
2.	Yard Hydrants				
, Y	Total number of hydrants	NA	NA	NA	
	Hose Box	NA	NA	NA	
3.	<b>Pumping Arrangements</b>				
	Ground Level				
	Discharge of main Pump	NA	NA	NA	
	Head of Main pump	NA	NA	NA	
	Number of main pumps	NA	NA	NA	
	Jockey Pump out put	NA	NA	NA	
	Jockey pump head	(Fort)   Strf [16] Factor			
	Standby Pump out put	NA	NA	NA	
	> Standby Pump Head	NA	NA	NA	
	> Auto Starting/Manual	NA	NA	NA	
	Stopping	NA	NA	NA	
	<ul><li>Pump House Access</li><li>Terrace level</li></ul>				
	> Discharge of pump	450 LPM	450 LPM	MR	
	> Head of the pump	30 M	30 M	MR	
	> Power Supply	Required	Provided	MR	
	> Auto Starting of pump	NA	NA	NA	
	, interest and or pump	NA	INA	INA	
14.	Captive Water Storage for fire fighting	NA	NA	NA	
	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>	NA NA	NA	NA NA	
	> Fire service inlet				
	> Access to tank	NA	NA	NA	
	Overhead Tank capacity	NA	NA	NA	
		5000 Ltr Required	5000 Ltr Provided	MR MR	
5.	Exit Signage.	Required	Tiovided		
16.	Provision of Lifts.				
	Pressurization of Lift Shaft	NA	NA	NA	
	Pressurization of Lift lobby	NA	NA	NA	
	Communication In lift Car	Required	Provided	MR	
	<ul> <li>Fireman's Grounding Switch</li> </ul>	Required	Provided	MR	
	Lift Signage	Required	Provided	MR	
		Required	Trovided	IVIK	

17.	Standby power supply	Required	Provided	MR
18.	Refuge Area.			
	➤ Total Area ➤ Location	NA	NA	NA
		NA	NA	NA
19.	Fire Control Room			
	<ul> <li>Detector System Panel</li> <li>Flow Switch Panel</li> <li>PA System Panel</li> <li>Batter backup</li> <li>Building Floor Plans</li> </ul>	NA	NA	NA
		NA	NA	NA
		NA	NA	NA
		NA	NA	NA
		NA	NA	NA
20.	Special Fire Protection System for Protection of special Risks, if any:	NA	NA	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2012/583 dated 21.02.2012 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Signature of Inspecting Officer

Signature of Inspecting Officer

Name: Rajesh Panwar

Name

Designation: - Dy. C.F.O (NDZ)

Designation