## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No. F6/OFS/ans/ 9H/2015/52/618

Dated: 27/64/15

## FIRE SAFETY CERTIFICATE

Certified that the M/S Baljeet Lodge, located at A2/13, Africa Avenue, Safdarjung Enclave, New Delhi-110029, comprised of ground floor (Reception+Loby+3 Rooms), 1<sup>st</sup> floor (6 Rooms), 2<sup>rd</sup> floor (6 Rooms), and 3<sup>rd</sup> floor (6 Rooms) total 21 guest rooms, was granted Fire Safety Certificate by this department vide letter No. F6/DFS/MS/GH/201/1627 dated 04-05-12. The premises was re-inspected by the officer concerned of this department on 18-04-2015 in the presence of Sh. Baljeet Singh (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential (Guest House) with effect from 27.1.29.1.2015 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on. 2.7. ..... 2015 at New Delhi by.

(Dr.G.C.Misra)
Chief Fire Officer

T.No.011-2341433

Copy to:-.

M/S Baljeet Lodge, located at A2/13, Africa Avenue, Safdarjung Enclave, New Delhi-110029.

Conditions for the validity of fire safety certificate are overleaf:-

## **CONDITIONS:**

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire
  equipments and method of smooth and speedy safe evacuation of occupants in case of
  emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate on form J, six month prior to its expiry.

**INSPECTION REPORT** 1. Name & address of the building : M/S Baljeet Lodge, located at A2/13, Africa Avenue, Safdarjung Enclave, New Delhi-110029. 2. Building is comprised of : G+3, (Ground floor reception+Loby+3rooms, first floor 6 rooms, 2<sup>nd</sup> floor 6 rooms and 3<sup>rd</sup> floor 6 rooms). Total 21 guest rooms. 3. Type of Occupancy : Lodging House 4. Type of Case : Old Case 5. Details of Previous NOC : No.F.6/DFS/MS/GH/2012/1627, dated-04.05.2012. 6. Fire Safety direction letter No :Nil. 7. Date of Inspection : 18.04.2015. 8. Name of the Inspecting Officers: : Vedpal (ADO) 9. Name and designation of officer from the building side : Sh. Baljeet Singh (Owner) 10. Year of Construction : 1985. 11. Applicant's letter No. :Nil, dated 07.04.15. S.N Minimum Standards on fire Old NOC Provided at Remarks prevention and fire safety U/R33 Requirements Site 1 Access to building Road width 9m 18 m MR Gate width N.A. N.A. N.A. Width of internal road N.A. N.A. N.A. 2 Number, Width, Type and Arrangement of Exits. Number of Staircases a. Upper Floor 02nos. 02nos. MR Basement N.A. N.A. N.A. B. Width of Staircases Upper Floor 125cm 130cms & 75cm MR Basement N.A. N.A. N.A. c. Protection of exits N.A. N.A. N.A. Fire check door N.A. N.A. N.A. Pressurization N.A. N.A. N.A. e. No. of continuous staircases 1no. 1no. MR to terrace. g. Width of Corridor 1.25m 1.25m MR h. Door Size 1m 1m MR 3 Compartmentation Fire check door N.A. N.A. N.A. Sealing of electrical shafts Required Provided MR Fire rating of shaft door N.A. N.A. N.A. Water curtain N.A. N.A. N.A. Fire Dampers N.A. N.A. N.A. 4 Smoke Management System. Basement 30a/c per hour N.A. N.A. Upper floor 12 a/c per hour N.A. N.A.

1/2

5	. Fire Extinguisher	S, Africa Avenue, Sa								
	Total numbers	00 nos								
	types	08 nos.		16 nos.		M	R			
	IS marking	WCO <sub>2</sub> & AE	3C	WCO <sub>2</sub> &		MI				
6	First-aid-Hose Reels.	ISI marked		ISI marked		MR				
	Total numbers of analytic									
Length of hose reel hose		01no.		01no.		MF				
	Nozzle diameter	30 m		30m		MF				
7		5mm		5mm		MF				
	reaction and alarming system									
	Type of detectors						NI A			
	Location of main panel	N.A.		Reception		- 1	N.A.			
	Location of repeater panel	N.A.		AL A			N.A.			
	Alternate source of power Hooters	N.A.		N.A.	. 10		N.A.			
	Toolers			N.A.	4		N.A.			
8	MOEFA	N.A.		Each Floor	r alle		N.A.			
9	Public address System.	Required		Provided	2 A.		MR			
10	Automatic Sprinkler System.	N.A.		Provided	1.184		N.A.			
	Basement									
	upper floor	N.A.		N.A.		N.A.				
	sprinkler above false ceiling	N.A.		V.A.		V.A.				
		N.A.		V.A.		15 20				
	internal Hydrants									
	size of riser/down-comer	100mm	1	00mm		10				
	Number of hydrants per floor Hose Box	01no.	10011111			/IR				
_		01no.		1no.		1R				
2 '	Yard Hydrants.	1 1 1 1 1 1 1 1	0	1110.	IV	1R				
	Total number of hydrants	N.A.	N	.A.		T.al				
	Hose Box	N.A.				.A.	The Tree			
F	Pumping Arrangements.	2.00 10	IN	.A.	N	.A.				
•	• Ground Level N.A.									
1	Disoriarye of main Pump	N.A.		.A.		A.				
>	Head of Main Pump	N.A.		Α.		A.				
1	Number of main pumps	N.A.		A.	N.	Α.				
1	Jockey pump out put	N.A.	N.		N.,	A.				
1	Jockey pump head	N.A.	N.		N.,	Α.				
1	Standby pump out put		N.	May.	N./	۹.	8 V 1			
1	Standby pump Head	N.A.	N.		N.A	۹.				
1	Auto Starting /Manual stopping	N.A.	N./	70	N.A	١.	1			
>	Pump House Access	N.A.	N.A		N.A	١.				
•	Terrace Level	N.A.	N.A		N.A	١.				
^	Discharge of pump	Required		vided	MR					
A	Head of the Pump	450 LPM	450LPM		MR					
1	Power supply	35 Mtrs.		Atrs.	MR					
	Auto Starting of pump	Required	Pro	vided	MR					
		Required	Dro	vided	MR					

Mal

M/S Baljeet Lodge, located at A2/13, Africa Avenue, Safdarjung Enclave, New Delhi-110029.

4	Captive Water Storage for Fire Fighting	N.A.	15000Liters	N.A.				
	Underground tank capacity  Draw-off connection	N.A.	N.A.	N.A.				
	Fire service inlet	N.A.	N.A.	N.A.				
	Access to tank	N.A.	Provided	N.A.				
	Overhead Tank capacity	10000Ltrs.	10000Ltrs.	MR				
4.5		Required	Provided	MR				
15	5 Extragrage.							
16	Pressurization of Lift Shaft	N.A.	N.A.	N.A.				
	Pressurization of Lift Ghalf  Pressurization of Lift lobby	N.A.	N.A.	N.A.				
	Communication in lift car	N.A.	N.A.	N.A.				
	Firemen's grounding switch	N.A.	N.A.	N.A.				
	Lift Signage	N.A.	N.A.	N.A.				
17	Standby power supply	Required	D.G. Set	MR				
	Startuby power suppry							
18	Refuge Area.  Total area	N.A.	N.A.	N.A.				
	Location	N.A.	N.A.	N.A.				
	Fire Control Room							
19		N.A.	N.A.	N.A.				
	Detector system panel Flow switch panel	N.A.	N.A.	N.A.				
	PA system panel	N.A.	N.A.	N.A.				
	Batter backup	N.A.	N.A.	N.A.				
	Building Floor Plans	N.A.	N.A.	N.A.				
20	Special Fire Protection systems for of special Risks, if any:	N.A.	N.A.	N.A.				

The fire protection systems provided in the building were test checked randomly and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the Fire Safety Certificate issued vide letter No.F.6/DFS/MS/GH/2012/1627 dated 04.05.12 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

Signature of the Inspecting Officer

Name: Vedpal
Designation: ADO