GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/EH/2015/ M/2/7 2m

Dated :----1/05/15

FIRE SAFETY CERTIFICATE

Issued -----at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph-011-23414333

- Copy to:- (1) Medical Officer of Health, New Delhi Municipal Council, Palika Kendra, New Delhi.
 - (2) The Manager.Chicken Inn Restaurant13,14 &15 Pandora Road Market, New Delhi.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building:- Chicken Inn Restaurant 13, 14 &15, Pandora Road Market, New Delhi.

2. Type of occupancy:
Group – D Assembly Building (Gr. + 1)

Restaurant at ground floor only.

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/2012/EH/1266 dated 10/04/12.

5. Fire safety directives No.- N/A

6. Date of inspection:- 02/05/15

7. Name of the inspecting officer:- D.O. Gurmukh Singh.

8. Name & designation of officer
From the building side:- Mr. Rahul

9. Year of construction:-

10. Applicant's letter No:- Nil. dated -Nil-

| 10. | Applicant's letter 140 | NII. dated | 1 -N1I- | | |
|-----------|---|-------------------------|----------------------|-------------------------|--|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement Existing | Provided at site | Old Case Remarks MR/NMR | |
| 1. | · Access to Building | | | | |
| | 1) Road width | 06 mtr. | 06 mtr. | MR | |
| | 2) Gate width | N/A | N/A | N/A | |
| | 3)Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & Art | | exits | IV/A | |
| | A. Number of staircases | | | _ | |
| | 1. Upper floors (mezz.) | N/A | 01 Nos. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | B. Width of staircase | | | 14/21 | |
| | 1. Upper floors | N/A | N/A | N/A | |
| | 2. Basements | N/A | N/A | N/A | |
| | C. Protection of exits | | | 1771 | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous | N/A | N/A | N/A | |
| | staircase to terrace | | | | |
| | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | 1.25 mtr. | 1.25 Mtr. | MR | |
| | Compartmentation | | | | |
| | 1) Fire check door | N/A . | N/A | N/A | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| 1. | Smoke Management System | | | | |
| | 1) Basements | 30 a/c per hour | N/A | N/A | |
| | 2) Upper floors | 12 a/c per hour | Exhaust fan provided | MR | |

MA

| 5. | Fire Extinguishers | | | | | |
|-----|--|-----------|------------------------|-------|--|--|
| | 1) Total numbers | 06 Nos. | 06 Nos. | MR | | |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | | |
| | 3) ISI marking | ISI | Yes | MR | | |
| 6. | First-Aid Hose Reel | 101 | 105 | IVIK | | |
| | 1) Total number at each floor | 01 No. | 01 No. at ground floor | MR | | |
| | 2) Length of hose reel hose | 30 m | 30 m | MR | | |
| | 3) Nozzle diameter | 5 mm | 5 mm | MR | | |
| 7. | Automatic Fire Detection & Alarming System | | | | | |
| | 1) Type of detectors | N/A | N/A | N/A | | |
| | 2) Location of main panel | N/A | N/A | N/A | | |
| | 3) Location of repeater panel | N/A | N/A | N/A | | |
| | 4) Alternate source of power | N/A | N/A | N/A | | |
| | 5) Hooter's Location | N/A | N/A | N/A | | |
| 8. | MOEFA | Required | Provided | MR | | |
| 9. | Public Address System | N/A | N/A | N/A | | |
| 10. | Automatic Sprinkler System | 2 1/2 2 | 1 1/2 1 | IVA | | |
| | 1) Basement | N/A | N/A | N/A | | |
| | 2) Upper floors | N/A | N/A | N/A | | |
| | 3) Sprinkler above false | N/A | N/A | N/A | | |
| | ceiling | 14/11 | IVA | IN/A | | |
| 11. | Internal Hydrants | | | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A | | |
| | 2) Number of hydrants per floor | N/A | N/A | N/A | | |
| | 3) Hose box | N/A | NT/A | 27/4 | | |
| 12. | Yard Hydrants | IN/A | N/A | N/A | | |
| 12. | 1) Total number of hydrants | NI/A | DT/A | 127/4 | | |
| | 2) Hose box | N/A | N/A | N/A | | |
| 13. | | N/A | N/A | N/A | | |
| 13. | Pumping Arrangement | | 2.71 | | | |
| | 1) Ground level | N/A | N/A | N/A | | |
| | a) Discharge of main pump, | N/A | N/A | N/A | | |
| | b) Head of main pump | N/A | N/A | N/A | | |
| | c) Number of main pump | N/A | N/A | N/A | | |
| | d) Jockey pump out put | N/A | N/A | N/A | | |
| | e) Jockey pump head | N/A | N/A | N/A | | |
| | f) Stand by pump output | N/A | N/A | N/A | | |
| | g) Stand by pump head | N/A | N/A | N/A | | |
| | h) Auto starting/Manual stopping | N/A | N/A | N/A | | |
| | 2) Terrace level | | | | | |
| | a). Discharge of pump | 225 LPM | 225 LPM | MR | | |
| | b) Head of pump | 30 Mtr. | 30 Mtr. | MR | | |
| | c) Power supply | Required | Provided | MR | | |
| | d) Auto starting of pump | Required | Provided | MR | | |
| 4. | Captive Water Storage for Fi | 1 | | 11111 | | |

| | 1) Under ground tank | N/A | NI/A | 27/4 |
|-----|--|------------|------------|------|
| | capacity | IN/A | N/A | N/A |
| | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank | 2,500 Ltr. | 2,500 Ltr. | MR |
| | capacity | | | |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: | | | N/A |

The fire protection system provided in the restaurant were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/2012/EH/1266 dated 10/04/12, renewal under rule35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh Divisional Officer

Dycho (NDZ)