## FORM 'H'

## FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

No. F6/Ofs/ms/215/42/775

Dated: 15/05/15

## FIRE SAFETY CERTIFICATE

Issued on ....... at New Delhi by.

(Santokh Singh) Chief Fire Officer Delhi Fire Service Phone -23414250 E-mail:cfowz.dlfire@nic.in

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working/condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used strictly as per Building Bye Laws.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on

www.dfs.delhigovt.nic.in.

## INSPECTION REPORT

1. Name & address of the building: Le Pacific Banquet Hall, Ground Floor, 31/35, Rohtak Road, Punjabi Bagh, New Delhi – 110026.

2. Type of Occupancy : Assembly at Ground Floor in a building comprised of Basement + Stilt + Ground + 3 Upper Floors

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/2012/BH/1243 dated 09-04-2012

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 09-04-2015

7. Name of the Inspecting Officer: Mukesh Verma ADO (MN)

8. Name and designation of Officer

from the building side : Sh. Rohit Bansal (Director)

9. Year of Construction : 2012

10. Applicant's letter No. : Nil dated 02-03-2015

S	Minimum standards on fire	BBL Requirements	Provided at site	Remarks MR/NMR		
No	prevention and fire safety U/R 33	Requirements	3110			
1.	Access of building					
7.7	<ul> <li>Road width</li> </ul>	12 m	Provided	MR		
	<ul> <li>Gate width</li> </ul>	4.5 m	6 m	MR		
	<ul> <li>Width of internal road</li> </ul>	NA	NA	NA		
2.	Number, width, Type & Arrangements of exits					
	a. Number of staircases					
	<ul> <li>Upper floors</li> </ul>	2	2	NA		
	• Basements	2	2	NA		
	b. Width of staircases					
	Upper floors	1.5 m	1X2 m & 1X1.5m	MR		
	Basements	1.5 m	Provided	MR		
	c. Protection of exits					
	Fire check door	Required	Provided	MR		
	<ul> <li>Pressurization</li> </ul>	NR	NR	NR		
	d. No of continuous	2	2 Provided	NA		
	staircase to terrace	NA	NA	NA		
	e. Width Of Corridor f. Door Size	1X2m, 1X1.5m	Provided	MR		
3.	Compartmentation		Provided	MR		
	Fire check door	Required	1 000 M 100			
	<ul> <li>Sealing of electrical shafts</li> </ul>	NR	NR	NR		
	Fire Rating of shaft door	NR	NR	NR		
	• Water Curtain	NR	NR	NR		
	Fire Dampers	NR	NR	NR		

	C	1	programente System			
	Sm		anagements System	Required	Provided	MR
				Required	Provided	MR
	77'		pper floors	1101		
	FII		guishers	12 nos.	Provided	MR
			tal numbers	ABC & CO <sub>2</sub>	Provided	MR
			pes	ISI marked	Provided	MR
		• IS	marking	101 marrie		
	Fi		d Hose Reels	2	Provided	MR
			otal numbers on each	2	Tiovided	
			oor	30 m	Provided	MR
			ength of hose reel	30 111	1101144	
			ose	5 mm	Provided	MR
		<ul> <li>N</li> </ul>	ozzle diameter	The second secon	TTOVIGEG	
7.	A		ic fire detection and ala	rming system	t Provided	MR
		• T	ype of detectors	Smoke & Hear	Provided	MR
		• L	ocation of Main Panel	Required	Provided	MR
			ocation of Repeater	Required	Provided	IVIIX
	_	P	anel	D 1	Provided	MR
		• A	Iternate source of	Required	Provided	IVIIX
		р	ower ·	72 1 1	Provided	MR
		• H	Hooters' Location	Required		
8.	N	<b>MOEFA</b>		Required	Provided	MR
9.			ddress System	Required	Provided	MR
10		Automat	tic Sprinkler System			T- **
10	1		Basements	Required	Provided	NR
			Jpper Floor	NR	Provided	MR
			Sprinkler above false	NR	Provided	MR
			ceiling			
1.1	1		Hydrants			
11	. 1	mternar	Size of riser/down-	150 mm	Provided	MR
			comer Number of hydrants	2	Provided	MR
	-					
			per floor	2	Provided	MR
-	_		Hose Box			
12	2.	Yard H		NR	NR	NR
			Total number of	INIX		
			hydrants	NR	NR	NR
			Hose Box	1417	1	
1	3.	Pumpir	ng Arrangements			
		•	Ground Level	2200 lpm	Provided	MR
		•	Discharge of main	2280 lpm	Tiovided	
			pump	0.0	Provided	MR
			Head of main pump	80 m	Provided	MR
		>	Number of main pump	os 1	Provided	MR
		>	Jockey pump out put	180 lpm		MR
		$\triangleright$	Jockey pump head	80 m	Provided Not Provide	
		>	Standby Pump out put	2280 lpm		
		>		80 m	Not Provid	
		>	Auto Staring/Manual	Required	Not Provid	ded MR
			stopping		×	
		>	Pump House Access	Required	Not Provid	ded MR
		•	Terrace level	•		
		>	Discharge of pump	900 lpm	Provided	MR
		1	Head of the pump		Provided	·MR

4	> Power supply	Required	Provided	MR	
	> Auto starting of pump	Required	Provided	MR	
4.	Captive water Storage for fire		rectance		
4.	Under ground tank capacity	50,000 litres	Provided	MR	
	> Draw of connection	Required	Provided	MR	
	> Fire service inlet	Required	Provided	MR	
- 2	> Access to tank	Required	Provided	MR	
	Overhead Tank    capacity	10, 000 litres	Provided	MR	
15	Exit Signage	Required	Provided	MR	
16.	Provision of Lifts				
10.	> Pressurization of Lift Shaft	NA	NA	NA	
	> Pressurization of lift lobby	NA	NA	NA	
	Communication in lif	t NA	NA	NA	
	Fireman's Grounding Switch	NA	NA	NA	
	> Lift Signage	NA	NA	NA	
17.	Standby power supply	Required	Provided	MR	
$\frac{17.}{18.}$	Refuge Area				
10.	> Total area	NA	NA	NA	
	> Location	NA	NA	NA	
19.	Fire control room				
19.	> Detector system pane	el NA	NA	NA	
	> Flow Switch Panel	NA	NA	NA	
	> PA System Panel	NA	NA	NA	
	> Battery backup	NA	NA	NA	
	> Building Floor Plans		NA	NA	
20.	Special Fire Protection Systems for Protection of	NA	NA	NA	
	special Risks, if any;				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2012/BH/1243 dated 09-04-2012 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer
Name

Designation

A PO(MV)

Signature of the Inspecting Officer Name Designation