GOVERNMENT OF NATIONAL CAPITALTERRITORYOF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001**

No. F6/DFS/MS/GH/2015/ NOZ / 826 Dated 21/05/15

FIRE SAFETY CERTIFICATE

Certified that the New Delhi Airport Merto Station Retail area of Airport Metro Express Line located at Ajmeri Gate New Delhi comprised of ground, Mezzanine and concourse was granted FSC by this department vide letter No.F6/DFS/MS/2012/360 dated 03-02-2012. The premises was re-inspected by the officer concerned of this department on 06-05-2015 in the presence of Sh. Ankit Raj (Fire Inspector) and found that the said Metro Station (retail area) have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building with effect from 21/05/2-2015 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Dr. G.C. Misra) Chief Fire Officer Ph-011-23414333

Copy to:-

Mr. Rajesh Agrawal, 1. Sr.DGM/E&M, Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

INSPECTION REPORT

1. Name & address of the building : DMRC New Delhi Metro Station of Airport Line

2. Type of Occupancy : Assembly building (D7as Per NBC Part IV 2005)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/2012/360 dated 03/02/2012

5. Fire Safety directives Letter No. : F6/DFS/MS/BP/2011/3249 dated 29/11/2011

6. Date of inspection : 06/05/2015

7. Name of the Inspecting Officer : D.O. Gurmukh Singh & A.D.O. M.K. Sharma

8. Name and designation of Officer

from the building side Sh. Ankit Raj (Fire Inspector)

9. Year of Construction : 2011

10. Applicant's letter No. : DMRC/O&M/Fire/NOC/AMEL/2015/01 dated 29-01-15

	Minimum Standards on fir Prevention and fire safety U/R 33	re Required	Provided at si	te Remarks MR/NMR
1.	Access to Building			
	1) Road width	12 mtr.	10	
	2) Gate width	N/A	18 mtr.	MR
	3) Width of internal road	6	N/A	N/A
2.	Number, Width Type & A	rengement 61	6 mtr.	MR
		trangement of	Exits	
	1. Upper floors	N/A	27/4	
	2. Basements	3 Nos.	N/A	N/A
+	B. Width of staircase	3 1103.	3 Nos.	MR
-	1. Upper floors	N/A	NI/A	
1	2. Basements	1.50 mtr.	N/A	N/A
-	C P	each.	1.50 mtr. each.	MR
	C. Protection of exits			
,	1. Fire check door	Required	Provided	
1	2. Pressurization	Required	Provided	MR
1	D. No. of continuous	N/A	N/A	MR
I	staircase to terrace		14/11	N/A
E	E. Width of corridor E. Door size	2.0 mtr.	2.0 mtr.	MD
	. Door size	1.5 mtr. & 2.0	1.5 mtr. & 2.0	MR
(Omnoviment	mtr.	mtr.	MR
1)	Compartmentation			
2)	Fire check door	Required	Provided	MR
(3)	Sealing of electrical shafts	Required	Provided	MR
4)	Fire rating of shaft door Fire curtain	Required	D 1 1	MR
5)	Fire Dampers	Required	D '1 1	MR
Sn	noke Management System	Required	D	MR

	1) Basements	30 a/c per hour	Provided	MR
	2) Upper floors	12 a/c per	Provided	MR
-		hour		
5.	Fire Extinguishers			
	1) Total numbers	130 Nos.	132 Nos.	MR
	2) Types	ABC & CO2		MR
6.	3) ISI marking	ISI	Provided	MR
0.	First-Aid Hose Reel			
	1) Total number of eachfloor		4 Nos.	MR
	2) Length of hose reel hose	30 mtr.	36 mtr.	MR
7.	3) Nozzle diameter	05 mm	05 mm	MR
/ •	Automatic Fire Detection &			
	1) Type of detectors	Smoke & Heat	Provided	MR
	2) Location of main panel	Ground floor	The state of	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
8.	5) Hooter's Location	Every floor	Every floor	N/A
9.	MOEFA	Required	Provided	MR
10.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System 1) Basement			
		Required	Provided	MR
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	150 mm.	150	
	2) Number of hydrants per	4 Nos.	150 mm.	MR
	floor	4 Nos.	4 Nos.	MR
	3) Hose box per floor	4 Nos.	4 Nos.) (D
12.	Yard Hydrants	T 1103.	14 INUS.	MR
	1) Total number of hydrants	10 Nos.	10 Nos.	MR
	2) Hose box	10 Nos.	10 Nos.	MR
13.	Pumping Arrangement	101105.	10 1,05.	IVIK
	1) Ground level			
	a) Discharge of main	4500 LPM	4500 LPM	MR
	pump	1300 EI IVI	4500 L1 W1	IVIK
	b) Head of main pump	80 mtr.	80 mtr.	MR
	c) Number of main	1 No.	1 No.	MR
	pump		- 110.	IVIIC
	d) Jockey pump out put	180 LPM	180 LPM	MR
	e) Jockey pump head	80 mtr.	80 mtr.	MR
	f) Stand by pump	4500 LPM	4500 LPM	MR
	output			
	g) Stand by pump head	80 mtr.	80 mtr.	MR
	h) Auto starting/Manual	Required	Provided	MR
	stopping		¥	
	2) Terrace level	"	A CONTRACTOR OF THE CONTRACTOR	
	a) Discharge of pump	N/A	N/A	N/A
	b) Head of pump	N/A	N/A	N/A
	c) Power supply	N/A	N/A	N/A
	d) Auto starting of	N/A	N/A	N/A
		1		. 1

	pump	Ti-1.4:		
14.	Captive Water Storage for Fire	Fighting	2.00.000 ltra	MR
	1) Under ground tank	2,00,000 ltrs.	2,00,000 ltrs.	IVIK
	capacity	D: 1	Provided	MR
	a) Draw-off connection	Required		MR
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	N/A
R	d) Over head tank capacity	N/A	N/A	
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	Required	Provided	MR
	b) Pressurization of lift lobby	Required	Provided	MR
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	Required	Provided	MR
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR
20.	Special Fire Protection System any:	for Protection	of special Risk, if	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/2012/360 dated 03/02/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- G.S Chauhan Designation :- DO (CD) Signature of the Inspecting Officer

Name: - M.K. Sharma & Designation: - ADO (CC)