GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2015 / W2 833

Dated 22.05.2015

FIRE SAFETY CERTIFICATE

Certified that the Rajwara Palace located at B-33, Industrial Area, GT Karnal Road, Delhi comprised of ground and first floor was issued FSC vide this office letter No F 6 / DFS /MS/2012/EH/1236 dated 09.04.2012. The premises was re-inspected by the officer concerned of this department on 27.04.2015 in the presence of Sh. Ashok Kapoor and observed that all the fire safety and fire prevention arrangement as provided in the premises are found in good working condition. The premises have therefore deemed complied with the requirement under rule 33 of the Delhi Fire Service Rules, 2010 and building/ premises is fit for occupancy under Assembly with effect from 22.05, 2015 for a period of 03 (Three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on . 22.05. 2015 at New Delhi by

(Santokh Singh) Chief Fire Officer Ph-011-23414250

Copy to:-

- 1. The Dy. Health Officer, North MCD, ---Ref:-DHO/CLZ/2015/2716 dated 09.04.2015. Civil Line Zone, 16, Rajpur Road, Delhi-110054.
- 2. The Manager, Rajwara Palace, B-33, GT Karnal Road, Delhi.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.
- 9. This FSC is valid for banquet hall building comprised of ground and first floor only as plans approved by building department dated 18.04.2007.

Rajwara Palace at B-33, Industrial Area G.T.K. Road, Delhi

INSPECTION REPORT

Ground + One Upper Floors

1. Name & address of the building : Rajwara Palace at B-33, Industrial Area G.T.K. Road,

Delhi, -110033

2. Type of Occupancy : Assembly building

3. Type of Case : Renewal

4. Details of previous NOC : F-6/DFS/MS/2012/EH/1236 dated 09/04/2012

5. Fire Safety directives letter No : F5/DFS/MS/EH/2008/3491 dated 19/12/2008

6. Date of inspection : 27/04/2015

7. Name of the Inspecting Officers : S.S.Tuli /DO NW & Rajesh Kumar /ADO (RN)

8. Name and designation of officers

from the building side : Sh. Ashok Kapoor

9. Year of Construction : 2008-09

				5/2716 Dated 09/		
S. No.		Minimum Standards on fire evention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Pr					
	-	Road width	09 mtr	09 mtr	M/R	
	•	Gate width	5 mtr	5 mtr	M/R	
	•	Width of internal road				
2	Number, Width, Type & Arrangement of Exits					
	a. Nu	mber of staircases	a .		,	
	•	Upper Floors	02	02	M/R	
	•	Basements				
	b. Wi	dth of staircases				
	•	Upper Floors	1.5 mtr	1.85m & 1.85 m	M/R	
	•	Basements				
	c. Protection of exits		-			
	•	Fire check door		. =	,	
		Pressurization				
		The state of the s				
		of continuous staircases to terrace	01	02	M/R	
		dth of Corridor		·		
= 7	f. Doo	or Size	02 m	02m	M/R	

: Rajwara Palace at B-33, Industrial Area G.T.K. Road, Delhi

3	Compartmentation.					
	Fire check door	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
	Sealing of electrical shafts	N.A.	N.A.	N.A.		
	Fire Rating of shaft door	N.A.	N.A.	N.A.		
	Water Curtain	N.A.	N.A.	N.A.		
	Fire Dampers	IN.A.	IV.A.	IV.A.		
1	Smoke Management System.					
	Basements	30 a/c per hour	N.A.	N.A.		
	Upper floors	12 a/c per hour	N.A.	N.A.		
5	Fire Extinguishers	× ×				
	Total numbers	01 WCo ₂ 9 ltr & 01 CO2 type 4.5 kg/	P	M/R		
	• Types	01 DCP type 5 kg (02 no's in each	P	M/R		
	IS marking	floor) ISI marked	P	M/R		
5						
	Total numbers on each floor	01 at each floor	03 on G.F 01 on F.F	M/R		
	 Length of hose reel hose 	30 m	P	M/R		
	Nozzle diameter	5 mm _	P	M/R		
7	Automatic fire detection and alarming	g system.				
	Type of detectors	N.A.	N.A.	N.A.		
	 Location of Main Panel 	N.A.	N.A.	N.A.		
	Location of Repeater Panel	N.A.	N.A.	N.A.		
	Alternate source of power	N.A.	N.A.	N.A.		
	Hooters' Location	N.A.	N.A.	N.A.		
8	MOEFA	Required	Provided	M/R		
9	Public Address System.	N.A.	N.A.	N.A.		
10	Automatic Sprinkler System.					
	Basement	N.A.	N.A.	N.A.		
	Upper Floor	N.A.	N.A.	N.A.		
	Sprinkler above false ceiling	N.A.	N.A.	N.A.		

Size of riser/down-comer 100 mm 100mm M.	'R						
Hose Box							
12 Yard Hydrants.	R						
Total number of hydrants Hose Box N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.A. Pumping Arrangements. Ground Level Discharge of main Pump N.A. Standby Pump out put N.A.	R						
Hose Box N.A. N.A. N.A. Pumping Arrangements. Ground Level Discharge of main Pump N.A.	Yard Hydrants.						
Pumping Arrangements. Ground Level N.A. N.A. N.A.	1 .						
Ground Level Discharge of main Pump N.A. Head of Main pump N.A. N.A. N.A. N.A. N.A. N.A. Jockey Pump out put N.A. Jockey pump head N.A. N.A. Standby Pump out put N.A.	١.						
 Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping N.A. 							
 Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping N.A. 							
 Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping N.A. 	١.						
 Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping N.A. 	١.						
 Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping N.A. N.A.	١.						
 Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping N.A. 	١.						
Standby Pump Head N.A.	١.						
Auto Starting/ Manual stopping N.A. N.A. N.A. N.A.	١.						
Down H.	١.						
Pump House Access N.A. N.A. N.A.							
11/2							
Terrace level							
➤ Discharge of pump 450 LPM P M/F	<u> </u>						
Head of the pump 40 m P M/F	2						
➤ Power Supply R P M/R							
Auto Starting of pump R P M/R 14 Captive Water Storage for fire fighting							
Captive Water Storage for fire fighting.							
Underground tank capacity 75,000 ltr 75,000 ltrs M/R							
Draw-off connection N.A. N.A. N.A.							
Fire service inlet N.A. N.A. N.A.							
Access to tank N.A. N.A. N.A.							
Overhead Tank capacity 25,000 Ltr 25,000 Ltr M/R							
15 Exit Signage. Required Provided M/R							
Provision of Lifts.							

: Rajwara Palace at B-33, Industrial Area G.T.K. Road, Delhi

				L L		
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
	Communication In lift CarFireman's Grounding Switch	N.A.	N.A.	N.A.		
	Lift Signage	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
17	Standby power supply	Required	Provided	M/R		
18	Refuge Area.					
	> Total Area	N.A.	N.A.	N.A.		
	> Location	N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector System Panel	N.A.	N.A.	N.A.		
	Flow Switch Panel	N.A.	N.A.	N.A.		
	PA System Panel	N.A.	N.A.	N.A.		
	Batter backup	N.A.	N.A.	N.A.		
	Building Floor Plans	N.A.	N.A.	N.A.		
20	Special Fire Protection Systems for Protection of special Risks, if any:	N.A.	N.A.	N.A.		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Further, Banquet hall is running at ground floor only and rooms at first floor are being used for the residential purpose own occupied by the owner. Only one room at first floor is being used for bride and grooms makeup purposes.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F-6/DFS/MS/2012/EH/1236 dated 09/04/2012 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer
Name RAJESH KUMAR

Signature of the Inspecting Officer Name S.S. Tuli

Designation Do NWD

Designation ADORN

100loles