GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2015/ HD2/733

Dated: 12/01/15

FIRE SAFETY CERTIFICATE

Issued 12/55/15—at New Delhi by.

(**Dr. G.C. Misra**) Chief Fire Officer Ph-011-23414333

demu

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter No. 6208/Joint C.P./Lic. (H) dated 09/04/2015
- 2. Mr. Sanjeev Kumar (Manager), Indian Guest House located at 8599, D.B. Gupta Road, Pahar Ganj, New Delhi Condition for the validity of fire safety certificate
 - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
 - 3. The trained fire fighting staff should be available round the clock.
 - 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
 - 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
 - 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
 - 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

| | INSPECTION REPORT | | | | |
|----|----------------------------------|--|--|--|--|
| 1. | Name & address of the building:- | Indian Guest House located at 8599, D.B. | | | |
| | | Gupta Road, Pahar Ganj, New Delhi | | | |
| 2. | Type of occupancy:- | Residential, Sub Division-A-1 | | | |
| | | Gr. + 02 Upper floors (total 11 Guest rooms) | | | |
| 3. | Type of case:- | Renewal | | | |
| 4. | Details of previous FSC:- | No. F6/DFS/MS/2012/GH/2907 dated | | | |
| | | 09/08/12. | | | |
| 5. | Fire safety directives No | N/A | | | |
| 6. | Date of inspection:- | 25/04/15 | | | |
| 7. | Name of the inspecting officer:- | Sh. Manoj Kumar Sharma (ADO/CC) | | | |
| 8. | Name & designation of officer | | | | |
| | From the building side:- | Mr. Sanjeev Kumar (Manager) | | | |
| 9. | Year of construction:- | 2001 | | | |

| From the building side:- | Mr. Sanjeev Kumar (Manager) | |
|-----------------------------|--|------|
| 9. Year of construction:- | 2001 | |
| 10. Applicant's letter No:- | No. 6208/Joint C.P./Lic. (H) dated 09/04/2 | 2015 |
| | | |

| | | | | Old Case |
|-------|---|-------------------------|----------------------|-------------------|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement Existing | Provided at site PSS | Remarks MR/NMR |
| 1. | Access to Building | | | |
| | 1) Road width | N/A | 18 mtr. | MR |
| | 2) Gate width | N/A | N/A | N/A |
| | 3)Width of internal road | N/A | N/A | N/A |
| 2. | Number, Width Type & Arrangement of Exits | | | |
| - | A. Number of staircases | | | |
| | 1. Upper floors | 01 Nos. | 01 Nos. | MR |
| | 2. Basements | N/A | N/A | N/A |
| | B. Width of staircase | | | |
| | 1. Upper floors | 0.80 mtr. | 1.08 mtr. | MR |
| | 2. Basements | N/A | N/A | N/A |
| | C. Protection of exits | | | |
| | 1. Fire check door | N/A | N/A | N/A |
| | 2. Pressurization | N/A | N/A | N/A |
| | D. No. of continuous staircase to terrace | 01 | 01 | MR |
| | E. Width of corridor | N/A | N/A | N/A |
| | F. Door size | 1 mtr. | 1 mtr. | MR |
| 3. | Compartmentation | | | |
| | 1) Fire check door | N/A | N/A | N/A |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A |
| | 3) Fire rating of shaft door | N/A | N/A | N/A |
| | 4) Water curtain | N/A | N/A | N/A |
| | 5) Fire Dampers | N/A | N/A | N/A |
| 4. | Smoke Management System | | | |
| | 1) Basements | 30 ACPH | N/A | N/A |
| | 2) Upper floors | 12 a/c per | Nature | MR |

| | | hour | Ventilation | | |
|-----|--|--------------|-------------|-----|--|
| 5. | Fire Extinguishers | * | 147 | | |
| | 1) Total numbers | 06 Nos. | 06 Nos. | MR | |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | |
| | 3) ISI marking | Required | Provided | MR | |
| 6. | First-Aid Hose Reel | | | | |
| | 1) Total number of eachfloor | N/A | N/A | N/A | |
| | 2) Length of hose reel hose | N/A | N/A | N/A | |
| | 3) Nozzle diameter | N/A | N/A | N/A | |
| 7. | Automatic Fire Detection & Alarming System | | | | |
| | 1) Type of detectors | N/A | N/A | N/A | |
| | 2) Location of main panel | N/A | N/A | N/A | |
| | 3) Location of repeater panel | N/A | N/A | N/A | |
| | 4) Alternate source of power | N/A | N/A | N/A | |
| | 5) Hooter's Location | N/A | N/A | N/A | |
| 8. | MOEFA | N/A | N/A | N/A | |
| 9. | Public Address System | N/A | N/A | N/A | |
| 10. | Automatic Sprinkler System | | | | |
| | 1) Basement | N/A | N/A | N/A | |
| | 2) Upper floors | N/A | N/A | N/A | |
| | 3) Sprinkler above false | N/A | N/A | N/A | |
| | ceiling | | | | |
| 11. | Internal Hydrants | | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A | |
| | 2) Number of hydrants per | N/A | N/A | N/A | |
| | floor | | | | |
| | 3) Hose box | N/A | N/A | N/A | |
| 12. | Yard Hydrants | | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A | |
| | 2) Hose box | N/A | N/A | N/A | |
| 13. | Pumping Arrangement | | | | |
| | 1) Ground level | N/A | N/A | N/A | |
| | a) Discharge of main | N/A | N/A | N/A | |
| | pump | | 2 | | |
| | b) Head of main pump | N/A | N/A | N/A | |
| | c) Number of main pump | N/A | N/A | N/A | |
| | d) Jockey pump out put | N/A | N/A | N/A | |
| | e) Jockey pump head | N/A | N/A | N/A | |
| | f) Stand by pump output | N/A | N/A | N/A | |
| | g) Stand by pump head | N/A | N/A | N/A | |
| | h) Auto starting/Manual | N/A | N/A | N/A | |
| | stopping | 1 | | | |
| | 2) Terrace level | | | | |
| | a) Discharge of pump | N/A | N/A | N/A | |
| | b) Head of pump | N/A | N/A | N/A | |
| | c) Power supply | N/A | N/A | N/A | |
| ě. | d) Auto starting of pump | N/A | N/A | N/A | |
| 14. | Captive Water Storage for F | ire Fighting | 2 | | |

var

| | 1) Under ground tank | N/A | N/A | N/A |
|-----|--|----------------|------------------|-----|
| | capacity a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank | N/A | N/A | N/A |
| | capacity | | | |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Syst Risk, if any: | tem for Protec | ction of special | NA |

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/2907 dated 09/08/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

11-545 322

Doled

lishmol 7/5/15 Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)