## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/EH/2015/ MDZ/723

Dated : 11 | 55 | 15

## FIRE SAFETY CERTIFICATE

Issued ------at New Delhi by.

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service Ph-011-23414333

Copy to:- (1) Medical Officer of Health, New Delhi Municipal Council, Palika Kendra, New Delhi.

(2) The Partner, Milano Restaurant,M-89 & 90,1st Floor ,Cannaught Place,New Delhi Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSF	PECTION REPO	ORT	
1.	Name & address of the building			1st Floor
		,Cannaught	Place, New Delh.	
2.	Type of occupancy:-		Assembly Building	g(Gr. + 2)
	T		at 1 <sup>st</sup> floor only.	
3.	31			
4.	Details of previous FSC:-	No. F6/DF 14/06/12.	S/MS/2012/EH/213	39 dated
5.	Fire safety directives No	N/A		
	Date of inspection:-	27/04/15		
7.	Name of the inspecting officer			
	Name & designation of officer		8	
	From the building side:-	Mr. Ravi		
	Year of construction:-	Old.		
10.	Applicant's letter No:-	Nil. dated	30/03/15	
				Old Case
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks
	Prevention and fire safety	Existing		MR/NMR
4	U/R 33			
1.	Access to Building		No. of the last of	
	1) Road width	9 mtr.	12 mtr.	MR .
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arr	angement of Ex	cits	
	A. Number of staircases			
	1. Upper floors (mezz.)	02 Nos	2 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	93 cm & 88	93 cm &88 cm	MR old case
		cm		
	2. Basements	N/A	N/A	N/A
	C. Protection of exits	THE PARTY OF THE		
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous	N/A	N/A	N/A
	staircase to terrace			

11	021100	21105.	IVIIV
2. Basements	N/A	N/A	N/A
B. Width of staircase			
1. Upper floors	93 cm & 88	93 cm &88 cm	MR old case
	cm		
2. Basements	N/A	N/A	N/A
C. Protection of exits	THE THE T		
1. Fire check door	N/A	N/A	N/A
2. Pressurization	N/A	N/A	N/A
D. No. of continuous	N/A	N/A	N/A
staircase to terrace			
E. Width of corridor	N/A	N/A	N/A
F. Door size	N/A	2 mtr.2.4 Mtr.	MR
		&1.0 Mtr.	
Compartmentation			
1) Fire check door	N/A	N/A	N/A
2) Sealing of electrical shafts	N/A	N/A	N/A
3) Fire rating of shaft door	N/A	N/A	N/A
4) Water curtain	N/A	N/A	N/A
5) Fire Dampers	N/A	N/A	N/A
Smoke Management System			
1) Basements	30 a/c per	N/A	N/A
	hour		
2) Upper floors	12 a/c per	Exhaust fan	MR
	B. Width of staircase 1. Upper floors 2. Basements C. Protection of exits 1. Fire check door 2. Pressurization D. No. of continuous staircase to terrace E. Width of corridor F. Door size  Compartmentation 1) Fire check door 2) Sealing of electrical shafts 3) Fire rating of shaft door 4) Water curtain 5) Fire Dampers Smoke Management System 1) Basements	B. Width of staircase  1. Upper floors  2. Basements  N/A  C. Protection of exits  1. Fire check door  N/A  D. No. of continuous staircase to terrace  E. Width of corridor  F. Door size  N/A  Compartmentation  1) Fire check door  1) Fire check door  A) N/A  Sealing of electrical shafts  N/A  N/A  N/A  N/A  3) Fire rating of shaft door  4) Water curtain  N/A  Smoke Management System  1) Basements  30 a/c per hour	B. Width of staircase  1. Upper floors  2. Basements N/A N/A  C. Protection of exits  1. Fire check door N/A N/A  D. No. of continuous staircase to terrace E. Width of corridor N/A  F. Door size  N/A  N/A  Compartmentation  1) Fire check door N/A N/A  N/A  N/A  N/A  N/A  N/A  N/A

		hour	provided			
5.	Fire Extinguishers					
	1) Total numbers	08 Nos.	08 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	ISI	Yes	MR		
6.	First-Aid Hose Reel					
	1) Total number of eachfloor	02	02 at first floor	MR		
	2) Length of hose reel hose	30 m	30 m	MR		
	3) Nozzle diameter	5 mm	5 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	Provided	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	Required	Provided	MR		
	5) Hooter's Location	Required	Provided	MR		
8.	MOEFA	Required	Provided	MR		
9.	<b>Public Address System</b>	Required	Provided	MR		
10.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	Required	Provided	MR		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants	Electrone and				
	1) Size of riser/down-comer	100 mm.	100 mm.	MR		
	2) Number of hydrants per	01 No.	01 No.	MR		
	floor					
	3) Hose box	01 No.	01 No.	MR		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A .	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pum	p N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	C) JOCKEY Dullip lieud			27/4		
	7 7 1	t N/A	N/A	N/A		
	f) Stand by pump outpu		N/A N/A	N/A N/A		
	f) Stand by pump outpug) Stand by pump head h) Auto starting/Manual	N/A				
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	N/A	N/A	N/A		
	f) Stand by pump outpug) Stand by pump head h) Auto starting/Manual	N/A N/A	N/A N/A 900 LPM & 180	N/A N/A		
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump	N/A N/A 180 LPM	N/A N/A 900 LPM & 180	N/A N/A		
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A	N/A N/A 900 LPM & 180 LPM	N/A N/A		

14.	Captive Water Storage for I	Fire Fighting		
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	5,000 Ltr.	5,000 Ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
Lange.	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	em for Protect	tion of special	N/A

The fire protection system provided in the restaurant were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/2012/EH/2139 dated 14/06/12, renewal under rule35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh
Divisional Officer

Dy CFO (700Z)

HOW