GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2015/ No2 | 857

Dated: 27/5/15

FIRE SAFETY CERTIFICATE

Issued 27/15-at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Ph-011-23414333

of LME

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. letter No. 85/Joint C.P./Lic.(H) dated 23/04/2015.
- Sh. Devsis Dutta (Manager), M/s Hotel Sai Palace Dx. located at 3790, Tel Mandi, Pahar Ganj, New Delhi. Condition for the validity of fire safety certificate
 - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

1		PECTION REPO		1 1 2500		
1. Name & address of the building:- M/s Hotel Sai Palace Dx. located at 3790						
2 7	Cyma of a company		di, Pahar Ganj, New	Delhi		
2.	Type of occupancy:-	Residential, Sub Division-A-1				
3	. Type of case:-	Gr. + 04 Upper floors (total 16 Guest rooms) Renewal No. F6/DFS/MS/GH/2012/3004 dated 17/08/12.				
4						
	•					
	5. Fire safety directives No N/A					
	Date of inspection:-	15/05/15	77			
	Name of the inspecting officer	3	Kumar Sharma (A	DO/CC)		
1	. Name & designation of officer		D " () ()			
	the building side: Year of construction:-		s Dutta (Manager)			
		1988	CD /I !- (II) 1-4-12	2/04/2015		
10	. Applicant's letter No:-	No. 85/Joint C	C.P./Lic.(H) dated 2			
S.No.	Minimum Standards on fire	Requirement	Provided at site	Old Case Remarks		
5.140.	Prevention and fire safety	Existing	PSS	MR/NMR		
	U/R 33	Laisting	133	IVININIVIN		
1.	Access to Building					
	1) Road width	N/A	08 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3) Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr	angement of E	xits			
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	0.80 mtr.	1.15 to 1.31 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation			, u		
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 a/c per hour	N/A	N/A		
5.	Fire Extinguishers					

	1) Total numbers	10 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2	ABC & CO2	MR	
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel				
	1) Total number of eachfloor	01	01	MR	
	2) Length of hose reel hose	30 m	30 m	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection & Alarming System				
	1) Type of detectors	N/A	N/A	N/A	
	2) Location of main panel	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	N/A	N/A	N/A	
8.	MOEFA	N/A	N/A	N/A	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System		11071404	IVIIC	
	1) Basement	N/A	N/A	N/A	
	2) Upper floors	N/A	N/A	N/A N/A	
	3) Sprinkler above false	N/A	N/A	N/A	
	ceiling			IVA	
11.	Internal Hydrants				
	1) Size of riser/down-comer	N/A	N/A	N/A	
	2) Number of hydrants per	N/A	N/A	N/A	
	floor		1 1/1 1	IVA	
	3) Hose box	N/A	N/A	N/A	
12.	Yard Hydrants	100	1011	11//1	
	1) Total number of hydrants	N/A	N/A	N/A	
	2) Hose box	N/A	N/A	N/A	
3.	Pumping Arrangement		11/12	IVA	
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	N/A	N/A	N/A N/A	
	pump	1 1/1 1	IVA	IN/A	
	b) Head of main pump	N/A	N/A	N/A	
	c) Number of main pump	N/A	N/A	N/A N/A	
	d) Jockey pump out put	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump output	N/A	N/A	N/A	
	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	N/A	N/A	N/A	
	stopping	IVA	IN/A	N/A	
	2) Terrace level				
	a) Discharge of pump	225 LPM	225 I DM	MD	
	b) Head of pump	25 mtr	225 LPM 25 mtr	MR	
	c) Power supply	Required		MR	
	d) Auto starting of pump	Required	Provided Provided	MR	
	was a successful to the succes	Required	rrovided	MR	
	Cantive Water Storage for E	ro Fighting			
4.	Captive Water Storage for Fi	re Fighting N/A	N/A	N/A	

	a) Draw-off connectionb) Fire service inlet	- 100001 - 1000	N/A	N/A
	The service inici	N/A	N/A	N/A
	to tulik	N/A	N/A	N/A
1.7	capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	
16.	Provision of Lifts.		Flovided	MR
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	NT/A
17	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	N/A
18.	Refuge Area	N/A	N/A	MR
	Total area location		IN/A	N/A
	otal area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	
	a) Detector system	- H-77 ASS. VO		N/A
	panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A N/A
4	a) D-'11'			IN/A
7. 1-		N/A	N/A	N/A
0.	Special Fire Protection System Risk, if any:	n for Protection	on of special	NA NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/3004 dated 17/08/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma 11
Designation: - ADO (CC)