GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/DFS/MS/GH/2015/876

Dated: 29/5/15

FIRE SAFETY CERTIFICATE

Nizamuddin West, Mahila Park road, New Delhi-110013 comprised of ground floor (Reception + 01 office + 04 guest rooms), first floor (05 guest rooms), second floor (06 guest rooms) & third floor (owners residence) owned/occupied by M/s Sufian Residency Guest House have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of Fire Service on 15-05-2015 in the presence of Fauzia Reyaz Siddiqui, owner /manager of the guest house and that the building/premises is fit for occupancy class residential (Guest house) for 15 guest rooms with effect from 2915/15 for a period of _______ years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 29/5/15 at New Delhi by

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. The Joint C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

2. The Manager, the Sufian Residency Guest House located at B-2, Hazrat Nizamuddin West, Mahila Park road, New Delhi-110013.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1 Name & address of the building : M/s Sufian Residency Guest House, B-2, Hazrat Nizamuddin

West, Mahila Park road, New Delhi-110013

2 Type of Occupancy : Lodging House

3 Type of Case : New Case

Details of previous NOC : N/A
 Fire Safety directives letter No : N/A

6 Date of inspection : 15.05.2015

7 Name of the Inspecting Officers : M.K.Chattopadhyay, ADO(M. Road)

8 Name and designation of officers from the building side : Fauzia Reyaz Siddiqui, owner /manager

9 Year of Construction : 2003

10 Applicant's letter No. : 111-115/Joint C.P./Lic.(H) dated 28.04.2015

The said guest house is comprised of ground floor (reception + 04 guest rooms + 01 office), first floor (05 guest rooms), second floor (06 guest rooms) and third floor (owner's residence)

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR
1	Access to building			Б
	Road width	06 mts	provided	MR
	Gate width		Directly accessible from the road	MR
	Width of internal road	N/A	N/A	N/A
!	Number, Width, Type & Arrangement	of Exits		-
	a. Number of staircases	-	- 7	-
	• Upper Floors	01	Provided	MR
	• Basements	N/A	N/A	N/A
	b. Width of staircases	-	-	_
	• Upper Floors	1.0 mts	provided (1.07ml)	MR
	• Basements	N/A	N/A	N/A
	c. Protection of exits	-	, · -	_
	Fire check door	N/A	N/A	N/A
	• Pressurization	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	1.0 mts	Provided	MR
	h. Door Size	1.0 mts	Provided	MR
	Compartmentation.	9		×



54.78.	• Fire check door		more realization and regions assessed as	
	THE CHECK GOOF	N/A	N/A	N/A
	• Sealing of electrical shafts	N/A	N/A	N/A
	Fire Rating of shaft doorWater Curtain	N/A	N/A	N/A
	• Fire Dampers	N/A	N/A	N/A
		N/A	N/A	N/A
4	smoke Management System.			1071
8	• Basements	30 a/c per hour	N/A	N/A
	• Upper floors	12 a/c per hour	N/A	
5	Fire Extinguishers		IV/A	N/A
	• Total numbers	05	Duo.: 1 1	
	• Types	ABC	Provided	MR
	IS marking	ISI marked	Provided	MR
6	First-Aid Hose Reels.		Provided	MR
	 Total numbers on each floor 	01	Provided	
	 Length of hose reel hose 	30 m	Provided	MR
	 Nozzle diameter 	5 mm	Provided	MR
7	Automatic fire detection and alarming	2 system	Tiovided	MR
	Type of detectors	N/A	N/A	N/A
	Location of Main Panel	N/A	N/A	N/A
	• Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
1	Hooters' Location	N/A	N/A	N/A
8	MOEFA	N/A	N/A	N/A
9	Public Address System.	N/A	N/A	N/A
10	Automatic Sprinkler System.			
	Basement Unner Floor	N/A	N/A	N/A
٥	Upper FloorSprinkler above false ceiling	N/A	N/A	N/A
1	_	N/A	N/A	N/A
1	Internal Hydrants	•		
	Size of riser/down-comer Number of hydronts are g	N/A	N/A	N/A
	Number of hydrants per floorHose Box	N/A	N/A	N/A
		N/A	N/A	N/A

12	Yard Hydrants.			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.			
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
٥	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	 Auto Starting/ Manual stopping 	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
	Terrace level			
	Discharge of pump	450 LPM	Provided	MR
	► Head of the pump	40 mts	Provided	MR
	Power Supply	Required	Provided (DG Set)	MR
	Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for fire fighting.			· /
	Underground tank capacity	N/A	N/A	N/A
	Draw-off connection	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A
	Overhead Tank capacity	5,000 lts	Provided	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	➤ Pressurization of Lift Shaft	N/A	N/A	N/A
	➤ Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	N/A	N/A	N/A
	Fireman's Grounding Switch	N/A	N/A	N/A

17	Lift Signage	N/A	N/A	N/A
17	standby power supply	Required	Provided(25 KVA)	
18	Refuge Area.			MR
	> Total Area	N/A	N/A	N/A
19	Fire Control Room	N/A	N/A	N/A
	The Control Room			a.
	 Detector System Panel 	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	 PA System Panel 	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
)	Building Floor Plans Special Fig. 19	N/A	N/A	N/A
	Special Fire Protection Systems for Protection of special Risks, if any:	Required	01 ABC type fire extinguisher cap. 5 Kg found provided near elect. panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, it is recommended to grant fire safety certificate under rule 35 of the Delhi Fire Service rules 2010.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation: - Asstt. Div. Officer (M.Rd)

esignation. - A

DO(8Z) DCFO(8Z)