## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. 6-6/068/MS/Schcol/2015/NOZ/883

Dated: 10/06/15

## FIRE SAFETY CERTIFICATE

(Dr.G.C.Misra) Chief Fire Officer Ph.011-23414333

O/C

To,

The Manager Shri Ram Vidya Mandir School Shri Siddh Hanuman Mandir,Mandawali Fazal Pur,Delhi-92, Copy to:-

The Dy.Director of Education
East Delhi Municipal Corporation
Udyog Sadan,419,FIE,Patparganj,Delhi.

## - Conditions -

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in good working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety certificate can not be treated in any case for regularizations of unauthorized construction if any.
- 6 ."The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate,six months prior to its expiry"
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION F	REPORT					
Name & address of the building : Shree Ram	Vidya Mandir Scho	ool, Shri Siddh F	lanuman			
	zalpur, Delhi-92					
Building is comprised of : <b>G+2</b>						
Rullding is combused of	I					
Type of Occupancy						
Type of case	6//MS/DFS/2006,	/2422 Dated 11	1.09.2006			
Detaile	/CC/Fire safety/20	011/3298 to 33	98			
Fire Safety direction letter No : F.16/Estate Dated. 01.0						
Date of hispection						
Name of the Inspecting Officers: : R.K.Yadav (						
Name of the designation of Officer  from the building side : Manager						
Hom the banding side						
J. Year of Construction	L4 dated 99 04	15				
1,1,00	Requirement	Provided at	Remarks			
No Minimum Standards on fire safety	nequirement	Site	MR/NMR			
requirements as per circular no. 3298 to						
3398 dated 01.03.11						
Access to building	6 m	4 m	Old Case/MR			
Road width	N.A.	N.A.	N.A.			
Gate width		N.A.	N.A.			
Width of internal road	N.A.	14./7.	_			
Number, Width, Type and Arrangement of	EXILS.					
a. Number of Staircases	1 no.	2 no.	MR			
Upper Floor	N.A.	N.A.	N.A.			
Basement	IN.A.	111.7.11				
B. Width of Staircases	4.5	1.05 m, 1 m	MR			
Upper Floor	1.5 m		N.A.			
Basement	N.A.	N.A.	N.A.			
c. Protection of exits	N.A.	N.A.	N.A.			
Fire check door	N.A.	N.A.				
Pressurization	N.A.	N.A.	N.A.			
e. No. of continuous staircases to terrace	1 no.	1 no.	MR			
g. Width of Corridor	1.5 m	1.5 m	MR			
h. Door Size	1 m	1 m	MR			
3 Compartmentation.	_		NI A			
Fire check door	N.A.	N.A.	N.A.			
Sealing of electrical shafts	N.A.	N.A.	N.A.			
Fire rating of shaft door	N.A.	N.A.	N.A.			
Water curtain	N.A.	N.A.	N.A.			
Fire Dampers	N.A.	N.A.	N.A.			
4 Smoke Management System.	Smoke Management System.					
T JIIIOKO MISHISDOM	30a/c per hour	N.A.	N.A.			
Racement	Joan C per mou.					
Basement Upper floor	12a/c per hour		N.A.			

	Total nu	t <mark>inguisher</mark> umbers	6 no.	6 no.	MR		
	types		ABC+ CO <sub>2</sub>	ABC+ CO <sub>2</sub>	MR		
	IS mark	ing	ISI marked	ISI marked	MR		
6	First-aid-Hose Reels.						
	Total number of each floor		01 no.	1 no	MR		
	Length of hose reel hose		30 m	Provided	MR		
	Nozzle diameter		5 mm	Provided	MR		
7	Automatic fire detection and alarming system.						
	Type of detectors		N.A.	N.A.	N.A.		
	Location of main panel		N.A.	N.A.	N.A.		
	Location of repeater panel		N.A.	N.A.	N.A.		
	Alternate source of power		N.A.	N.A.	N.A.		
	Hooters		N.A.	N.A.	N.A.		
8	MOEFA		N.A.	N.A.	N.A.		
9		address System.	N.A.	Provided	MR		
10	Automatic Sprinkler System.						
	Baseme		N.A.	N.A.	N.A.		
	upper f	loor	N.A.	N.A.	N.A.		
		er above false ceiling	N.A.	N.A.	N.A.		
11	Internal Hydrants						
		riser/down-comer	N.A.	N.A.	N.A.		
	Number of hydrants each floor		N.A.	N.A.	N.A.		
	Hose box each floor		N.A.	N.A.	N.A.		
12	Yard H	Yard Hydrants.					
	Total number of hydrants		N.A.	N.A.	N.A.		
	Hose Box		N.A.	N.A.	N.A.		
13	Pumpir	Pumping Arrangements.					
	•	Ground Level	N.A.	N.A.	N.A.		
	>	Discharge of main Pump	N.A.	N.A.	N.A.		
<b>*</b>	>	Head of Main Pump	N.A.	N.A.	N.A.		
	>	Number of main pumps	N.A.	N.A.	N.A.		
	>	Jockey pump out put	N.A.	N.A.	N.A.		
	>	Jockey pump head	N.A.	N.A.	N.A.		
	>	Standby pump out put	N.A.	N.A.	N.A.		
	>	Standby pump Head	N.A.	N.A.	N.A.		
		Auto Starting /Manual stopping	N.A.	N.A.	N.A.		
	>	Pump House Access	N.A.	N.A.	N.A.		
	•	Terrace Level					
	>	Discharge of pump	450 LPM	450 LPM	MR		
			40 m	40 m	MR		
	~	Head of the Pump	Required	Provided	MR		
	~	Power supply	Required	Provided	MR		
	>	Auto Starting of pump					

14	Captive Water Storage for Fire Fighting.			97.	
	Underground tank capacity	N.A.	N.A.	N.A.	
	Draw-off connection	N.A.	N.A.	N.A.	
	Fire service inlet	N.A.	N.A.	N.A.	
	Access to tank	N.A.	N.A.	N.A.	
	Overhead Tank capacity	10,000 Liters	10,000 Liters	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.			*	
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.	
	Pressurization of Lift lobby	N.A.	N.A.	N.A.	
	Communication in lift car	N.A.	N.A.	N.A.	
	Firemen's grounding switch	N.A.	N.A.	N.A.	
	Lift Signage	N.A.	N.A.	N.A.	
17	Standby power supply	N.A.	N.A.	N.A.	
18	Refuge Area.				
	Total area	N.A.	N.A.	N.A.	
	Location	N.A.	N.A.	N.A.	
19	Fire Control Room				
	Detector system panel	N.A.	N.A.	N.A.	
	Flow switch panel	N.A.	N.A.	N.A.	
	PA system panel	N.A.	N.A.	N.A.	
	Batter backup	N.A.	N.A.	N.A.	
	Building Floor Plans	N.A.	N.A.	N.A.	
20	Special Fire Protection systems for	N.A.	N.A.	N.A.	
		1			

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection. In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules. The NOC issued vide letter no. F.6/MS/DFS/2006/2422 Dated 11.09.2006 renewal under the circular no. F.16/Estate/CC/FS/2011/3298 to 3398 dated

1.3.11 is recommended fire safety certificate.

protection of special Risks, if any:

Signature of the Inspecting Officer 3 6 2015
Name:-R.K.Yadav

Designation:-ADO (LN)

DO(ED)