GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADOUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

Fax:-011-23412593

No. F.6/DFS/MS/GH/2015/ MOZ/97/

E-mail ID: cfohq.dlfire@nic.in

Dated: 9/6/15

FIRE SAFETY CERTIFICATE

Certified that the Pitrashish Premium Guest House (A unit of Pitrashish Aashrya Pvt. Ltd.) located at 59/36, New Rohtak Road, Karol Bagh, New Delhi-110005 comprises of Basement, Stilt, Ground floor + Three Upper floors, using basement as hall/storage, stilt floor as reception and parking, Ground floor having six guest room and one store, first, second & third floor each having six guest rooms respectively (Total 24 guest rooms) was granted NOC by this department vide letter No.F.6/DFS/MS/GH/2012/2645 dated 20-07-2012. The premises was re- inspected by the officer concerned of this department on 03-06-2015 in the presence of Mr. Avijit Bose (General Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 Guest House for 24 guest rooms with effect from -9-1-6-1---2015 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(**Dr. G.C. Misra**) Chief Fire Officer Delhi Fire Service Ph-011-23414333

Copy to:-

ou

1. The Joint Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049 w.r.t. letter No. 168/Joint C.P./Lic.(H) dated New Delhi 07-05-2015

2. Mr. Nishant Prakash (Owner), M/s Pitrashish Premium Guest House (A unit of Pitrashish Aashrva Pvt. Ltd.), 59/36, New Rohtak Road, Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

	INS	PECT	ION REPORT			
0	1. Name & address of the building : Pitrashish Premium, 59/36, New Rohtak Road, Karol Bagh,					
	C		New Delhi-110005.			
	2. Type of Occupancy				otal guest rooms-24	
	3. Type of Case		enewal		rtal gaest rooms 2 r	
	1. Details of Previous NOC			12/2645 dated 20	/07/2012	
	5. Fire Safety directives letter No		I/A	12/2015 dated 20/	07/2012	
	6. Date of inspection		3/06/2015			
	7. Name of Inspecting Officer		y. C.F.O Rajesh Pa	nwar		
	Name and designation of officers		y. c.i .o najesii i a	TIVV CI		
	From the building side		Sh. Avijit Bose (Gen	eral Manager)		
(P. Year of Construction		an 2010	iciai manager,		
	0. Applicant's letter No.			l) dt New Delhi 07/	05/2015	
S. No.	Minimum Standards on fire preve		NBC/BBL	Provided at site	Remarks	
3. 110.	and fire safety U/R 33	пион	Requirement	special area	MR/NMR	
1.	Access to building		Requirement	special alea	WINTYIN	
•	Road width		Accessible	18 mtr	MR	
	to state and the state of the s		NA	NA	NA	
	Gate width		NA NA	NA	NA	
	Width of internal road			11/1	11/1	
•	Number, Width, Type & Arranger	ment of	Exits			
	a. Number of staircases		7			
	Upper Floors		One	One	MR	
	• Basements		One	One	MR	
	b. Width of staircases					
			125 cms	150 cms	MR	
	Upper Floor		125 cms	150 cms	MR	
	• Basements		123 01118	130 0118	IVIIC	
	c. Protection of exits		27.1	37.	27.1	
	Fire check door		NA	NA	NA	
	TO SEC USE DESCRIPTION & LOSS OF CORP.		NA	NA	NA	
	Pressurization No. of continuous staircases to					
	CONTROL OF THE CASE OF THE CONTROL O		One	One	MR	
	e. Width of Corridor		1.0 Mtr	1.28, 2.40 Mtr	MR	
	c. Width of Corridor		1.0 1/161	1.20, 2.10 1111	1711	
	f. Door Size		48 100 100		20.0000	
	1. Door Size		1.0 Mtr.	86cm X 202 cm	MR, Old Case	
3.	Compartmentation					
•			NI.A	274	NTA.	
	Fire check door		NA	NA	NA	
	 Sealing of electrical shafts 		NA	Sealed	MR	
	 Fire Rating of shaft door 		NA	NA	NA	
	Water Curtain		NA	NA	NA	
	Fire Dampers		NA NA	NA NA	NA NA	
	Smoke Management System		INA	INA	INA	
•	Smoke Management System					
	 Basements 		30 ACPH	Exhaust Fans are	MR	
			10	provided Natural	MD	
	Upper floors		12 ACPH	Ventilation	MR	
				, chillation		
5.	Fire Extinguishers					
	Total numbers		Two at each floor	Provided	MR	
	 Types 		ABC, Water Co2	Provided	MR	
	IS marking		ICI	ISI marked	MR	
			ISI marked	101 marked	1711(
	First-Aid Hose Reels		One	Dung: 1 - 1	MD	
	Total numbers on each floor		One	Provided	MR	
	 Length of hose reel hose 		30 m	Provided	MR	
	Nozzle diameter		5 mm	Provided	MR	

•	Automatic fire detection and alarming sy	NA	NA	NA
	Type of detectorsLocation of Main Panel	NA NA	NA	NA
	Location of Main Panel Location of Repeater Panel	NA	NA NA	NA
	Alternate source of power		NA	NA NA
	Alternate source of power	NA -	NA	NA
	Hooters' Location	NA	1471	
•	MOEFA	Required	Provided	MR
	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System		D '1 1	MD A 1
	Basement	NA	Provided	MR, Area less than 200 Sq.m
	Ground Floor	NA	NA	NA
	 Sprinkler above false ceiling 	NA	NA	NA
1.	Internal Hydrants			
	Size of riser/down-comer	NA	NA	NA
	 Number of hydrants per floor 	NA	NA	NA
	Hose Box	NA	NA	NA
2.	Yard Hydrants		27.4	374
	 Total number of hydrants 	NA	NA	NA
	Hose Box	NA	NA	NA
3.	Pumping Arrangements			
	Ground Level	D.T.A.	NA	NA
	Discharge of main Pump	NA		200 100 100
	Head of Main pumpNumber of main pumps	NA	NA	NA
	> Jockey Pump out put	NA	NA	NA
	> Jockey pump head	NA	NA	NA
	Standby Pump out put	NA	NA	NA
	Standby Pump Head	NA	NA	NA
	Auto Starting/Manual	NA	NA	NA
	Stopping	NA	NA	NA
	Pump House Access			
	Terrace level	450 LPM	450 LPM	MR
	> Discharge of pump	30 M	30 M	MR
	Head of the pumpPower Supply	Required	Provided	MR
	> Auto Starting of pump	NA	NA	NA
	Auto starting or pamp	INA	IVA	NA NA
14.	 Captive Water Storage for fire fighting Underground tank capacity 	NA	NA	NA
	 Onderground tank capacity Draw-off connection 	NA	NA	NA
	> Fire service inlet	NA	Provided	MR
	> Access to tank	NA	NA	NA
	 Overhead Tank capacity 	5000 ltr	5000 ltr	MR
		Required	Provided	MR
15.	Exit Signage.	Required	Tiorided	
16.	Provision of Lifts.			
	Pressurization of Lift Shaft	NA	NA	NA
	Pressurization of Lift lobby	NA	NA	NA
	Communication In lift Car	Required	Provided	MR
	Fireman's Grounding Switch	Required	Provided	MR

17.	Standby power supply	Required	Provided	MR
2				
18.	Refuge Area.			
	> Total Area	NA	NA	NA
	> Location	NA	NA	NA
19.	Fire Control Room	NA NA	NA NA	NA NA
	PA System Panel	NA	NA NA	NA NA
	Batter backup			
		NA	NA	NA
	Building Floor Plans	NA	NA	NA
20.	Special Fire Protection System for Protection of special Risks, if any:	NA	NA	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2012/2645 dated 20.07.2012 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Signature of Inspecting Officer

Name:- Rajesh Panwar

Designation: - Dy. C.F.O (NDZ)

Signature of Inspecting Officer

Name

Designation