GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2015/ MOZ/958

Dated :- 3/6/15

FIRE SAFETY CERTIFICATE

Certified that the "Swisston Inn" Guest House located at 8433, Arya Nagar, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (01 guest room + reception + 01 store + shop), 1st floor to 2nd floor (08 guest rooms at each floor), 3rd floor (05 guest rooms + 01 room for personal use), 4th floor (06 guest rooms) and Terrace floor (01 staff room + kitchen for staff sealed) total 28 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/2668 dated 23/07/12. The premises was reinspected by the officer concerned of this department on 30/05/15 in the presence of Sh. Suresh Malik (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 28 guest rooms only with effect from --- 9-/-- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Are Service Rules 2010, printed below.

Issued -----at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Ph-011-23414333

Copy to:-

- of c Me The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. letter No. 154/Joint C.P./Lic.(H) dated 05/05/2015.
- 2. Sh. Suresh Malik (Owner),

Swisston Inn Guest House located at 8433, Arya Nagar, Pahar Ganj, New Delhi.

The Commissioner NDMC with a request to get height of the building measured and send intimation to this department. Reply of letter No. F.6/DFS/MS/GH/2009/1708 dated 16/06/2009 is still awaited.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSF	PECTION REPO				
1.	Name & address of the building:- "Swisston" Guest House located a					
	Arya Nagar, Pahar Ganj, New Delhi					
2.	Type of occupancy:-	Residential, Sub Division-A-1 Gr. + 04 Upper floors (total 28 Guest rooms)				
2	Truncafaca					
3. Type of case:- Renewal 4. Details of previous FSC:- No. F6/DFS/MS/GH/2012/26						
4,	Details of previous FSC:- No. F6/DFS/MS/GH/2012/2668 dated 23/07/12.					
5	Fire safety directives No	N/A				
	Date of inspection:-	30/05/15				
	Name of the inspecting officer					
	Name & designation of officer	· ·	(
	he building side:-		Malik (Owner)			
9.	Year of construction:-	Before 2009				
10.	Applicant's letter No:-	No. 154/Joint	C.P./Lic.(H) dated	05/05/2015.		
				Old Case		
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks		
	Prevention and fire safety	Existing	PSS	MR/NMR		
1	U/R 33					
1.	Access to Building					
	1) Road width	N/A	N/A	N/A		
	2) Gate width	N/A	N/A	N/A		
	3) Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr	angement of E	xits			
	A. Number of staircases			l l		
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase	·				
	1. Upper floors	0.80 mtr.	1.0 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	staircase to terrace		Te la company			
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
1	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 a/c per	N/A	N/A		
	Fire Extinguishers	hour				

5.

Fire Extinguishers

	1) Total numbers	12 Nos.	12 Nos.	MR
		ABC & CO2	ABC & CO2	MR
	2) Types 3) ISI marking	Required	Provided	MR
	First-Aid Hose Reel	100		
6.	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 m	30 m	MR
	3) Nozzle diameter	05 mm	05 mm	MR
-	Automatic Fire Detection &			
7.	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
0	MOEFA	Required	Provided	MR
8.		Required	Provided	MR
9.	Public Address System Automatic Sprinkler System			
10.	1) Basement	N/A	N/A	N/A
		N/A	N/A	N/A
	2) Upper floors3) Sprinkler above false	N/A	N/A	N/A
		14/12		
11	ceiling Internal Hydrants			
11.	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	1071		
		N/A	N/A	N/A
10	3) Hose box Yard Hydrants	11/11		
12.	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
12				
13.	Pumping Arrangement 1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
		14/11		_
	b) Head of main pump	N/A	N/A	N/A
	1 0		N/A	N/A
		•	N/A	N/A
	1 1	N/A	N/A	N/A
			N/A	N/A
	1 1		N/A	N/A
	g) Stand by pump head h) Auto starting/Manua		N/A	N/A
	stopping			
	2) Terrace level	3		
	a) Discharge of pump	225 LPM	225 LPM	MR
	b) Head of pump	18 mtr	18 mtr	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pum	1	Provided	MR
1.4	Captive Water Storage for			
14.	1) Under ground tank	N/A	N/A	N/A
1 3	1) Under ground tarik	- Annua an		

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A .	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DF\$/MS/GH/2012/2668 dated 23/07/2012 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)