GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. P6/DFS/MS/School/2015/1402/1032 Dated: 18/06/15-

FIRE SAFETY CERTIFICATE

Certified that the Evergreen Public School, C-32, Acharya Niketan Mayur Vihar, Phase-I, Delhi-91 comprised of ground floor plus two upper floors was granted NOC by this department vide Letter No- F6/MS/DFS/2006/1454 dated 03.07.2006. The school building was re-inspected by the officer concerned of this department on 12.06.2015 in the presence of Headmistress of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with the Circular No. 262-362 dated 17.01.2005 issued by the Director of Education and found that the building having GF+FF+SF is fit for occupancy Group B "Educational Building" with effect from ...]. 8./. o.6.//.s... renewed for a period of three years, subject to conditions printed overleaf.

Issued on 18/06/05 at New Delhi by

(Dr. G.C. Misra) Chief Fire Officer Ph -011- 23414333

07C8h

To,

The Principal

Evergreen Public School, C-32, Acharya Niketan Mayur Vihar, Phase-I, Delhi-91 Copy to:-.

The Director of Education,

East Delhi Municipal Corporation,

419, Udyog Sadan, Patparganj Industrial Area, Delhi-92

CONDITIONS:

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

	1.Name & address of the building : Evergreen Public School Con-						
	address of the building	8. Seri Ablic School, C-32 Acharya Niles					
	2. Building is comprised of	Widydi Villar, Phase-I, Delhi-91					
	3. Type of Occupancy 4. Type of Case Ground plus two upper floors Educational						
	5. Details of Previous NOC	: Renewal Ca					
1	5. Fire Safety diversity	: F6/MS/DF	S/2006/1454 dat	ted na c	7 2006		
	5. Fire Safety direction letter No	: Old require	ements (Circular	No 262	7.2006		
17	Old requirements (Circular No. 262-362 da 17.01.2005)						
8	7. Date of Inspection	: 12.06.2015					
9	Name of the Inspecting Officers:	: Suresh Singh	(ADO)				
	of the designation of Office	r	,				
110	from the building side	: Headmistre	SS				
	O. Year of Construction	: 2000					
11	1. Applicant's letter No	: EPS/MV/20	15/19 <mark>20 dated 0</mark>	11 00 00			
5.1	No Minimum Standards on	fire Requirer	ment Provided	1.06.20			
	safety requirements as	per	ment Provided	at Site	Remarks		
	circular no. 262-362 dated				MR/NMI		
-	17.01.2005)						
1	Access to building						
	Road width	6 m	10				
	Gate width	N.A	10 m		MR		
	Width of internal road	N.A	N.A		N.A		
2	Number, Width, Type and Arran	Gement of E	N.A		N.A		
	a. Number of Staircases	gement of Exit	S				
	Upper Floor	1					
	Basement	1 no.	2 no.		MR		
	B. Width of Staircases	N.A	N.A		N.A		
	Upper Floor						
	Basement	1.5 m	1.5 M, 1.10	m	MR		
	c. Protection of exits	N.A	N.A	-	N.A		
	Fire check door	N.A	N.A		V.A		
	Pressurization	N.A	N.A		V.A		
	e. No. of continuous staircases to	N.A	N.A		V.A		
	terrace	N.A.	N.A.				
	g. Width of Corridor				I.A.		
	h. Door Size	1.5 m	1.5 m	N	1R		
	· · · · · · · · · · · · · · · · · · ·	1 m	1 m		IR		
	Compartmentation. Fire check door			IV			
		N.A	N.A	N.	٨		
	Sealing of electrical shafts	N.A	N.A				
	Fire rating of shaft door	N.A	N.A	N.			
- 1	Water curtain	N.A	N.A	N.			
	Fire Dampers	N.A		N.	A		
	Smoke Management System.	IV.A	N.A	N.A	4		
E	Bacomont	200/-					
1	Innov fla	30a/c per hour 12a/c per hour	N.A	N.A			
1	PPCI IIOUI	17-/-	N.A				

5.	Fire Extinguisher Total numbers	06 no.	06 no.	MR				
	types	CO ₂ & ABC	CO ₂ & ABC	MR				
	IS marking	ISI marked	ISI marked	MR				
6	First-aid-Hose Reels.	131 Marked	131 marked	TVIIV				
	Total numbers of each floor	01 no.	01 no.	MR				
	Length of hose reel hose	30 m	30 m	MR				
	Nozzle diameter	5 mm	5 mm	MR				
7	Automatic fire detection and alarm	COL DESCRIPTION	3 111111	IVIIV				
	Type of detectors	N.A	N.A	N.A				
	Location of main panel	N.A	N.A	N.A				
	Location of repeater panel							
	Alternate source of power	N.A	N.A	N.A				
	Hooters	N.A	N.A	N.A				
J	A CONTRACTOR OF THE CONTRACTOR	N.A	N.A	N.A.				
8	MOEFA	N.A	N.A.	N.A.				
9	Public address System.	N.A	N.A.	N.A.				
10	Automatic Sprinkler System.	T						
	basement	N.A	N.A	N.A				
	upper floor	N.A	N.A	N.A				
	sprinkler above false ceiling	N.A	N.A	N.A				
11	Internal Hydrants							
	size of riser/down-comer	N.A	N.A	N.A				
	Number of hydrants per floor	N.A	N.A	N.A				
	Hose Box	N.A	N.A	N.A				
12	Yard Hydrants.	Yard Hydrants.						
	Total number of hydrants	N.A	N.A	N.A				
	Hose Box	N.A	N.A	N.A				
13	Pumping Arrangements.							
	Ground Level	N.A	N.A	N.A				
	Discharge of main Pump	N.A	N.A	N.A				
	Head of Main Pump	N.A	N.A	N.A				
	Number of main pumps	N.A	N.A	N.A				
	Jockey pump out put	N.A	N.A	N.A				
	Jockey pump head	N.A	N.A	N.A				
	Standby pump out put	N.A	N.A	N.A				
	Standby pump Head	N.A	N.A	N.A				
3 -	Auto Starting /Manual stopping	N.A	N.A	N.A				
	Pump House Access	N.A	N.A	N.A				
	Terrace Level		1					
	Discharge of pump	225 LPM	225 LPM	MR				
	Head of the Pump	40 m	Provided	MR				
	Power supply	Required	Provided	MR				
	Auto Starting of pump	Required	Provided	MR				
		Required	TTOVIGEG	With				

		(
14	Captive Water Storage for Fire Fighting.					
	Underground tank capacity	N.A	N.A	N.A		
	Draw-off connection	N.A	N.A	N.A		
	Fire service inlet	N.A	N.A	N.A		
	Access to tank	N.A	N.A	N.A		
	Overhead Tank capacity	2,500 Liters	2,500 Liters	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N.A	N.A	N.A		
	Pressurization of Lift lobby	N.A	N.A	N.A		
	Communication in lift car	N.A	N.A	N.A		
	Firemen's grounding switch	N.A	N.A	N.A		
	Lift Signage	N.A	N.A	N.A		
17	Standby power supply	N.A	N.A	N.A		
18	Refuge Area.					
	Total area	N.A	N.A	N.A		
	Location	N.A	N.A	N.A		
19	Fire Control Room					
	Detector system panel	N.A	N.A	N.A		
	Flow switch panel	N.A	N.A	N.A		
	PA system panel	N.A	N.A	N.A		
	Batter backup	N.A	N.A	N.A		
	Building Floor Plans	N.A	N.A	N.A		
20	Special Fire Protection systems for	N.A	N.A	N.A		
	protection of special Risks, if any:					

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules the NOC issued vide letter no. F6/MS/DFS/2006/1454 dated 03.07.2006 renewal under the Circular No. 262-362 dated 17.01.2005 is recommended.

Shigh 13.6.15 Signature of the Inspecting Officer

Name

Suresh Singh

Designation

ADO (Shah)

DO (EAST)

Submitted for approval please.