FORM 'H'
FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. f6/085/ms/sehool/2015/ w2/1093

Dated: 26/06/15

FIRE SAFETY CERTIFICATE

Certified that the **Guru Nanak Public School** Located at Pushpanjali Enclave, Pitampura, Delhi110034 comprised of Ground + 02 Upper Floors was issued FSC vide Letter No.
F6/DFS/MS/SCHOOL/2012/600 Dated 23-02-2012. The premises was re inspected by the officers concerned of this department on 3/06/2015 in the presence of **Sh. D Batra (AO)** and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance DOE Circular 262-362 dated 17-01-2005 and that the premises is fit for occupancy class "Educational" Group B with effect from 26/06/fs for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .2.6./.5... at New Delhi by.

(Santokh Singh) Chief Fire Officer PH 011-23414250

Copy to:

- 1. The Principal, Guru Nanak Public School, Pushpanjali Enclave, Pitampura, Delhi-110034 Following fire safety directives must be adhered to:-
 - 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
 - 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
 - 3. The trained staff should be available round the clock.
 - 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
 - 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
 - 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
 - 7. Basement shall be used strictly as per building bye laws.
 - 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

 Name & address of the building: Guru Nanak Public School Located as Pushpanjali Enclave, Pitampura, Delhi-110034

Type of Occupancy

: Educational (Ground + 2 Upper Floor)

• Type of Case

: Renewal

• Details of previous NOC: Lt. No. F6/DFS/MS/School/2012/600 Dated 23/2/12

• Fire Safety directives Letter No.: DOE Circular3298-3398 dated 01-03-2011

Date of inspection

: 03-06-2015

• Name of the Inspecting Officer: Udai Vir singh, ADO (WP)

Plot Area - 14016 M² Covered Area -5607 M² No. or Class Rooms-54 No. of Student- 1640

Name and designation of Officer

from the building side

:Sh. D Batra(AO)

Year of Construction

: 1989

• Applicant's letter No.

: Nil Dated -nil

S	Minimum standards on fire	DOE Cr	Provided at site	Rema	
N	prevention and fire safety U/R 33			-	
0	<u> </u>		7		
1.	Access of building				
	 Road width 	6mtrs	12 mtrs	MR	
	 Gate width 	4.5 mtrs	5 mtrs	MR	
	 Width of internal road 	3 mtrs	Provided	MR	
2.	Number, width, Type &		<u> </u>		
	Arrangements of exits				
	a. Number of staircases				
	 Upper floors 	2	4 Provided	MR	
	• Basements	NA	NA	NA	
	b. Width of staircases				
	 Upper floors 	2x1.5mtr	1x160cm,1x180cn,	MR	
			1x175cm	1,111	
			&1x110cm		
	Basement	NA	NA	NA	
	c. Protection of exits				
	Fire check door	NR	NR	MR	
	Pressurization	NR	NR	NA	
	d. No of continuous	one,	One Provided	Old	
	staircase toterrace	lu _s		case	
	e. Width Of Corridor	2 mtrs	Provided	MR	
	f Door Size	1			
		1 mtr	Varies from 95cm	Old	
			to 100cm	case	

4. Si 5. Fi 6. Fi	 ompartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers moke managements System Basements Upper floors ire Extinguishers Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	NA NA NA NA NA NA NA NA Solution NA NA NA NA ABC & CO ₂ ISI marked	NA NA NA NA NA NA NA Provided Provided Provided Provided	NA MR
5. Fi 6. Fi	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers moke managements System Basements Upper floors ire Extinguishers Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	NA NA NA NA NA NA ABC & CO ₂ ISI marked	NA NA NA NA NA NA Provided Provided Provided	NA NA NA NA NA NA MR
5. Fi	 Fire Rating of shaft door Water Curtain Fire Dampers moke managements System Basements Upper floors ire Extinguishers Total numbers Types IS marking irst – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	NA NA NA NA NA ABC & CO ₂ ISI marked	NA NA NA NA NA Provided Provided Provided	NA NA NA NA NA NA MR
5. Fi	 Water Curtain Fire Dampers moke managements System Basements Upper floors ire Extinguishers Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	NA NA NA NA 20 nos. ABC & CO ₂ ISI marked	NA NA NA NA Provided Provided Provided	NA NA NA NA NA MR
5. Fi	 Fire Dampers moke managements System Basements Upper floors ire Extinguishers Total numbers Types IS marking irst – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	NA NA NA 20 nos. ABC & CO ₂ ISI marked	NA NA NA Provided Provided Provided	NA NA NA MR MR
5. Fi	 moke managements System Basements Upper floors ire Extinguishers Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	NA NA 20 nos. ABC & CO ₂ ISI marked	NA NA Provided Provided Provided	NA NA MR MR
5. Fi	 Basements Upper floors Total numbers Types IS marking Total numbers on each floor Length of hose reel hose 	NA 20 nos. ABC & CO ₂ ISI marked	Provided Provided Provided	NA MR MR
6. F	 Upper floors ire Extinguishers Total numbers Types IS marking irst – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	NA 20 nos. ABC & CO ₂ ISI marked	Provided Provided Provided	MR MR
6. F	 Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	20 nos. ABC & CO ₂ ISI marked	Provided Provided Provided	MR MR
6. F	 Total numbers Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	ABC & CO ₂ ISI marked	Provided Provided	MR
7. A	 Types IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	ABC & CO ₂ ISI marked	Provided Provided	MR
7. A	 IS marking First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 	ISI marked	Provided	
7. A	 First – Aid Hose Reels Total numbers on each floor Length of hose reel hose 			TVIIC
7. A	Total numbers on each floorLength of hose reel hose	3	Provided	
	floor Length of hose reel hose	3	Provided	MR
2.00	 Length of hose reel hose 			IVIK
2.14	3 T 1 1'	30m	Provided	MR
2.00	 Nozzle diameter 	5mm	Provided	MR
a	Automatic fire detection and larming system			
	Type of detectors	NA	NA	NA
	 Location of Main Panel 	NA	NA	NA
	 Location of Repeater Panel 	NA	NA	NA
	All of several of marriage	NA	NA	NA
	Alternate source of powerHooters' Location	NA	NA	NA
8. N	MOEFA	Required	Provided	MR
	Public Address System	Required	Provided	MR
	Automatic Sprinkler System			
	Basements	NR	NR	NA
	Upper Floor	NR	NR	NA
	 Sprinkler above false ceiling 	NR	NR	NA
11.	Internal Hydrants:			
	Size of riser/down- comer	NA	Provided 100 mtrs	NA
	NY 1 C1 Junto man	NA	Provided	NA
	floor	NA	Provided	NA
	Hose Box Yard Hydrants			
12.		NA	Provided	NA
12.	 Total number of hydrants 	1111	110,100	TITE

13.	Pumping Arrangements:				
	Ground Level				
	Discharge of main pump	NA	NA	NA	
	Head of main pump	NA	NA	NA	
	Number of main pumps	NA	NA	NA NA	
	> Jockey pump out put	NA	NA	NA NA	
	> Jockey pump head	NA	NA	NA NA	
	> Standby Pump out put	NA	NA	NA NA	
	Standby Pump Head	NA	NA	NA	
	Auto Staring/Manual stopping	NA	NA	NA	
	Pump House Access	NA	NA	NA	
	Terrace level			1111	
	Discharge of pump	450 LPM &220lpm	Provided	MR	
	> Head of the pump	40Mtr	Provided	MR	
	> Power supply	Required	Provided	MR	
	> Auto starting of pump	Required	Provided	MR	
14.	Captive water Storage for fire fighting:			1.111	
	 Under ground tank 	NA	NA	NA	
	capacity	NA	NA	NA	
	Draw off connection	NA	NA	NA	
	> Fire service inlet	NA	NA	NA	
	Access to tankOverhead Tank capacity	5,000Ltr	Provided (15000 ltrs)	MR	
15	Exit Signage	Required	Provided	MR	
16.	Provision of Lifts				
	Pressurization of Lift Shaft	NA	NA	NA	
	Pressurization of lift lobby	NA	NA	NA	
	Communication in lift Car	NA	NA	NA	
	Fireman's Grounding Switch	NA	NA	NA	
1.5	➤ Lift Signage	NA	NA	NA	
17. 18.	Standby power supply Refuge Area	NA	NA	NA	
	> Total area	NA	NA	NA	
	> Location	NA	NA	NA NA	
19.	Fire control room	_ ,,,,	11/1	IVA	
	Detector system panelFlow Switch Panel	NA	NA	NA	
	PA System Panel	NA	NA	NA	
	Battery backup	NA	NA	NA	
	Building Floor Plans	NA	NA	NA	

any;	20. Special Fire Protection Systems for Protection of special Risks, i	f NA	NA	NA -	

1	Note:-	General	requirements	for	schools	as	per	Director	of	Education	circular
	1	Fecane	route				CI.				

- 2. LPG cylinders in laboratories Kept in LPG Bank at terrace
- 3. Electric wiring ... Conduit Wiring...... MCB and ELCB Electric circuit
- 4. Electric meter boardNot under the staircase.....
- 5. Basement use as per BBL 1983 ... NA
- 6. Emergency telephone no. board ...Displayed....
- 7. Generator setNil....

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2012/600 Dated 23/02/2012 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Instituting Officer

Signature of the Inspecting

Officer

Name Odor Vir Sigh Designation Abo/wp

Name

Designation

