GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2015/ W2 /128/

FIRE SAFETY CERTIFICATE

Issued on 17/07/15 at New Delhi by.

(SANTOKH SINGH) CHIEF FIRE OFFICER

Dated: 17/07/2015

PHONE:23414250

Copy to

1. Sarna International Pvt. Ltd., Plot No. G-15, Udyog Nagar Industrial Area, Rohtak Road, New Delhi-41.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc. shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provision of building bye laws.
- 6. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on www.dfs.delhigovt.nic.in

HIGH BUTTOTT TREET OFFI

1. Name & address of the building: Sarna International pvt. Ltd. Plot No. G-15, Udyog

Nagar Industrial Area, Rohtak Road, New Delhi-41

2. Type of Occupancy : Industrial

ndustrial Basement + GF+ Mez.

3. Type of Case : Renewal

4. Details of previous NOC : No.F6/DFS/MS/BP/92/243 dated 25.02.1992

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/85/512 dated 25.05.1985

6. Date of inspection : 24/06/2015

7. Name of the Inspecting Officer: A. K.-Jaiswal

8. Name and designation of Officer

from the building side : Mr. Sharma (Manager)

9. Year of Construction : 1985-86

10. Applicant's letter No.: -Nil Dated 28/5/2015

S	Minimum standards on fire	BBL	Provided at	Remarks			
No	prevention and fire safety U/R 33	Requirements	site	MR/NMR			
1.	Access of building						
	Road width	06 mtr	15 mtr.	MR			
	Gate width	4.5 mtr	Provided	MR			
	Width of internal road	3 mtr.	Provided	MR			
2.	Number, width, Type & Arrangements of exits						
	a. Number of staircases						
	Upper floors	2	2	MR			
	Basements	2	2	MR			
	b. Width of staircases						
	Upper floors	1.20	Provided	MR olg			
	Basements	1.20	Provided	MR			
	c. Protection of exits						
	Fire check door	Required	Provided	MR			
	Pressurization	N/A	N/A	N/A			
	d. No of continuous	As per sanctioned	1	MR			
	staircase to terrace	plan					
	e. Width Of Corridor	N/A	N/A	N/A			
	f. Door Size	1.00mtr	Provided	MR			
3.	Compartmentation						
	• Fire check door	Required	Provided	MR			
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire Rating of shaft door	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers						
4.	Smoke managements System		.00				
	Basements	Required	Provided	MR			
	Upper floors	N/A	N/A	N/A			
5.	Fire Extinguishers						
	Total numbers	10	15	MR			
	Typeg	ISI marked	Provided	MR			

6.	First – Aid Hose Reels				
	Total numbers on	2	Provided	MR	
	each floor				
	• Length of hose reel	30Mtr.	Provided	MR	
	hose			· · · · · · · · · · · · · · · · · · ·	
	 Nozzle diameter 	5mm.	Provided	MR	
		<u> </u>			
7.	Automatic fire detection and a		D1/0	D1/0	
	• Type of detector	N/A	N/A	N/A	
	 Location of Main Panel 	N/A	N/A	N/A	
	Location of Repeater	N/A	N/A	N/A	
	• Panel	N/A	N/A	N/A	
	Alternate garries of	N/A	N/A	N/A	
	• Alternate source of power	IN/ A	N/A	IN/ A	
	Hooters' Location	N/A	N/A	N/A	
8.	MOEFA	N/A	N/A	N/A	
9.	Public Address System	N/A	N/A	N/A	
10.	Automatic Sprinkler System	1.7,	1/, .	,, .	
	Basements	Required	Provided	MR	
	Upper Floor	N/A	N/A	N/A	
	Sprinkler above false	N/A	N/A	N/A	
	ceiling				
11.	Internal Hydrants				
	Size of riser/down-	N/A	N/A	N/A	
	comer				
	Number of hydrants	N/A	N/A	N/A	
	per floor				
	Hose Box	N/A	N/A	N/A	
12.	Yard Hydrants				
	Total number of	N/A	N/A	N/A	
	hydrants				
	Hose Box	N/A	N/A	N/A	
13.	Pumping Arrangements				
•	Ground Level	N/A			
•	 Discharge of main pump 	N/A	N/A	,	
	Head of main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	Jockey pump out put	N/A	N/A	N/A	
	Jockey pump headStandby Pump out put	N/A N/A	N/A N/A	N/A N/A	
	Standby Pump out putStandby Pump Head	N/A	N/A	N/A N/A	
	Auto Staring/Manual	N/A	N/A	N/A	
	stopping		,		
7	Pump House Access	N/A	N/A	N/A	
•					
>	Discharge of pump	900Lit/min.	Provided	MR	
7	Head of the pump	30 mtr.	Provided	MR	
,	Power supply	Required	Provided	MR	
7	Auto starting of pump	Required	Provided	MR	
14.	Captive water Storage for fire	fighting	<u> </u>		
	Underground tank	52,000 lts.	Provided	M/R	

15	Exit Signage	Required	Provided	M/R	
16.	Provision of Lifts	•			
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of lift lobby	N/A	N/A	N/A	
	Communication in lift Car	N/A	N/A	N/A	
	Fireman's Grounding Switch	N/A	N/A	N/A	
	Lift Signage	N/A	N/A	N/A	
17.	Standby power supply	required	Provided	MR	
18.	Refuge Area	N/A	N/A		
	Total area	N/A	N/A	N/A	
	Location	N/A	N/A	N/A	
19.	Fire control room				
	Detector system panel	N/A	N/A	N/A	
	Flow Switch Panel	N/A	N/A	N/A	
	PA System Panel	N/A	N/A	N/A	
	Battery backup	N/A	N/A	N/A	
	Building Floor Plans	N/A	N/A	N/A	
20.	Special Fire Protection Systems for Protection of special Risks, if any;	N/A	N/A	N/A	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. MCB and Conduit Metal Wiring has also been provided.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No.F6/DFS/MS/BP/92/243 dated 25.02.1992 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended..

Signature of the Inspecting Officer

Name : Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)