GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2015/ W2/1279

Dated: 17 / 07 /2015

FIRE SAFETY CERTIFICATE

Certified that Sh. S. K. Gupta at Plot No. H-48, Udyog Nagar Industrial Area, Rohtak Road, New Delhi-41 comprised of Ground Floor, Mezzanine Floor and First Floor only was issued Fire Safety Certificate vide letter No. F6/DFS/MS/BP/87/617 dated 20.05.1987. The Premises / Building now owned / occupied by S. G. Engineers. The premises / Building was reinspected by the officer concerned of Fire Service on 24.06.2015 in the presence of Mr. Shyam Mohan Gupta and found that building / premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building / premises is fit for occupancy class Industrial Group (G) with effect from 17/67 /2015 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Issued on 17/07/15 at New Delhi by.

(SANTOKH SINGH) CHIEF FIRE OFFICER

PHONE:23414250 PM

Copy to :-

1. Mr. Shyam Mohan Gupta, S. G. Engineers, Plot No. H-48, Udyog Nagar Industrial Area, Rohtak Road, New Delhi-41

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc. shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: S. G. Engineers, Plot No. H-48, Udyog

Nagar Industrial Area, Rohtak Road, New Delhi-41

2. Type of Occupancy

: Industrial

 $(Plot Area - 1052m^2)$

3. Type of Case

: Renewal (GF, Mezz. Floor & 1st Floor)

4. Details of previous NOC

: No.F6/DFS/MS/BP/87/617 dated 20.05.1987

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/85/574 dated 25.05.1985

Date of inspection

: 24/06/2015

7. Name of the Inspecting Officer: A. K.-Jaiswal

8. Name and designation of Officer

from the building side : Mr. Shyam Mohan Gupta

9. Year of Construction

: 1985-86

10. Applicant's letter No. :-Nil

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site	Remarks MR/NMR		
1.	Access of building					
	Road width	06 mtr	15 mtr.	MR		
	Gate width	4.5 mtr	Provided	MR		
	Width of internal road	3 mtr.	Provided	MR		
2.	Number, width, Type & Arrangements of exits					
	a. Number of staircases					
	Upper floors	2	2	MR		
	Basements	NA	NA	NA		
	b. Width of staircases					
	Upper floors	1.20	Provided	MR		
	Basements	1.20	Provided	MR		
	c. Protection of exits					
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	d. No of continuous	As per sanctioned	1	MR		
	staircase to terrace	plan				
	e. Width Of Corridor	N/A	N/A	N/A		
	f. Door Size	1.00mtr	Provided	MR		
3.	Compartmentation					
	Fire check door	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	• Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	• Fire Dampers	N/A	N/A	N/A		
4.	Smoke managements System					
4.	Basements	N/A	N/A	N/A		
	Upper floors	N/A	N/A	N/A		
5.	Fire Extinguishers					
	Total numbers	10	15	MR		

0.	Total numbers on	2	Provided	MR		
	each floor					
	Cach floor					
	 Length of hose reel 	30Mtr.	Provided	MR		
	hose			NAD		
	Nozzle diameter	5mm.	Provided	MR		
1						
7.	Automatic fire detection and al	arming system				
1.	Type of detector	N/A	N/A	N/A		
	Location of Main	N/A	N/A	N/A		
	Panel			N/A		
	 Location of Repeater 	N/A	N/A	N/A		
	• Panel	N/A	N/A			
	Alternate source of	N/A	N/A	N/A		
	power					
		NI/A	N/A	N/A		
	Hooters' Location	N/A				
8.	MOEFA	N/A	N/A	N/A N/A		
9.	Public Address System	N/A	N/A	IN/ A		
10			Provided	MR		
	Basements	Required	N/A	N/A		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false	N/A	IV/A			
	ceiling					
1	Internal Hydrants					
1	Size of riser/down-	N/A	N/A	N/A		
	comer					
	Number of hydrants	N/A	N/A	N/A		
	per floor					
	Hose Box	N/A	N/A	N/A		
1	2. Yard Hydrants	NI/A	N/A	N/A		
	Total number of	N/A	14/ 🖰			
	hydrants	N/A	N/A	N/A		
	Hose Box	IV/A				
1	3. Pumping Arrangements	N/A	N/A			
	Ground Level Groin nump	N/A	N/A			
	Discharge of main pump	N/A	N/A	N/A		
	Head of main pumpNumber of main pumps	N/A	N/A	N/A		
	Jockey pump out put	N/A	N/A	N/A		
	> Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	> Standby Pump Head	N/A	N/A	N/A		
	Auto Staring/Manual	N/A	N/A	N/A		
	stopping	N1/0	N/A	N/A		
	> Pump House Access	N/A	IV/ A	1.7,7		
	Terrace level	0001:1/:-	Provided	MR		
	> Discharge of pump	900Lit/min.	Provided	MR		
	> Head of the pump	30 mtr.	Provided	MR		
	> Power supply	Required	Provided	MR		
	Auto starting of pump	Required	Provided	IVIIX		
	G. C. Fine fighting					
	Captive water Storage for II Underground tank	50,000 lts.	Provided	M/R		
1	capacity					
To Me	Capacity		Dided	M/R		

	14/10				
Exit Signage	Required	Provided	M/R		
Provision of Lifts					
	N/A	N/A	N/A		
Pressurization of lift	N/A	N/A	N/A		
Communication in lift	N/A	N/A	N/A		
Fireman's Grounding	N/A	N/A	N/A		
> Lift Signage	N/A	N/A	N/A		
Standby power supply	required	Provided	MR		
	N/A	N/A			
	N/A	N/A	N/A		
	N/A	N/A	N/A		
Fire control room					
	N/A	N/A	N/A		
	N/A	N/A	N/A		
	N/A	N/A	N/A		
		N/A	N/A		
		N/A	N/A		
Special Fire Protection Systems for Protection of	N/A	N/A	N/A		
	 Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans Special Fire Protection 	Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage N/A Standby power supply Refuge Area N/A Total area N/A Location Fire control room Poetector system panel PA System Panel PA System Panel PA System Panel PA System Panel Patient Systems for Protection Systems for Protection of	Exit Signage Provision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage N/A Standby power supply Refuge Area Total area Total area N/A Location Pier control room Detector system panel Patients N/A N/A N/A N/A N/A N/A N/A N/		

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. MCB and Conduit Metal Wiring has also been provided.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No.F6/DFS/MS/BP/87/617 dated 20.05.1987 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Ak Jousoal 2416/15

Name : Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)