GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ ND2 1239

Dated: 13 67 15

FIRE SAFETY CERTIFICATE

Certified that the New Shalimar Guest House located at 5611,Basant Road.Pahar Ganj,New Delhi-110055.comprised of Ground + 1 Upper Floors (Ground floor – reception + 02 guest rooms & 1st 02 guest rooms total 04 guest rooms was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/1927 dated 28/05/2012. The premise was re-inspected by the officer concerned of this department on 08/06/15 in the presence of Mr. Diwan Chand (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 04 guest rooms only at ground & 1st floor as above with effect from [3/57].

- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 13 | 97 | 15 at New Delhi by.

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service Ph – 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,
New Shalimar Guest House, 5611, Basant Road. Pahar Ganj, New Delhi-110055.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSPEC	TION REPORT			_			
	Now Chalimar (filest House, 3011, Dasant							
1.Na	Road Pahar Gani, New Delhi-110033.							
Residential Group A-1 Ground								
2. Type of occupancy:- + 1 Upper Floors.(04 guest rooms)								
2 7	Toron of aggain	Danayya						
3.	Type of case:-	No. F6/MS/D	Vo. F6/MS/DFS/GH/2012/1927 dated					
4. 1	4. Details of previous FSC:- No. F6/MS/DFS/GH/2012/1927 dated 28/05/2012.							
5.	5. Fire safety directives ito.							
6.	6. Date of inspection:- 7. Name of the inspecting officer:- 7. Name of the inspecting officer:-							
7.	/. Name of the insertion of officer							
8.	8. Name & designation of officer From the building side:- Mr. Diwan Chand (Manager)							
	Year of construction:-				105/1	_		
9.	Year of constitution.	204/Joint.C.	P./Lic.	(H) Dated 1	1/05/1	5		
10.	Applicant's letter No:-				Ola	ase		
	Minimum Standards on fire	Requirement	Prov	ided at site	Rema			
S.No.	Prevention and fire safety	(Existing)	PSS		MR/I	NMR		
	U/R 33	¥						
1.	Access to Building	N/A	2 mt	r.	N/A			
	1) Road width	N/A	N/A		N/A			
	2) Gate width		N/A		N/A			
	3)Width of internal road	N/A						
2.	Number, Width Type & Arran	gement of Exits						
	A. Number of staircases		011	No.	MR	4		
	1. Upper floors	01 No			N/A			
	2. Basements	N/A	N/1	A	14/12			
	B. Width of staircase		00		MR			
	1. Upper floors	80 cms.	80 cms.		N/A			
	2. Basements	N/A	N/A	A	14/1			
	C. Protection of exits		21/	N/A N/A		I		
	1. Fire check door	N/A				A		
	2. Pressurization	N/A						
	D. No. of continuous	N/A	N/	A	N/2	1		
	staircase to terrace				N/	٨		
	E. Width of corridor	N/A	N/.		MI			
	F. Door size	1 mtr.	1 r	ntr.	IVI			
3.	Compartmentation				3.77	٨		
3.	1) Fire check door	N/A	N/		N/	1		
	2) Sealing of electrical shafts			'A	N/			
	3) Fire rating of shaft door	N/A		/A	N/A			
	4) Wester curtain	N/A	N	/A	N/A			
	4) Water curtain	N/A	N	/A	N.	/A		
	3) FILE Dallipois							
4.	Smoke Management System	30 ACPH		N/A		N/A		
1) Basements		12 ACPH		Natural		MR		
	2) Upper floors	12 110111						
5.	Fire Extinguishers	04 Nos.		04 Nos.		MR		
	1) Total numbers	ABC & CO2		ABC &CO2		MR		
	2) Types	ADC & CO						
						h		

	3) ISI marking	Required	Provided				
6.	First-Aid Hose Reel	1					
	1)Total number at each floor	01 no.	01 no.	MR			
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
	3) Nozzle diameter	5 mm.	5 mm.	MR			
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System	N/A N/A		N/A			
10.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false ceiling	N/A	N/A	N/A			
11.	Internal Hydrants						
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per floor	N/A	N/A	N/A			
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement						
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main pump	N/A	N/A	N/A			
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pump	N/A	N/A	N/A			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump output	N/A	N/A	N/A			
	g) Stand by pump head	N/A	N/A	N/A			
	h) Auto starting/Manual stopping	N/A	N/A	N/A			
	2) Terrace level						
	a) Discharge of pump	180 LPM	180 LPM	MR			
	b) Head of pump	30 Mtr.	30 Mtr.	MR			
	c) Power supply	Required	Provided	MR			
	d) Auto starting of pump	Required	Provided	MR			
4.	Captive Water Storage for Fire		220.1000	1.11			
	Under ground tank capacity	N/A	N/A	N/A			
	a) Draw-off connection	N/A	N/A	N/A			

-/7

, 1

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltrs.	2,500 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	N/A		

. The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/MS/DFS/GH/2012/1927 dated 28/05/2012, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

DY. CFØ (NDZ)