GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ MD2/1240

Dated: 43 67 15

FIRE SAFETY CERTIFICATE

Certified that the Janta South Indian Lodge located at 4247,Tel Mandi,Pahar Ganj,New Delhi-110055.comprised of Ground + 3 Upper Floors (Ground floor – reception, 1st floor - 04 guest rooms, 2nd floor – 05 guest rooms, 3rd floor – 05 guest rooms & terrace – temporary tin shed for staff total 14 guest rooms) was granted FSC by this department vide letter No.F6/MS/DFS/GH/2012/3345 dated 12/09/2012. The premise was re-inspected by the officer concerned of this department on 06/07/15 in the presence of Mr. Parvesh Thakur (Proprietor) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 for 14 guest rooms only at 1st to 3rd floor as above with effect from - 12 - 27 + 27 - ------- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued --- 13 07 15 -at New Delhi by.

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,
Janta South Indian Lodge, 4247, Tel Mandi, Pahar Ganj, New Delhi-110055.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		- M-1	2		
	INSP	ECTION REPOR	RT		
1.1	Name & address of the building:-	Janta South	Indian Lodge,4247	Tel Mandi,	
			New Delhi-110055		
2.	Type of occupancy:-	Residential	Group A-1Ground		
			loors & terrace – te	emporary tin	
		shed.(14 gue		1	
3.	Type of case:-	Renewal	,		
4.	Details of previous FSC:-	No. F6/MS/	DFS/GH/2012/334	5 dated	
	P	12/09/2012.			
5.	Fire safety directives No	N/A			
6.	Date of inspection:-	06/07/15			
7.	Name of the inspecting officer:	- D.O. Gurmu	kh Singh		
8.	1				
	From the building side:-	Mr. Parvesh	Thakur (Proprietor	r)	
9.	Year of construction:-		(F	-)	
	Applicant's letter No:- 651/Joint.C.P.Lic (H) Dated 09/06/15				
10.	rippiredit b letter 1 (o.		1.210 (11) 2 400 4 0 9	Old Case	
No.	Minimum Standards on fire	Requirement	Provided at site	Remarks	
	Prevention and fire safety	(PSS Area)	PSS	MR/NMR	
	U/R 33				
,	Access to Building				

S.No.	Minimum Standards on fire Prevention and fire safety	Requirement (PSS Area)	Provided at site PSS	Remarks MR/NMR	
	U/R 33				
1.	Access to Building				
	1) Road width	N/A	2 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arran	gement of Exits			
	A. Number of staircases				
	1. Upper floors	01 No.	01 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	80 cms.	87 cms.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace				
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers				
	1) Total numbers	10 Nos.	10 Nos.	MR	

	2) Types	ABC & CO2	ABC &CO2	_			
	3) ISI marking	Required	Provided	M			
	First-Aid Hose Reel						
	1)Total number at each	01 no.	01 no.	MR			
	floor	X					
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
	3) Nozzle diameter	5 mm.	5 mm.	MR			
'.	Automatic Fire Detection & A	larming System					
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
3.	MOEFA	N/A	N/A	N/A			
).	Public Address System	N/A	N/A	N/A			
0.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling						
1.	Internal Hydrants						
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor						
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants		'				
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
3.	Pumping Arrangement						
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
	pump						
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pum		N/A	N/A			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump output		N/A	N/A			
	g) Stand by pump head	N/A	N/A	N/A			
	h) Auto starting/Manual		N/A	N/A			
	stopping	9					
	2) Terrace level						
	a) Discharge of pump	180 LPM	180 LPM	MR			
	b) Head of pump	30 Mtr.	30 Mtr.	MR			
	c) Power supply	Required	Provided	MR			
			Provided	MR			
	d) Auto starting of numi) Rediffed	Captive Water Storage for Fire Fighting				
14	d) Auto starting of pump		11011404				
14.			N/A	N/A			

-M-19

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltrs.	2,500 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	•		
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
17.	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Systemany:	em for Protection	n of special Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/MS/DFS/GH/2012/3345 dated 12/09/12, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

Gurmukh Singh Divisional Officer

DY. CFO (NDZ)