GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2015/ NO2) 1249

Dated: 14/07/15

FIRE SAFETY CERTIFICATE

Issued - 19/07/13 at New Delhi by.

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service Ph: - 011-23414333

Copy to: (1) The Joint Commissioner of Police (Lic.), 1st Floor, Police Station, Defence Colony, New Delhi.

(2) The Licensee,
Great Shiva Dx. Guest House,
2896, Sangatrashan, Pahar Gani, New Delhi-110055.

Conditions:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1.Name & address of the building:-Great Shiva Dx. Guest House, 2896,

Sangatrashan, Pahar Gani, New Delhi-110055.

2. Type of occupancy:-Residential Group A-1 Ground

+ 4 Upper Floors.(19 guest rooms)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/MS/DFS/GH/2012/3143 dated

29/08/2012.

5. Fire safety directives No.-

N/A 6. Date of inspection:-06/07/15

7. Name of the inspecting officer:-D.O. Gurmukh Singh

8. Name & designation of officer From the building side:-

Mr. N.K. Mishra.

9. Year of construction:-

595/Joint.C.P.Lic (H) Dated 05/06/15 10. Applicant's letter No:-

				Old Case		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement (PSS Area)	Provided at site PSS	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	6 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arran	gement of Exits				
	A. Number of staircases					
	1. Upper floors	01 No.	01 No.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	80 cms.	1.25 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace		×			
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	10 Nos.	10 Nos.	MR		
	2) Types	ABC & CO2	ABC &CO2	MR		

M-13

	3) ISI marking	Required	Provided	M			
6.	First-Aid Hose Reel						
	1)Total number at each floor	01 no.	01 no.	MR			
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
	3) Nozzle diameter	5 mm.	5 mm.	MR			
7.	Automatic Fire Detection & Alarming System						
	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			
	4) Alternate source of power	N/A	N/A	N/A			
	5) Hooter's Location	N/A	N/A	N/A			
8.	MOEFA	N/A	N/A	N/A			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling		- " - "	1771			
11.	Internal Hydrants						
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor			1071			
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement			1771			
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main	N/A	N/A	N/A			
	pump	11/11	14/11	IVA			
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pump		N/A	N/A			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump output	N/A	N/A	N/A			
	g) Stand by pump head	N/A	N/A	N/A			
	h) Auto starting/Manual	N/A	N/A	N/A N/A			
	stopping	14/11	IVA	IN/A			
	2) Terrace level						
	a) Discharge of pump	225 LPM	225 LPM	MR			
	b) Head of pump	30 Mtr.	30 mtr.	MR			
	c) Power supply	Required	Provided	MR			
	d) Auto starting of pump	Required	Provided	MR			
14.	Captive Water Storage for Fire		Tiovided	IVIK			
14.	1) Under ground tank	N/A	N/A	NI/A			
	capacity	11/11	IN/A	N/A			
	a) Draw-off connection	N/A	N/A	N/A			
	, and a solution	- 1/	11/11	14/11			

21-14

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A N/A
	d) Over head tank capacity	2,500 ltrs.	2,500 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			1111
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	n for Protection of s	pecial Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/MS/DFS/GH/2012/3143 dated 29/08/12, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended

DY. CFO (NDZ)

6000

Gurmukh Singh
Divisional Officer